



JKL PART NUMBER	LENGTH A +/- 2mm	COLOR 5200° KELVIN	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m <sup>2</sup> )	*RATED LIFE (HRS)
BF8300-20A	300mm	LCD HIGH OUTPUT WHITE	1200	390	5 ± 1	4,000	20,000

\* NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

	METRIC	DIMENSIONS ARE IN MILLIMETERS	<b>JKL COMPONENTS CORPORATION</b>						
	THIRD ANGLE PROJECTION	TOLERANCE UNLESS OTHERWISE SPECIFIED					TITLE		
		1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0	DUAL LEAD LOW PROFILE TIP TYPE HIGH OUTPUT WHITE MINIATURE FLUORESCENT						
RELEASED	8/12/03	DRAWN BY L. WENGSTROM	APP'VD BY DATE J.K. 8/12/03	SIZE <b>A</b>	FSCM NO. <b>55335</b>	DRAWING NO. <b>BF8300-20A</b>			
REV. NO.	DESCRIPTION/ECO NUMBER	APP'VD DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE <b>NONE</b>	RELEASED DATE <b>8/12/03</b>	REVISION DATE	REV. NO.	SHEET <b>1 of 1</b>