


TP 12T

Order No.: 2985194




<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2985194>

Touch panel with 12.1" graphics-capable TFT display, 65535 colors x 800 X 600 pixels, 1x Ethernet, 2x USB and integrated runtime of the Visu+ visualization software.

Commercial data	
GTIN (EAN)	 4 046356 117203
sales group	K310
Pack	1 pcs.
Customs tariff	84714100
Catalog page information	Page 135 (AX-2009)

Product notes

WEEE/RoHS-compliant since:
05/11/2010



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
Display data	
Display	30.7 cm/12.1" TFT active
Resolution	800 x 600 Pixel
Touch screen	Resistive industrial touch screen
Colors	65,536 colors

Computer data

Processor	Xscale PXA320, 806 MHz
Main memory	128 MByte SDRAM
Data memory	256 Mbyte external Compact Flash card for applications
Interfaces	10/100 MBit Ethernet; 2 x USB Host 1.1
Operating systems	Windows CE 5.0

General data

External dimension, width	340 mm
External dimension, height	270 mm
External dimension, depth	5 mm
Note regarding external dimension	Dimensions of the front plate
Installation dimension, width	315 mm
Installation dimension, height	243.5 mm
Mounting type	Installation in front plate

Ambient Conditions

Degree of protection	IP65 (front), IP20 (back)
Ambient temperature (operation)	0 °C ... 50 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C
Permissible humidity (operation)	20 % ... 85 % (no condensation)
Permissible humidity (storage/transport)	10 % ... 95 % (no condensation)
Vibration (operation)	DIN EN 60068-2-6
Shock	DIN EN 60068-2-27

Certificates / Approvals

Certification

ABS, BV, CUL Listed, GL, UL Listed

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;