


TP 07T

Order No.: 2913085




<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2913085>

Touch panel with 7.0" graphics-capable TFT display, 65535 colors x 800 X 480 pixels, 1x Ethernet, 2x USB and integrated runtime of the Visu+ visualization software.

Commercial data	
GTIN (EAN)	
sales group	K310
Pack	1 pcs.
Customs tariff	84714100
Catalog page information	Page 133 (AX-2009)

Product notes

WEEE/RoHS-compliant since:
05/11/2010



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
Display data	
Display	17.8 cm/7" TFT active
Resolution	800 x 480 Pixel
Touch screen	Resistive industrial touch screen
Colors	65,536 colors

Computer data

Processor	RISC ARM9 CPU; 200 MHz
Main memory	64 MByte SDRAM
Data memory	32 Mbyte Flash, with 8 Mbyte free for application
Interfaces	10/100 MBit Ethernet; 2 x USB Host 2.0
Operating systems	Windows CE 5.0

General data

External dimension, width	203 mm
External dimension, height	147 mm
External dimension, depth	5 mm
Note regarding external dimension	Dimensions of the front plate
Installation dimension, width	195 mm
Installation dimension, height	139 mm
Mounting type	Installation in front plate

Ambient Conditions

Degree of protection	IP65 (front), IP20 (back)
Ambient temperature (operation)	0 °C ... 50 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C
Permissible humidity (operation)	20 % ... 85 % (no condensation)
Permissible humidity (storage/transport)	10 % ... 95 % (no condensation)
Vibration (operation)	DIN EN 60068-2-6
Shock	DIN EN 60068-2-27

Certificates / Approvals

Certification

ABS, BV, CUL Listed, DNV, GL, LR, UL Listed

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;