THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
© COPYRIGHT 19 BY AMP INCORPORATED. ALL RIGHTS RESERVED.

REVISIONS					
LTR	DESCRIPTION	DATE	DWN	APVD
H	REVISED PER EC 063B-0300-00	23-JUN-00	KW	KC

1. PARTS COMPLY TO AMP SOLDERABILITY SPECIFICATION 109-11-3.
2. CIRCUIT IDENTIFICATION CHARACTERS ARE ADJACENT TO THE INDICATED CAVITIES, BUT LOCATION AND ORIENTATION MAY DIFFER FROM PRINT.
3. DIMENSIONS IN BRACKETS ARE IN INCHES.
4. DRAIN HOLES LOCATED AS SHOWN. OPTIONAL CONSTRUCTION- ALL DRAIN HOLES LOCATED 90° AS SHOWN IN DETAIL A.







3-DIMENSIONAL MODEL
NTS

DETAIL A
OPTIONAL CONSTRUCTION
4



RECOMMENDED MOUNTING HOLE PATTERN
FOR 1.57 [.062] THICK P.C. BOARD

PHOSPHOR BRONZE, PRE-TIN	NYLON, UL94V-0, WHITE	643416-1
PIN CONTACT MATERIAL AND FINISH	HOUSING MATERIAL	PART NO

METRIC

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]
TOLERANCES UNLESS OTHERWISE SPECIFIED:
2 PLC ±
3 PLC ±
4 PLC ±
5 PLC ±
ANGLES ±
MATERIAL: SEE TABLE
FINISH: SEE TABLE

DWN: T. McEACHIN 07-JUN-2000
CH: K. COBLE 07-JUN-2000
APVD: K. COBLE 07-JUN-2000
PRODUCT SPEC: –
APPLICATION SPEC: –
WEIGHT: –
CUSTOMER DRAWING

AMP Incorporated
Harrisburg, PA 17105-3608

NAME: SOCKET HEADER ASSEMBLY, POLARIZED,4 CIRCUIT, UNIVERSAL MATE-N-LOK™
SIZE: A1 | CAGE CODE: 00779 | DRAWING NO: C-643416
SCALE: 5:1 | SHEET: 1 OF 1 | REV: H

Downloaded from Elcodis.com electronic components distributor