



- Single row interconnects having an even number of pins are now available with a left or right hand footprint.
- Headers (850 & 852) use MM# 4006 pins. See page 175 for details.
- Sockets (851 & 853) use MM# 4890-0 receptacles and accept pin diameters from 0,38 - 0,53. See page 131 for details.
- Coplanarity 0,13 (Single Row max 20 pins; Double Row max 40 pins). For higher pin counts contact technical support .
- Insulators are high temp. thermoplastic.



**Ordering Information**

<b>Fig. 1L</b>	<b>Single Row Header, Left Hand Footprint</b> Odd or Even # of pins	850-XX-0__-30-001000		
	<b>Specify # of pins</b>	01-50		
<b>Fig. 1R</b>	<b>Single Row Header, Right Hand Footprint</b> Even # of pins	850-XX-0__-30-002000		
	<b>Specify even # of pins</b>	02-50		
<b>Fig. 2</b>	<b>Double Row Header, Even # of pins</b>	852-XX-__-30-001000		
	<b>Specify even # of pins</b>	004-100		
SPECIFY PLATING CODE XX=		10 $\diamond$	90	40 $\diamond$
Pin Plating		0,25 $\mu$ m Au	5,08 $\mu$ m Sn/Pb	5,08 $\mu$ m Sn
<b>Fig. 3L</b>	<b>Single Row Socket, Left Hand Footprint</b> Odd or Even # of pins	851-XX-0__-30-001000		
	<b>Specify # of pins</b>	01-50		
<b>Fig. 3R</b>	<b>Single Row Socket, Right Hand Footprint</b> Even # of pins	851-XX-0__-30-002000		
	<b>Specify even # of pins</b>	02-50		
<b>Fig. 4</b>	<b>Double Row Socket, Even # of pins</b>	853-XX-__-30-001000		
	<b>Specify even # of pins</b>	004-100		
SPECIFY PLATING CODE XX=		93	99	43 $\diamond$ 44 $\diamond$
Sleeve (Pin)		5,08 $\mu$ m Sn/Pb	5,08 $\mu$ m Sn/Pb	5,08 $\mu$ m Sn 5,08 $\mu$ m Sn
Contact (Clip)		0,76 $\mu$ m Au	5,08 $\mu$ m Sn/Pb	0,76 $\mu$ m Au 5,08 $\mu$ m Sn