


ENTER DESCRIPTION EC NO: I2010-0674 DRAWN: SJS01 CHKD: GWF APPR: MPRASAD DATE: 2010/06/11 DATE: 87/11/16 DATE: 2010/06/22	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE IN/MM		SCALE 1:1	DESIGN UNITS INCH	THIRD ANGLE PROJECTION	
		4 PLACES ± --- ± ---	mm INCH	DRAWN BY RK	DATE 87/11/16	TITLE HOUSING, PLUG .084/(2.13) DIA. SERIES			
		3 PLACES ± --- ± .010		CHECKED BY GWF	DATE 87/11/16	MOLEX INCORPORATED			
		2 PLACES ± 0.25 ± 0.14		APPROVED BY GWF	DATE 87/11/16	MATERIAL NO. DOCUMENT NO. SD-42021-** SHEET NO. 1 OF 2			
		1 PLACE ± 0.36 ± ---		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE TABLE		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	
		ANGULAR ± --- °							

PART NO.	ENG. NO.	CIRCUIT SIZE	MATERIAL (SEE NOTE 1)	DIM. "A"	DIM. "B"	DIM. "C"	STATUS
050-84-1010	42021-1A	1	A				ACTIVE
050-84-1011	42021-1B	1	B	1.090	.290	----	VOID
050-84-1015	42021-1C	1	C	(27.69)	(7.37)		ACTIVE
366430001	36643-001	1	E				ACTIVE
050-84-1020	42021-2A	2	A				ACTIVE
050-84-1021	42021-2B	2	B	1.087	.580	.300	VOID
050-84-1025	42021-2C	2	C	(27.61)	(14.73)	(7.62)	ACTIVE
366430002	36643-002	2	E				ACTIVE
050-84-1030	42021-3A	3	A				ACTIVE
050-84-1031	42021-3B	3	B	1.087	.580	.300	VOID
050-84-1035	42021-3C	3	C	(27.61)	(14.73)	(7.62)	ACTIVE
366430003	36643-003	3	E				ACTIVE
050-84-1040	42021-4A	4	A				ACTIVE
050-84-1041	42021-4B	4	B	1.087	.580	.300	VOID
050-84-1045	42021-4C	4	C	(27.61)	(14.73)	(7.62)	ACTIVE
366430004	36643-004	4	E				ACTIVE
050-84-1060	42021-6A	6	A				ACTIVE
050-84-1061	42021-6B	6	B	1.087	1.080	.800	VOID
050-84-1065	42021-6C	6	C	(27.61)	(27.43)	(20.32)	ACTIVE
366430005	36643-005	6	E				ACTIVE
PRELIMINARY	42021-8A	8	A	1.087	.580	.300	ACTIVE
PRELIMINARY	42021-8B	8	B	(27.61)	(14.73)	(7.62)	ACTIVE
PRELIMINARY	42021-8C	8	C				ACTIVE
050-84-1090	42021-9A	9	A				ACTIVE
050-84-1091	42021-9B	9	B	1.087	1.080	.800	VOID
050-84-1095	42021-9C	9	C	(27.61)	(27.43)	(20.32)	ACTIVE
366430006	36643-006	9	E				ACTIVE
050-84-1120	42021-12A	12	A				ACTIVE
050-84-1121	42021-12B	12	B	1.087	1.080	.800	VOID
050-84-1125	42021-12C	12	C	(27.61)	(27.43)	(20.32)	ACTIVE
366430007	36643-007	12	E				ACTIVE
050-84-1150	42021-15A	15	A				ACTIVE
050-84-1151	42021-15B	15	B	1.087	1.080	.800	VOID
050-84-1155	42021-15C	15	C	(27.61)	(27.43)	(20.32)	ACTIVE
366430008	36643-008	15	E				ACTIVE
366480001	36648-001	1	D		.290(7.37)	----	ACTIVE
366480002	36648-002	2	D	1.079	.580	.300	ACTIVE
366480003	36648-003	3	D	(27.43)	(14.73)	(7.62)	ACTIVE
366480004	36648-004	4	D				ACTIVE
366480005	36648-005	6	D				ACTIVE
366480006	36648-006	9	D	1.079	1.080	.800	ACTIVE
366480007	36648-007	12	D	(27.43)	(27.43)	(20.32)	ACTIVE
366480008	36648-008	15	D				ACTIVE
366410001	36641-001	4	D	1.090	580(14.73)	300(7.62)	OBSOLETE
366410002	36641-002	9	D	(27.69)	1080(27.43)	800(20.32)	OBSOLETE

NOTES:

- 1) MATERIAL CODES:
 "A"= NYLON TYPE 6/6, 94V-2
 COLOR: NATURAL (WHITE/TRANSLUCENT)
 "B"= NYLON TYPE 6/6, 94V-0
 COLOR: (BRICK RED)
 "C"= NYLON TYPE 6/6, 94V-0
 COLOR: NATURAL (WHITE)
 "D"= NYLON 94V-2
 COLOR: BLACK (ZYTEL 101F)
 "E"= NYLON 94V-2
 COLOUR/NATURAL
 GLOW WIRE COMPATIBLE WITH CTI OF 325 VOLTS.
 ACCORDING TO IEC 60335-4TH EDITION
- 2) UNLESS OTHERWISE INDICATED, DIMENSIONS ARE FOR REFERENCE ONLY.
- 3) PLUG HOUSINGS MATE WITH :
 - CAP HOUSINGS, .084/(2.13) DIA, SERIES: (42022-***)
 - HEADER ASSEMBLY HOUSINGS, .084/(2.13) DIA, SERIES: (A-42002-*****)
- 4) HOUSINGS DESIGNED TO BE USED WITH TERMINALS :
 - PINS, .084/(2.13) DIA, SERIES: (42023-*****)
 - SOCKETS, .084/(2.13) DIA, SERIES: (42024-*****)
- 5) CONTACTS ARE ON .250/(6.35) GRID CENTERLINE SPACING.
- 6) PRODUCT SPECIFICATION PS-42022-0001 APPLIES.
- 7) LEGEND SCHEME IS NOT APPLICABLE FOR GLOW WIRE COMPATIBLE PART NUMBERS

LEGEND:



ENTER DESCRIPTION IEC NO: 12010-0674 DRAWNS: NS01 CHKD: GWF APPR: KPRASAD 2010/06/11 87/11/16 2010/06/12	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED) <table border="1"> <tr><th colspan="2">mm</th><th colspan="2">INCH</th></tr> <tr><td>4 PLACES</td><td>± .10</td><td>± .004</td><td>± .001</td></tr> <tr><td>3 PLACES</td><td>± .12</td><td>± .010</td><td>± .004</td></tr> <tr><td>2 PLACES</td><td>± .15</td><td>± .014</td><td>± .005</td></tr> <tr><td>1 PLACE</td><td>± .20</td><td>± .008</td><td>± .003</td></tr> <tr><td colspan="4">ANGULAR ± .005</td></tr> </table>	mm		INCH		4 PLACES	± .10	± .004	± .001	3 PLACES	± .12	± .010	± .004	2 PLACES	± .15	± .014	± .005	1 PLACE	± .20	± .008	± .003	ANGULAR ± .005				DIMENSION STYLE IN/MM DRAWN BY: RK DATE: 87/11/16 CHECKED BY: GWF DATE: 87/11/16 APPROVED BY: GWF DATE: 87/11/16	SCALE 1:1 DESIGN UNITS INCH	THIRD ANGLE PROJECTION HOUSING, PLUG .084/(2.13) DIA. SERIES
	mm		INCH																										
	4 PLACES	± .10	± .004	± .001																									
	3 PLACES	± .12	± .010	± .004																									
2 PLACES	± .15	± .014	± .005																										
1 PLACE	± .20	± .008	± .003																										
ANGULAR ± .005																													
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE TABLE	MATERIAL NO. SD-42021-***	DOCUMENT NO. SD-42021-***	SHEET NO. 2 OF 2																								
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																													
SIZE A																													