



ASSEMBLED VIEW
SCALE 1:1

| | | |
|-----------------|--------------|-------------|
| 194190007 | 2 | 16-14 |
| 194190008 | 2 | 22-18 |
| MATERIAL NUMBER | CIRCUIT SIZE | UL WIRE AWG |

NOTES:

- ASSEMBLY BULK PACKAGED PER PK-19419-001.
- MOUNTING SLOT DIMENSIONS.
- USE CONNECTOR WITH MALE CRIMP TERMINAL: SERIES 19417.

| EC NO: ETC2004-0202 DRW: J.PAWLIC 2004/06/03 CHK: J.PAWLIC 2004/06/03 APPR: J.PAWLIC 2004/06/03 | QUALITY SYMBOLS | GENERAL TOLERANCES (UNLESS SPECIFIED) | SCALE 2:1 | DESIGN UNITS INCH | THIRD ANGLE PROJECTION | REVISE ON CAD ONLY | | | | | | | | | | | | | | | |
|----------------------------------------------------------------------------------------------------------|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|-------------------|-------------------------------------------------------------------------------------------------------------------------------|--------------------|--------|--------|----------|--------|--------|----------|--------|-------|---------|--------|--------|-----------------------|--|---------------------------|--|
| | ▽ 0 ▽ 0 | <table border="1"> <tr> <th></th> <th>mm</th> <th>INCH</th> </tr> <tr> <td>4 PLACES</td> <td>± .---</td> <td>± .---</td> </tr> <tr> <td>3 PLACES</td> <td>± .---</td> <td>± .005</td> </tr> <tr> <td>2 PLACES</td> <td>± 0.13</td> <td>± .01</td> </tr> <tr> <td>1 PLACE</td> <td>± 0.25</td> <td>± .---</td> </tr> </table> | | mm | INCH | 4 PLACES | ± .--- | ± .--- | 3 PLACES | ± .--- | ± .005 | 2 PLACES | ± 0.13 | ± .01 | 1 PLACE | ± 0.25 | ± .--- | DIMENSION STYLE IN/MM | | TITLE 2 WAY PLUG ASSEMBLY | |
| | | | mm | INCH | | | | | | | | | | | | | | | | | |
| | 4 PLACES | ± .--- | ± .--- | | | | | | | | | | | | | | | | | | |
| 3 PLACES | ± .--- | ± .005 | | | | | | | | | | | | | | | | | | | |
| 2 PLACES | ± 0.13 | ± .01 | | | | | | | | | | | | | | | | | | | |
| 1 PLACE | ± 0.25 | ± .--- | | | | | | | | | | | | | | | | | | | |
| DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS | | DRAWN BY B.RUPERT DATE 12/05/02 CHECKED BY J.PAWLIC DATE 12/06/02 APPROVED BY R.DERROSS DATE 12/06/02 | MOLEX INCORPORATED MATERIAL NO. SEE CHART DOCUMENT NO. SD-19419-002 SHEET NO. 1 OF 1 | | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION | | | | | | | | | | | | | | | | |