



製品番号
ENG. NO.

回路番号
CIRCUIT NO.

材料
MATERIAL
ナイロン66, UL94V-0
NYLON66, UL94V-0

注記
NOTE

使用ターミナル: ENG. NO. 5103*
APPLICABLE TERMINAL: ENG. NO. 5103*

	47.5	51	22-01-1204	5102-20	20
	45	48.5	▲ -1194	▲ -19	19
	42.5	46	-1184	-18	18
	40	43.5	-1174	-17	17
	37.5	41	-1164	-16	16
	35	38.5	-1154	-15	15
	32.5	36	-1144	-14	14
	30	33.5	-1134	-13	13
	27.5	31	-1124	-12	12
	25	28.5	-1114	-11	11
	22.5	26	-1104	-10	10
	20	23.5	-1094	-09	9
	17.5	21	-1084	-08	8
	15	18.5	-1074	-07	7
	12.5	16	-1064	-06	6
	10	13.5	-1054	-05	5
	7.5	11	-1044	-04	4
	5	8.5	▼ -1034	▼ -03	3
	2.5	6	22-01-1024	5102-02	2
	B	A	EDP. NO.	ENG. NO.	NO. OF EXTS.

REVISED EC NO. J2006-347 2006/07/31 DRW:KSAI1001 2006/08/04 CHKD:HTANAKA 2006/08/04 APPR:NIKIITA 2006/08/07	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 4:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION
	10 UNDER	±0.2	DRAWN BY H. IJIMA	DATE 1996/07/05	TITLE MINI SPOX HSG		
	10 OVER 30 UNDER	±0.25	CHECKED BY M. FUKUSHIMA	DATE 1996/07/05	MOLEX INCORPORATED		
	30 OVER	±0.3	APPROVED BY M. ENOMOTO	DATE 1996/07/05	DOCUMENT NO. SD-5102-001	SHEET NO. 1 OF 1	
H	DESCRIPTION	ANGULAR	±3 °	MATERIAL NO.	SEE CHART	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SIZE A3		EN-02JA(021)			