






三角法 (THIRD ANGLE PROJECTION)



寸法公差は±0.20
(TOLERANCE : ±0.2)
パネル取付穴
(DIMENSION OF PANEL)



キボティマーク (CAVITY MARK)

トレドマーク (TRADE MARK)

NOTES:

1. APPLIED CONTACT P/N : 170359, 170360, 170361, 170362.
2. MATING CONN ; PLUG HOUSING P/N 172338.
3. PANEL THICKNESS : 0.8~2.0 mm
4. PRESS DIRECTION OF PANEL MUST BE SAME AS HOUSING INSERTED DIRECTION.
5. INSTRUCTION SHEET : IS-105J
6. PRODUCT SPEC : 108-5151.

△ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

注:

1. 使用端子型番は、170359, 170360, 170361, 170362
2. 嵌合相手ハウジング型番は、172338
3. 適用パネル厚 0.8~2.0 mm
4. 取付穴打抜方向とハウジングの挿入方向は同じである。
5. 取扱説明書 : IS-105J
6. 適用製品仕様書 : 108-5151

△ OBSOLETE

黄 (YELLOW)	1-172330	-4
黒 (BLACK)	1-	-9
青 (BLUE)	1-	-6
緑 (GREEN)	1-	-5
赤 (RED)	1-	-2
自然色 (NATURAL)	172330	-1
色 (COLOR)	型番 (P/N)	

材料 (MATERIAL) 6/6ナイロン (UL94V-2) (NYLON 6/6 UL94V-2)		一般公差 TOLERANCE ±0.3 EXCEPT ±1° AS NOTED	STE TE Connectivity	
仕上 (FINISH) 色: 表参照 HOUSING COLOR : SEE TABLE		DR. <i>R. Yano</i> CHK. <i>...</i> DE. <i>...</i> APP. <i>...</i>	名称 (NAME) MINI-UNIVERSAL MATE-N-LOK CONN. CAP HOUSING 4 Pos. (UL94V-2) 4極ミニユニバーサルメイトロックコネクタ キャビティハウジング (UL94V-2)	
		SIZE B	LOC J	番号 (NO.) C-172330
		尺取 (SCALE) 2:1	REV. A3	SHEET #

単位: 寸法 DIMENSIONS IN MM. DO NOT SCALE PRINT

A3	REVISED PER ECO-11-005030	RK	HMR
LTR.	変更 (REVISION RECORD)	DR.	CHK. DATE