

RoHS COMPLIANT

REVISIONS				
REV	ECN NO.	DESCRIPTION	APPROVED BY	DATE
A			ELTON MENG	2006-05-22

Product Specification

Material

Insulator: Glass-Filled Thermoplastic
PBT,UL94V-0 rates

Contact: Brass

Plated full gold or selected gold in mating area, 100u² min. tin-lead on termination area, with entire contact under-plated 50u² min. Nickel

Electrical

Contact Resistance: ± 30 milliohms
Max at 1 AMP DC.

Insulation Resistance: ± 1000 megohms at 500 VDC

Dielectric Withstanding Voltage: 500 VAC/rms 60Hz for 1 minute

Current Rating: 1 AMP

Voltage Rating: ± 250 VAC/rms 60Hz



A Type

AKSG-200-X-R

Contact Plating
G Gold Contact
Z Tinned



B Type

AKSO-200-X-R

Contact Plating
G Gold Contact
Z Tinned

DO NOT SCALE DRAWING

DIMENSIONS: <input type="checkbox"/> MM (INCH) <input type="checkbox"/> INCH (MM) <input checked="" type="checkbox"/> MM ONLY		CAD GENERATED DRAWING, DO NOT MANUALLY UPDATE	
UNLESS OTHERWISE SPECIFIED, GENERAL TOLERANCE: DECIMALS ANGLES X: ± 0.38 (0.015) X*: $\pm 3^\circ$.X: ± 0.25 (0.010) X*: $\pm 1.0^\circ$.XX: ± 0.13 (0.005)		CHECKED BY AND DATE JUSTIN XING 03-07-06	
MATERIAL:		APPROVED BY AND DATE ELTON MENG 06-09-06	
FINISH:		THIRD ANGLE PROJECTION 	
SCALE: 5:1		SIZE: A3	

TITLE MINI JUMPER 2.00MM (0.079")	
FILE NO.:	REV A
SHEET 1 OF 1	