

- DIP sockets with increased solder tail length of 4,32, allowing application on multi-layer PCBs up to 3,53mm thick. Other lengths available upon request.
- Hi-Rel, 4-finger BeCu #30 contact is rated at 3 amps. See page 218 for details.
- Series 111 use MM #0134 pins. See page 136 for details.
- Insulators are high temperature thermoplastic.

Total number of pins				Quantity per tube	<h3 style="margin: 0;">Ordering Information</h3>
	A	B	C		

10	12,6	5,08	7,6	40	111-XX-210-41-001000	<div style="border: 1px solid black; padding: 5px; display: inline-block;"> RoHS 2002/95/EC </div> <div style="border: 1px solid green; padding: 2px; margin-top: 5px; font-size: small;"> For RoHS compliance select ◇ plating code. </div>
4	5,0	7,62	10,1	102	111-XX-304-41-001000	
6	7,6	7,62	10,1	67	111-XX-306-41-001000	
8	10,1	7,62	10,1	50	111-XX-308-41-001000	
10	12,6	7,62	10,1	40	111-XX-310-41-001000	
14	17,7	7,62	10,1	28	111-XX-314-41-001000	
16	20,3	7,62	10,1	25	111-XX-316-41-001000	
18	22,8	7,62	10,1	22	111-XX-318-41-001000	
20	25,3	7,62	10,1	20	111-XX-320-41-001000	
22	27,8	7,62	10,1	18	111-XX-322-41-001000	
24	30,4	7,62	10,1	16	111-XX-324-41-001000	
28	35,5	7,62	10,1	14	111-XX-328-41-001000	
20	25,4	10,16	12,7	20	111-XX-420-41-001000	
22	27,8	10,16	12,7	18	111-XX-422-41-001000	
24	30,4	10,16	12,7	16	111-XX-424-41-001000	
28	35,5	10,16	12,7	14	111-XX-428-41-001000	
32	40,6	10,16	12,7	12	111-XX-432-41-001000	
24	30,4	15,24	17,7	16	111-XX-624-41-001000	
28	35,5	15,24	17,7	14	111-XX-628-41-001000	
32	40,6	15,24	17,7	12	111-XX-632-41-001000	
36	45,7	15,24	17,7	11	111-XX-636-41-001000	
40	50,8	15,24	17,7	10	111-XX-640-41-001000	
42	53,3	15,24	17,7	9	111-XX-642-41-001000	
48	60,9	15,24	17,7	8	111-XX-648-41-001000	
50	63,5	15,24	17,7	8	111-XX-650-41-001000	
52	66,0	15,24	17,7	7	111-XX-652-41-001000	
50	63,5	22,86	25,3	8	111-XX-950-41-001000	<div style="border: 1px solid black; border-radius: 50%; padding: 10px; display: inline-block;"> XX=Plating Code See Below </div>
52	66,0	22,86	25,3	7	111-XX-952-41-001000	
64	81,2	22,86	25,3	6	111-XX-964-41-001000	

For Electrical,
Mechanical & Environmental
Data, See pg. 4

SPECIFY PLATING CODE XX=		93		43◇	
Sleeve (Pin)		5,08µm Sn/Pb		5,08µm Sn	
Contact (Clip)		0,76µm Au		0,76µm Au	

Downloaded from Elcodis.com electronic components distributor