

- High density DIP sockets and strips for devices featuring .070" lead spacing.
- Solder tails use MM #1802 receptacles, See page 140 for details. Wraposts use MM # 1702-2 or 1703-3 receptacles, See page 166 for details.
- Receptacles use Hi-Rel, 4-finger #30 contact and 6-finger #43 contact, both rated at 3 amps. See pages 218 & 220.
- Insulators are high temp. thermoplastic.

Total number of pins				Quantity per tube	<div style="border: 1px solid black; border-radius: 50%; padding: 5px; display: inline-block;"> <i>For Electrical, Mechanical &amp; Environmental Data, See pg. 4</i> </div> <b>Ordering Information</b> <div style="border: 1px solid black; border-radius: 50%; padding: 5px; display: inline-block; margin-left: 20px;"> <i>XX=Plating Code See Below</i> </div>				
	A	B	C		Solder Tail	2 Level Wrapost L = .370	3 Level Wrapost L = .510		
<b>OPEN FRAME DIP SOCKET</b>									
16	0.572	0.3	0.39	35	117-XX-316-41-005000	127-XX-316-41-002000	127-XX-316-41-003000		
28	0.992	0.4	0.49	20	117-XX-428-41-005000	127-XX-428-41-002000	127-XX-428-41-003000		
30	1.062	0.4	0.49	18	117-XX-430-41-005000	127-XX-430-41-002000	127-XX-430-41-003000		
48	1.692	0.4	0.49	12	117-XX-448-41-005000	127-XX-448-41-002000	127-XX-448-41-003000		
20	0.712	0.6	0.69	28	117-XX-620-41-005000	127-XX-620-41-002000	127-XX-620-41-003000		
28	0.992	0.6	0.69	20	117-XX-628-41-005000	127-XX-628-41-002000	127-XX-628-41-003000		
40	1.412	0.6	0.69	14	117-XX-640-41-005000	127-XX-640-41-002000	127-XX-640-41-003000		
42	1.482	0.6	0.69	13	117-XX-642-41-005000	127-XX-642-41-002000	127-XX-642-41-003000		
48	1.692	0.6	0.69	11	117-XX-648-41-005000	127-XX-648-41-002000	127-XX-648-41-003000		
52	1.832	0.6	0.69	11	117-XX-652-41-005000	127-XX-652-41-002000	127-XX-652-41-003000		
56	1.972	0.6	0.69	10	117-XX-656-41-005000	127-XX-656-41-002000	127-XX-656-41-003000		
64	2.252	0.6	0.69	8	117-XX-664-41-005000	127-XX-664-41-002000	127-XX-664-41-003000		
68	2.392	0.6	0.69	8	117-XX-668-41-005000	127-XX-668-41-002000	127-XX-668-41-003000		
64	2.252	0.75	0.84	8	117-XX-764-41-005000	127-XX-764-41-002000	127-XX-764-41-003000		
<b>CLOSED FRAME DIP SOCKET</b>									
64	2.252	0.75	0.84	8	217-XX-764-41-005000	227-XX-764-41-002000	227-XX-764-41-003000		
<b>SINGLE ROW STRIP SOCKET</b>									
If desired, we will supply any length up to 21 pins.									
21	1.482	---	.104	-	317-93-121-41-005000	327-XX-121-41-002000	327-XX-121-41-003000		
<div style="border: 1px solid green; padding: 5px; display: inline-block;"> <i>For RoHS compliance select <span style="color: green;">◇</span> plating code.</i> </div>					SPECIFY PLATING CODE XX=			<b>93</b>	<b>43</b> <span style="color: green;">◇</span>
Sleeve (Pin)					200µ" Sn/Pb			200µ" Sn	
Contact (Clip)					30µ" Au			30µ" Au	