

- For components to be mounted perpendicularly to the PCB, such as LED displays.
- Horizontal mount solder tails are available with either 7,62 (standard) or 2,54 row spacing.
- Series 299 use MM #1103/0903, #1103/1610 or #1103/0904 pins. See pages 137 & 138 for details.
- Hi-Rel, 4-finger BeCu #30 contact is rated at 3 amps. See page 218 for details.
- Insulators are high temperature thermoplastic.

Total number of pins				Quantity per tube	Ordering Information	
	A	B	C		E=7,62	E=2,54
	6	7,6	7,62		10,1	
8	10,1	7,62	10,1		299-XX-308-10-001000	299-XX-308-11-001000
10	12,6	7,62	10,1		299-XX-310-10-001000	299-XX-310-11-001000
12	15,2	7,62	10,1	33	299-XX-312-10-001000	299-XX-312-11-001000
14	17,7	7,62	10,1	29	299-XX-314-10-001000	299-XX-314-11-001000
16	20,3	7,62	10,1	25	299-XX-316-10-001000	299-XX-316-11-001000
18	22,8	7,62	10,1	22	299-XX-318-10-001000	299-XX-318-11-001000
20	25,3	7,62	10,1	20	299-XX-320-10-001000	299-XX-320-11-001000
24	30,4	7,62	10,1	16	299-XX-324-10-001000	299-XX-324-11-001000
8	10,1	15,24	17,7	50	299-XX-608-10-002000	
10	12,6	15,24	17,7	40	299-XX-610-10-002000	
12	15,2	15,24	17,7	34	299-XX-612-10-002000	
14	17,7	15,24	17,7	28	299-XX-614-10-002000	
16	20,3	15,24	17,7	25	299-XX-616-10-002000	
18	22,8	15,24	17,7	22	299-XX-618-10-002000	
20	25,3	15,24	17,7	20	299-XX-620-10-002000	
22	27,8	15,24	17,7	18	299-XX-622-10-002000	
24	30,4	15,24	17,7	16	299-XX-624-10-002000	
26	33,0	15,24	17,7	15	299-XX-626-10-002000	
28	35,5	15,24	17,7	14	299-XX-628-10-002000	
30	38,1	15,24	17,7	13	299-XX-630-10-002000	
32	40,6	15,24	17,7	12	299-XX-632-10-002000	
36	45,7	15,24	17,7	11	299-XX-636-10-002000	
40	50,8	15,24	17,7	10	299-XX-640-10-002000	

*For Electrical,  
Mechanical & Environmental  
Data, See pg. 4*

**XX=Plating Code  
See Below**

*For RoHS compliance  
select ◇ plating code.*

**RoHS  
2002/95/EC**

SPECIFY PLATING CODE XX=		93			43◇	
Sleeve (Pin)		5,08µm Sn/Pb			5,08µm Sn	
Contact (Clip)		0,76µm Au			0,76µm Au	

Downloaded from [Elcodis.com](http://Elcodis.com) electronic components distributor