


- Unique compliant tail pins conform to $1,02 \pm 0,76$ finished hole diameter without stressing inner layers.
- Two tails lengths are offered for 1,52 - 2,54 and 2,29 - 3,30 thick panels.
- Series 146 use MM #4612 or MM #4613 pins with a BeCu #30 contact, rated at 3 amps. See page 133 for details.
- Insulators are high temperature thermoplastic.

APPLICATION OF COMPLIANT TAIL PINS



Mill-Max's patented* compliant tail features precision-machined pins that are hollow and slotted to conform to a $1,02 \pm 0,76$ diameter PTH. As the pin is inserted, the slot compresses to fit the PTH, thus avoiding damage (see illustration at left). The pin's tail has fine serrations that form a perfect "gas tight" connection that doesn't require soldering. And since the pin doesn't damage the hole, compliant tail sockets and connectors can be easily replaced.

*Patent No. 4,799,904.

Total number of pins				Quantity per tube	Ordering Information		<div style="border: 1px solid black; padding: 5px; text-align: center;"> RoHS 2002/95/EC </div> <div style="border: 1px solid green; padding: 5px; margin-top: 10px; text-align: center;"> <i>For RoHS compliance select ◇ plating code.</i> </div> <div style="border: 1px solid black; border-radius: 50%; padding: 10px; margin-top: 10px; text-align: center;"> <i>For Electrical, Mechanical & Environmental Data, See pg. 4</i> </div> <div style="border: 1px solid black; border-radius: 50%; padding: 10px; margin-top: 10px; text-align: center;"> XX=Plating Code See Below </div>	
	A	B	C		L = 3,05mm (for 1,52 - 2,54 thick panel)	L = 4,45mm (for 2,29 - 3,30 thick panel)		
	6	7,6	7,62		10,1	67		146-XX-306-41-012000
8	10,1	7,62	10,1	50	146-XX-308-41-012000	146-XX-308-41-013000		
14	17,7	7,62	10,1	28	146-XX-314-41-012000	146-XX-314-41-013000		
16	20,3	7,62	10,1	25	146-XX-316-41-012000	146-XX-316-41-013000		
18	22,8	7,62	10,1	22	146-XX-318-41-012000	146-XX-318-41-013000		
20	25,3	7,62	10,1	20	146-XX-320-41-012000	146-XX-320-41-013000		
24	30,4	7,62	10,1	16	146-XX-324-41-012000	146-XX-324-41-013000		
22	27,8	10,16	12,7	18	146-XX-422-41-012000	146-XX-422-41-013000		
24	30,4	15,24	17,7	16	146-XX-624-41-012000	146-XX-624-41-013000		
28	35,5	15,24	17,7	14	146-XX-624-41-012000	146-XX-624-41-013000		
32	40,6	15,24	17,7	12	146-XX-624-41-012000	146-XX-624-41-013000		
40	50,8	15,24	17,7	10	146-XX-624-41-012000	146-XX-624-41-013000		
SPECIFY PLATING CODE XX=						93		43◇
Sleeve (Pin)						5,08µm Sn/Pb		5,08µm Sn
Contact (Clip)						0,76µm Au		0,76µm Au