



- 1. RECEPTACLE ACCEPTS A .008--014 THICK I.C. LEAD.
- △ TUBE LOADED FOR AUTOMATIC INSERTION.
- △ TWO .000030 MIN THK. GOLD STRIPES IN CONTACT AREA WITH TIN-LEAD (93/7) ON CONTACT LEGS, BALANCE OF CONTACT NICKEL PLATED.
- △ TWO .000015 MIN THK. GOLD STRIPES IN CONTACT AREA WITH TIN-LEAD (93/7) ON CONTACT LEGS, BALANCE OF CONTACT NICKEL PLATED.
- △ MAXIMUM DIMENSION FOR I.C. SEATING PLANE.

REV	DATE	DESCRIPTION	BY	CHK	APP
AD	0				
AB	REV PER 003C-0198-99		23AUG90	BT	HW

REVISION	DESCRIPTION	DATE	BY	CHK	APP
1	REVISION				

  

CONTACT FINISH	CONTACT MAT'L	HOUSING MATERIAL	PART NO.	
△ TINNED	PHOSPHZ .008 THK	GLASS-FILLED THERMOPLASTIC, 94V-O, BLACK	△ 2-640361-4	
△ TINNED	PHOSPHZ .008 THK	GLASS-FILLED THERMOPLASTIC, 94V-O, BLACK	△ 2-640361-3	
SUPSD BY 390262-1	△ TINNED	BE.CU .008 THK	GLASS-FILLED THERMOPLASTIC, 94V-O, BLACK	△ 2-640361-2
SUPSD BY 390262-1	△ TINNED	PHOSPHZ .008 THK	GLASS-FILLED THERMOPLASTIC, 94V-O, BLACK	640361-4
	△ TINNED	PHOSPHZ .008 THK	GLASS-FILLED THERMOPLASTIC, 94V-O, BLACK	640361-3
	△ TINNED	BE.CU .008 THK	GLASS-FILLED THERMOPLASTIC, 94V-O, BLACK	640361-2
OBSOLETE	△ TINNED	PHOSPHZ .008 THK	GLASS-FILLED THERMOPLASTIC, 94V-O, BLACK	640361-1

  

THIS DRAWING IS A CONTROLLED DOCUMENT	AMPS	TYPE DESIGNATOR
REVISIONS	DATE	BY
1	108-1066	SOCKET ASSEMBLY, DIP
2	114-1049	24 POS. DIP/MATE. DL
3		
4		
5		
6		
7		
8		
9		
10		
11		
12		
13		
14		
15		
16		
17		
18		
19		
20		
21		
22		
23		
24		
25		
26		
27		
28		
29		
30		
31		
32		
33		
34		
35		
36		
37		
38		
39		
40		
41		
42		
43		
44		
45		
46		
47		
48		
49		
50		
51		
52		
53		
54		
55		
56		
57		
58		
59		
60		
61		
62		
63		
64		
65		
66		
67		
68		
69		
70		
71		
72		
73		
74		
75		
76		
77		
78		
79		
80		
81		
82		
83		
84		
85		
86		
87		
88		
89		
90		
91		
92		
93		
94		
95		
96		
97		
98		
99		
100		