

# Series F40 Thru-Hole .040 [1.02] Female DIP Strips


- This female DIP strip is used in conjunction with Aries' Shorting Plug SP200, available separately, for your programming needs.
- "Break" feature allows strips to be cut to the number of positions desired.

### **SPECIFICATIONS:**

- Body material is black UL 94V-0 Glass-filled 4/6 Nylon.
- Pin body is Brass Alloy 360 1/2 hard per UNS C36000 ASTM-B16-00.
- · Pin body plating:
  - $-10 = 200\mu$  [5.08µm] min.Tin per ASTM B545 Type 1 over 100 $\mu$ [2.54µm] min. Nickel per SAE-AMS-QQ-N-290.
  - -10TL = 200μ [5.08μm] min. 93/7 Tin/Lead per MIL-P-81728 over 100μ [2.54μm] min. Nickel per SAE-AMS-QQ-N-290.
- 4-fingered collet contact is Beryllium Copper Alloy per UNS C17200 ASTM-B194-01.
- Collet contact plating is 30μ [.76μm] min. Gold per MIL-G-45204 over 50μ [1.27μm] min. Nickel per SAE-AMS-QQ-N-290.
- Contact current rating=8 Amps.
- Operating temperature= -67° to 221°F [-55° to 105°C].
- Insertion Force=240 grams/pin; Withdrawal Force=130 grams/pin; Normal Force=210 grams/pin; based on a .040 [1.02] diameter test lead.
- · Accepts leads .032-.047 [.81-1.19] in diameter, .130-.180 [3.30-4.561 long.

#### MOUNTING CONSIDERATIONS:


• Suggested PCB hole size=.081 ± .002 [2.03 ± .05] dia.




Note: Aries specializes in custom design and production. In addition to the standard products shown on this page, special materials, platings, sizes, and configurations can be furnished, depending on quantities. Aries reserves the right to change product specifications without notice.


## ORDERING INFORMATION

XX - F40 - 10 XX Plating Option: No. of Pins: TL = Tin/Lead 2 - 20 (even # only) Series Ex. 02 = 2 pins Tin Plating 14 = 14 pins





Consult Data Sheet No. 16007 for thru-hole male DIP strips.







16008 REV. E

TEL: (215) 781-9956

FAX: (215) 781-9845

ELECTRONICS, INC.

http://www.arieselec.com • info@arieselec.com