



- Wrapost double row strip sockets are available with 1 - 4 level wraposts:
 - 1-Level uses pin # 0040-1
 - 2-Level uses pin # 0089-2
 - 3-Level uses pin # 0088-3
 - 4-Level uses pin # 0086-4
 - See page 166 for details.
- Hi-Rel, 4-finger BeCu #30 contact is rated at 3 amps. See page 218 for details.
- Insulators are high temp. thermoplastic.



Ordering Information

Fig. 1	Series 421...001 1 Level Wrapost
	421-XX-2__-41-001000 Specify # of pins → 02-64
Fig. 2	Series 422...001 2 Level Wrapost
	422-XX-2__-41-001000 Specify # of pins → 02-64
Fig. 3	Series 423...001 3 Level Wrapost
	423-XX-2__-41-001000 Specify # of pins → 02-64
Fig. 4	Series 424...002 4 Level Wrapost
	424-XX-2__-41-002000 Specify # of pins → 02-64

For Electrical, Mechanical & Environmental Data, See pg. 4

XX=Plating Code See Below

For RoHS compliance select ◊ plating code.

SPECIFY PLATING CODE XX=	13 ◊	93		43 ◊
Sleeve (Pin)	0,25µm Au	5,08µm Sn/Pb		5,08µm Sn
Contact (Clip)	0,76µm Au	0,76µm Au		0,76µm Au