



General ordering data

Order No.	1688110000
Part designation	ZTA 4
Version	Modular terminal, accessories, Test adapter
EAN	4008190855666
Qty.	25 pc(s).

Product notes

Product description	The clip-on test adapter ZTA is used as a single thin element and as a test adapter strip for measurements in electrical cabinets. Conductors with cross-sections from 0.5 mm ² to 1.5 mm ² can be connected. The test adapter simply clips onto the terminal and thus guarantees reliable contact with the live busbar.
---------------------	--

Additional technical data

Installation advice	Direct mounting
---------------------	-----------------

Conductors for clamping (rated connection)

Clamping range, min.	0.5 mm ²
Clamping range, max.	1.5 mm ²
Type of connection	Plug-in connection
Stripping length	10 mm
Solid, min.	0.5 mm
Solid, max.	1.5 mm
Flexible, min.	0.5 mm
Flexible, max.	1.5 mm
Flexible with ferrule, min. (DIN 46228/1)	0.5 mm
Flexible with ferrule, max. (DIN 46228/1)	1.5 mm

Dimensions

Width	5.1 mm
Height of lowest version	69 mm
Length	31 mm

Dimensions**Rating data**

Rated cross-section	1.5 mm ²
Rated current	11 A

Test adapter

Function	Test adapter
With snap-in pegs	Yes

Test adapter dimensions

Height with TS 35	69 mm
With snap-in pegs	Yes

Test adapter rated data

Rated voltage	250 V
---------------	-------

Approvals

Approvals institutes

**Classifications**

eClass 4.1	NK
eClass 5.0	NK
eClass 5.1	NK

Similar products

Order No.	Part designation	Version
-----------	------------------	---------