General ordering data	
Order No.	1062060000
Part designation	WTA 5/10
Version	Modular terminal, accessories, Test adapter
EAN	4008190020781
Qty.	5 pc(s).
Product notes Note, technical data	Rated current 6 A
	Raled current of A
Additional technical data	
Installation advice	Direct mounting
CSA rating data	
Voltage (CSA)	300 V
CSA current	6 A
Conductors for clamping (additional connection)	
Clamping range, max.	1 mm ²
Rated cross-section	0.75 mm ²
Conductors for clamping (rated connection)	
Type of connection	Plug-in connection
No. of connections	1
Stripping length	6 mm
Solid, min.	0.5 mm ²
Solid, max.	1 mm ²
Flexible, min.	1 mm ²
Flexible, max.	1 mm ²
Flexible with ferrule, min. (DIN 46228/1) Flexible with ferrule, max. (DIN 46228/1)	0.5 mm² 1 mm²
Dimensions	
Width	5 mm
	-1- Weidmüller 🟵

Dimensions	
Height of lowest version	68.2 mm
Length	17 mm
ç	
Rated cross-section	0.75 mm ²
Rated voltage	250 V
Rated current	6 A
Function	Test adapter
With snap-in pegs	Yes
Height with TS 35	68.2 mm
With snap-in pegs	Yes
Rated voltage	250 V
-	
UL rating data	
Voltage (UL)	300 V
Current (UL)	6 A
Approvals institutes	
	(P (p)
	ME25
Classifications	
eClass 4.1	27-14-11-99
eClass 5.0	27-14-11-45
eClass 5.1	27-14-11-45
Similar products	
Order No. Part designation	Version
1051260000 WTA 5/1	Modular terminal, accessories, Test adapter

