


PART NO	WIRE RANGE AWG (mm <sup>2</sup> )	COLOR	STRIP LENGTH : 1/16", 1/8", 3/16"	L	P	ID-1	OD-1	MAX WIRE INSUL DIA	OD-2	INSTALLATION TOOLS
FSF72-6-D	26 (0,14)	BROWN	3/8 (9,5)	0,41 (10,5)	0,24 (6,0)	0,03 (0,8)	0,04 (1,1)	0,07 (1,7)	0,10 (2,5)	CT-1002
FSF72-8-D			15/32 (11,9)	0,49 (12,5)	0,31 (8,0)	0,03 (0,8)	0,04 (1,1)	0,07 (1,7)	0,10 (2,5)	
FSF73-6-D	24 (0,25)	VIOLET	3/8 (9,5)	0,41 (10,5)	0,24 (6,0)	0,03 (0,8)	0,04 (1,1)	0,07 (1,7)	0,10 (2,5)	CT-1123
FSF73-8-D			15/32 (11,9)	0,49 (12,5)	0,31 (8,0)	0,03 (0,8)	0,04 (1,1)	0,07 (1,7)	0,10 (2,5)	
FSF74-6-D	24 (0,34)	PINK	3/8 (9,5)	0,41 (10,5)	0,24 (6,0)	0,03 (0,8)	0,04 (1,1)	0,07 (1,7)	0,10 (2,5)	CT-1002
FSF74-8-D			15/32 (11,9)	0,49 (12,5)	0,31 (8,0)	0,03 (0,8)	0,04 (1,1)	0,07 (1,7)	0,10 (2,5)	
FSF75-6-D	22 (0,50)	WHITE	3/8 (9,5)	0,45 (11,5)	0,24 (6,0)	0,04 (1,1)	0,06 (1,4)	0,09 (2,2)	0,12 (3,0)	CT-1002
FSF75-8-D			15/32 (11,9)	0,53 (13,5)	0,31 (8,0)	0,04 (1,1)	0,06 (1,4)	0,09 (2,2)	0,12 (3,0)	
FSF75-10-D			17/32 (13,5)	0,61 (15,5)	0,39 (10,0)	0,04 (1,1)	0,06 (1,4)	0,09 (2,2)	0,12 (3,0)	CT-1003
FSF76-6-D	20 (0,75)	BLUE	3/8 (9,5)	0,47 (12,0)	0,24 (6,0)	0,05 (1,3)	0,06 (1,6)	0,09 (2,4)	0,13 (3,2)	
FSF76-8-D			15/32 (11,9)	0,55 (14,0)	0,31 (8,0)	0,05 (1,3)	0,06 (1,6)	0,09 (2,4)	0,13 (3,2)	CT-1004
FSF76-10-D			17/32 (13,5)	0,63 (16,0)	0,39 (10,0)	0,05 (1,3)	0,06 (1,6)	0,09 (2,4)	0,13 (3,2)	
FSF76-12-D			5/8 (15,9)	0,71 (18,0)	0,47 (12,0)	0,05 (1,3)	0,06 (1,6)	0,09 (2,4)	0,13 (3,2)	CT-1003
FSF77-6-D	18 (1,1)	RED	3/8 (9,5)	0,49 (12,5)	0,24 (6,0)	0,06 (1,5)	0,07 (1,8)	0,11 (2,7)	0,14 (3,6)	
FSF77-8-D			15/32 (11,9)	0,57 (14,5)	0,31 (8,0)	0,06 (1,5)	0,07 (1,8)	0,11 (2,7)	0,14 (3,6)	CT-1123
FSF77-10-D			17/32 (13,5)	0,65 (16,5)	0,39 (10,0)	0,06 (1,5)	0,07 (1,8)	0,11 (2,7)	0,14 (3,6)	
FSF77-12-D			5/8 (15,9)	0,73 (18,5)	0,47 (12,0)	0,06 (1,5)	0,07 (1,8)	0,11 (2,7)	0,14 (3,6)	CT-1005
FSF78-6-D	16 (1,50)	BLACK	3/8 (9,5)	0,49 (12,5)	0,24 (6,0)	0,07 (1,8)	0,08 (2,1)	0,12 (3,0)	0,16 (4,0)	
FSF78-8-D			15/32 (11,9)	0,57 (14,5)	0,31 (8,0)	0,07 (1,8)	0,08 (2,1)	0,12 (3,0)	0,16 (4,0)	CT-1006
FSF78-10-D			17/32 (13,5)	0,65 (16,5)	0,39 (10,0)	0,07 (1,8)	0,08 (2,1)	0,12 (3,0)	0,16 (4,0)	
FSF78-12-D			5/8 (15,9)	0,73 (18,5)	0,47 (12,0)	0,07 (1,8)	0,08 (2,1)	0,12 (3,0)	0,16 (4,0)	CT-1006
FSF78-18-D			7/8 (22,2)	0,96 (24,5)	0,71 (18,0)	0,07 (1,8)	0,08 (2,1)	0,12 (3,0)	0,16 (4,0)	

PART NO	WIRE RANGE AWG (mm <sup>2</sup> )	COLOR	STRIP LENGTH : 1/16", 1/8", 3/16"	L	P	ID-1	OD-1	MAX WIRE INSUL DIA	OD-2	INSTALLATION TOOLS
FSF79-8-D	14 (2,08)	YELLOW	15/32 (11,9)	0,57 (14,5)	0,31 (8,0)	0,08 (2,1)	0,09 (2,2)	0,13 (3,2)	0,17 (4,2)	CT-1002
FSF80-8-D			15/32 (11,9)	0,59 (15,0)	0,31 (8,0)	0,09 (2,3)	0,10 (2,6)	0,15 (3,7)	0,19 (4,8)	
FSF80-12-D		GREY	5/8 (15,9)	0,75 (19,0)	0,47 (12,0)	0,09 (2,3)	0,10 (2,6)	0,15 (3,7)	0,19 (4,8)	CT-1003
FSF80-18-D			7/8 (22,2)	0,98 (25,0)	0,71 (18,0)	0,09 (2,3)	0,10 (2,6)	0,15 (3,7)	0,19 (4,8)	
FSF81-10-D			17/32 (13,5)	0,69 (17,5)	0,39 (10,0)	0,11 (2,9)	0,13 (3,3)	0,17 (4,3)	0,21 (5,4)	CT-1123
FSF81-12-C	12 (4)	ORANGE	5/8 (15,9)	0,79 (20,0)	0,47 (12,0)	0,11 (2,9)	0,13 (3,3)	0,17 (4,3)	0,21 (5,4)	
FSF81-18-C			7/8 (22,2)	1,02 (26,0)	0,71 (18,0)	0,11 (2,9)	0,13 (3,3)	0,17 (4,3)	0,21 (5,4)	CT-1003
FSF82-12-C	10 (6)	GREEN	5/8 (15,9)	0,79 (20,0)	0,47 (12,0)	0,14 (3,6)	0,16 (4,0)	0,22 (5,5)	0,27 (6,9)	
FSF82-18-C			7/8 (22,2)	1,02 (26,0)	0,71 (18,0)	0,14 (3,6)	0,16 (4,0)	0,22 (5,5)	0,27 (6,9)	CT-1004
FSF83-12-C	8 (10)	BROWN	5/8 (15,9)	0,83 (21,0)	0,47 (12,0)	0,14 (3,6)	0,15 (3,8)	0,20 (5,1)	0,27 (6,9)	
FSF83-18-C			7/8 (22,2)	1,06 (27,0)	0,71 (18,0)	0,14 (3,6)	0,15 (3,8)	0,20 (5,1)	0,27 (6,9)	CT-1104
FSF84-12-C	6 (16)	WHITE	5/8 (15,9)	0,91 (23,0)	0,47 (12,0)	0,16 (4,0)	0,25 (6,4)	0,32 (8,1)	0,38 (9,6)	
FSF84-18-C			7/8 (22,2)	1,14 (29,0)	0,71 (18,0)	0,16 (4,0)	0,25 (6,4)	0,32 (8,1)	0,38 (9,6)	CT-1005
FSF85-16-L	4 (5)	BLACK	3/4 (19,1)	1,14 (29,0)	0,63 (16,0)	0,16 (4,0)	0,17 (4,3)	0,25 (6,4)	0,32 (8,1)	
FSF85-18-L			7/8 (22,2)	1,22 (31,0)	0,71 (18,0)	0,16 (4,0)	0,17 (4,3)	0,25 (6,4)	0,32 (8,1)	CT-1006
FSF85-22-L			1 (25,4)	1,38 (35,0)	0,87 (22,0)	0,16 (4,0)	0,17 (4,3)	0,25 (6,4)	0,32 (8,1)	
FSF86-16-L			3/4 (19,1)	1,18 (30,0)	0,63 (16,0)	0,16 (4,0)	0,17 (4,3)	0,25 (6,4)	0,32 (8,1)	CT-1006
FSF86-18-L	2 (35)	RED	7/8 (22,2)	1,26 (32,0)	0,71 (18,0)	0,16 (4,0)	0,17 (4,3)	0,25 (6,4)	0,32 (8,1)	
FSF86-25-L			1 1/8 (28,6)	1,54 (39,0)	0,98 (25,0)	0,16 (4,0)	0,17 (4,3)	0,25 (6,4)	0,32 (8,1)	CT-1006
FSF87-20-L	1 (50)	BLUE	15/16 (23,8)	1,42 (36,0)	0,79 (20,0)	0,16 (4,0)	0,17 (4,3)	0,25 (6,4)	0,32 (8,1)	
FSF87-25-O			1 1/8 (28,6)	1,61 (41,0)	0,98 (25,0)	0,16 (4,0)	0,17 (4,3)	0,25 (6,4)	0,32 (8,1)	

NOTES:

- MATERIAL:
  - A. STAMPING - COPPER, TIN PLATED
  - B. HOUSING - POLYPROPYLENE, COLOR CODED
- DIMENSIONS IN BRACKETS ARE IN mm OR mm<sup>2</sup>
- FOR TOLERANCING REFER TO DIN 46228 PART 4
- PACKAGE QTY.:
  - 0:25
  - L:50
  - C:100
  - D:500



REV	DATE	BY	CHK	DESCRIPTION	ECN #	PM	CUST	SCALE	DWG SIZE
07	05/09	SRB	LCA	OD-1 was 0.05(1,3) for FSF72, FSF73, FSF74					
06	03/08	BCT	LCA	ADDED SQUARE CRIMP TOOLS CT-1123 & CT-1104 TO THE INSTALLATION TOOLS	NLECN00429	RRE			
05	4/07	BCT	BCT	MODIFIED PART LENGTH TO 'L'; MODIFIED MAX. WIRE INSUL. DIA. TO 2 DECIMAL PLACES	TRO0252	TRO	LCA		
04	10/05	DAW	DAW	MAX INSUL DIA COLUMN WAS ID-2. UPDATED ALL MAX INSULATION DIAMETERS.	TRO0027				
03	1/01	EJS	SKB	ADDED PACKAGE CODE TO PART NUMBER. ADDED NOTE 4	08912	CCH	JAC		
02	3/99	JKD	SKB	WIRE RANGE FOR CT-1003 TOOL WAS 14-8 AWG	07519	TRO	JCU		
01	3/99	JKD	SKB	WIRE RANGE WAS 22 FOR FSF74-6 & -8, 20 FOR FSF75-6, -8 & -10	07488	TRO	JCU		
00	2/99	JKD	SKB	RELEASED	07459	TRO	JCU		
REV	DATE	BY	CHK	DESCRIPTION	ECN #	PM	CUST	SCALE	DWG SIZE

CAD FILENAME/LAYERS

**PANDUIT** CORP TINLEY PARK, ILLINOIS

FERRULE - SINGLE WIRE (FRENCH)

UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: (XXX) ± ANGLES ±

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION

DRAWN BY: JKD MAT'L: NONE

DATE: 2/9/99

DRAWING NO. A41668

DWG SIZE: B