


UM 45-FLK10

Order No.: 2962544

The illustration shows a 34-pos. version

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2962544>VARIOFACE module, with screw connection and flat-ribbon cable
connector, for assembly on NS 35/7.5, 10 positions

Commercial data

EAN	4017918087210
Pack	1 pcs.
Customs tariff	85369010
Weight/Piece	0.0751 KG
Catalog page information	Page 244 (IF-2007)

Product notes

WEEE/RoHS-compliant since:
09/11/2006

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data

Nominal voltage U_N	25 V AC
	60 V DC
Max. current carrying capacity per branch	1 A
Number of positions	10

Width	54 mm
Height	50 mm
Depth	45 mm
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Test voltage input/output	500 V AC
Mounting position	Any
Standards/regulations	IEC 60664
	DIN EN 50178
	DIN VDE 110
Pollution degree	2
Surge voltage category	II

Connection data

Connection 1	PCB connection
Connection in acc. with standard	IEC / EN
Type of connection	Screw connection
Conductor cross section solid min.	0.14 mm ²
Conductor cross section solid max.	1.5 mm ²
Conductor cross section stranded min.	0.14 mm ²
Conductor cross section stranded max.	1.5 mm ²
Conductor cross section AWG/kcmil min.	26
Conductor cross section AWG/kcmil max	16
Stripping length	6 mm
Screw thread	M3
Connection 2	Flat-ribbon cable connection
Type of connection	Pluggable

Certificates / Approvals

Certification

CUL, GOST, UL

CUL

Nominal voltage U _N	125 V
--------------------------------	-------


Nominal current I_N	1 A
UL	
Nominal voltage U_N	125 V
Nominal current I_N	1 A

Accessories

Item	Designation	Description
Cable/conductor		
2299204	FLK 10/EZ-DR/ 50/KONFEK	Round cable set, with two 10-pos. socket strips, (1:1 connection), cable length: 0.5 m
2299217	FLK 10/EZ-DR/ 100/KONFEK	Round cable set, with two 10-pos. socket strips (1:1 connection), cable length: 1 m
2299220	FLK 10/EZ-DR/ 150/KONFEK	Round cable set, with two 10-pos. socket strips (1:1 connection), cable length: 1.5 m
2299233	FLK 10/EZ-DR/ 200/KONFEK	Round cable set, with two 10-pos. socket strips, (1:1 connection), cable length: 2 m
2299246	FLK 10/EZ-DR/ 300/KONFEK	Round cable set, with two 10-pos. socket strips (1:1 connection), cable length: 3 m
2299259	FLK 10/EZ-DR/ 400/KONFEK	Round cable set, with two 10-pos. socket strips (1:1 connection), cable length: 4 m
2299262	FLK 10/EZ-DR/ 600/KONFEK	Round cable set, with two 10-pos. socket strips (1:1 connection), cable length: 6 m
2299275	FLK 10/EZ-DR/ 800/KONFEK	Round cable set, with two 10-pos. socket strips (1:1 connection), cable length: 8 m
2299288	FLK 10/EZ-DR/1000/KONFEK	Round cable set, with two 10-pos. socket strips (1:1 connection), cable length: 10 m
2295059	FLK EZ-DR.../.../...	Round cable, with preassembly, not shielded, variable cable length

Diagrams/Drawings

Circuit diagram



Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;