

## ► General data

---



Screw-type socket strip, type F, 32-position, equipped in rows z + d, one 1.5 mm<sup>2</sup> screw connection per position

Order number	2285195
Type	SFL 1,5/F32/ZD
<hr/>	
Barcode number	4017918055882
Unit pack	10 Piece
Customs tariff	85369010000

---

## ► Technical data

---

**Dimensions / positions**

Length	14.8 mm
Height	37.7 mm
Width	95 mm
Number of positions	32
Hole diameter	2.8 mm
Screw thread	M 3
Tightening torque	0.4 Nm

---

**Technical data**

Insulating material group	II
Rated surge voltage (III/3)	4 kV
Connection in acc. with standard	IEC/ DIN VDE
Nominal current $I_N$	4 A
Nominal voltage $U_N$	250 V
Insulating material	PA-F
Inflammability class acc. to UL 94	HB
Stripping length	10 mm

---

**Connection data**


Min. conductor cross section, rigid	0.5 mm <sup>2</sup>
Conductor cross section, rigid max.	1.5 mm <sup>2</sup>
Conductor cross section flexible min.	0.5 mm <sup>2</sup>
Max. conductor cross section, flexible	1.5 mm <sup>2</sup>
Min. conductor cross section AWG/kcmil	20
Conductor cross section AWG/kcmil max	16

---

## ▶ Drawings

---

### Dimensioned drawing



## ► Accessories

---

Item	Designation	Description
<b>Tools</b>		
1205040	SZS 0,6X2,5	Screwdriver, bladed, matches SFL screw socket strips, blade: 0.6 x 2.5 mm

---

## ► Address

---

Phoenix Contact GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel + 49 - (0) 52 35 - 3-00  
Fax + 49 - (0) 52 35 - 3-4 12 00  
[www.phoenixcontact.com](http://www.phoenixcontact.com)

© Phoenix Contact  
Technical modifications reserved