

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT - By - ALL RIGHTS RESERVED.




MATERIAL:  
 HOUSING: THERMOPLASTIC PA, UL94V-0, BLACK.  
 TERMINAL: BRIGHT TIN PLATED, COPPER ALLOY.  
 SCREW: 6-32, STEEL, ZINC PLATED CLEAR CHROMATE.

ELECTRICAL:  
 UL CLASS C: 20A, 150V.  
 UL CLASS D: 10A, 300V.  
 CSA TYPE B: 20A, 300V.  
 CSA TYPE C: 20A, 300V.  
 CSA TYPE D: 10A, 300V.  
 CSA TYPE E: 20A, 300V.  
 WIRE RANGE: 12-22 AWG

△ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

MECHANICAL:  
 MAXIMUM TORQUE RATING: 7 IN-LBS.  
 RUNNING TORQUE: 0.5-3.5 IN-LBS UNLESS OTHERWISE STATED.

- ① SCREWS ARE BOTTOMED, NO THREAD INTERRUPT.
- ② SCREWS ARE NICKEL PLATED BRASS.
- ③ SCREWS ARE CAPTIVE.
- ④ SEE FIGURE.
- ⑤ PRELIMINARY PART NUMBER.



RECOMMENDED PCB LAYOUT

LOC	DIST	REVISIONS							
		P	LTR	DESCRIPTION	DATE	DWN	APVD		
FT	0								
		N3		REVISED PER ECO-11-004587	11MAR11	RK	HMR		
⑤ ④	.160			4DB-P108-18	5.915	18		4-1437667-4	
	.160			4DB-P108-16-105	5.590	17		2-796628-4	
	.160			4DB-P108-17	5.590	17		4-1437667-2	
	.160			4DB-P108-16	5.265	16		4-1437667-0	
	.160			4DB-P108-15	4.940	15		3-1437667-9	
② ①	.160			4DB-P108-14-102	4.615	14		2-796658-5	
②	.160			4DB-P108-14-102	4.615	14		2-796658-3	
	.160			4DB-P108-14	4.615	14		3-1437667-8	
	.160			4DB-P108-13	4.290	13		3-1437667-7	
	.160			4DB-P108-12	3.965	12		3-1437667-6	
	.160			4DB-P108-11	3.640	11		3-1437667-5	
	.160			4DB-P108-10	3.315	10		3-1437667-3	
⑤ ②	.160			4DB-P106-09-094	2.990	9		1-796658-7	
	.160			4DB-P108-09	2.990	9		3-1437667-2	
⑥ ①	OBsolete	.160		4DB-P108-08-091	2.665	8		1-796658-4	
	.160			4DB-P108-08	2.665	8		3-1437667-1	
⑤ ③ ②	.160			4DB-P106-07-100	2.340	7		2-796658-2	
	.160			4DB-P106-07-093	2.340	7		1-796658-6	
	.160			4DB-P108-07	2.340	7		3-1437667-0	
⑤ ③ ②	.160			4DB-P106-06-099	2.015	6		2-796658-1	
⑥ ①	OBsolete	.160		4DB-P108-06-090	2.015	6		1-796658-3	
⑤	.200			4DB-P108-06	2.015	6		2-796658-6	
	.160			4DB-P108-06	2.015	6		2-1437667-9	
⑤ ③ ②	.160			4DB-P106-05-098	1.690	5		2-796658-0	
⑥ ④	OBsolete	.160		4DB-P108-05-093	1.690	5		1-796658-5	
	.160			4DB-P108-05	1.690	5		2-1437667-8	
⑤ ③ ②	.160			4DB-P106-04-097	1.365	4		1-796658-9	
①	.160			4DB-P108-04-089	1.365	4		1-796658-2	
	.160			4DB-P108-04	1.365	4		2-1437667-6	
⑤ ③ ②	.160			4DB-P106-03-096	1.040	3		1-796658-8	
⑥ ①	.160			4DB-P108-03-088	1.040	3		1-796658-1	
	.160			4DB-P108-03	1.040	3		2-1437667-5	
	.160			4DB-P108-02	.715	2		2-1437667-4	

DIM B	CATALOG NUMBER	DIM A	NO OF POSN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S WELDON 01MAY2003		TE Connectivity ASSEMBLY, DUAL BARRIER 4DB-P108-XX	
DIMENSIONS: INCHES		CHK S YODER 5/1/03			
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD S YODER 5/1/03			
0 PLC ± - 1 PLC ± - 2 PLC ± .01 3 PLC ± .005 4 PLC ± - ANGLES ± 1°		NAME			
MATERIAL		FINISH		SIZE CAGE CODE DRAWING NO RESTRICTED TO	
				A3 00779 C-2-1437667-4	
CUSTOMER DRAWING				SCALE NTS SHEET 1 of 2 REV N3	

4


3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS				
P	LTR	DESCRIPTION	DATE	DWN	APVD	
-	-	SEE SHEET 1	-	-	-	



2-796658-4

.160	4DB-P108-30	9.815	30	5-1437667-5
.160	4DB-P108-29	9.490	29	796658-9
.160	4DB-P108-28	9.165	28	5-1437667-3
.160	4DB-P108-27	8.840	27	796658-8
.160	4DB-P108-26	8.515	26	5-1437667-2
.160	4DB-P108-25	8.190	25	796658-7
.160	4DB-P108-24	7.865	24	5-1437667-0
.160	4DB-P108-23	7.540	23	796658-6
.160	4DB-P108-22	7.215	22	4-1437667-8
.160	4DB-P108-21	6.890	21	796658-2
.160	4DB-P108-20	6.565	20	4-1437667-6
.160	4DB-P108-19	6.240	19	4-1437667-5
DIM B	CATALOG NUMBER	DIM A	NO OF POSN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S WELDON 01MAY2003	<b>STE</b> TE Connectivity	
DIMENSIONS: INCHES		CHK S YODER 5/1/03		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD S YODER 5/1/03	NAME ASSEMBLY, DUAL BARRIER 4DB-P108-XX	
0 PLC ± -		PRODUCT SPEC	RESTRICTED TO	
1 PLC ± -		APPLICATION SPEC	SIZE A3	CAGE CODE 00779
2 PLC ± .01		WEIGHT	DRAWING NO C-2-1437667-4	SCALE NTS
3 PLC ± .005		MATERIAL	SHEET 2 of 2	REV N3
4 PLC ± -		FINISH	CUSTOMER DRAWING	
ANGLES ± 1°				