



NUMBER OF CIRCUITS	"A" DIM.	"B" DIM.	"C" DIM.	MATERIAL NUMBER
01	5.46 [0.215]	N/A	N/A	391000901
02	13.46 [0.530]	8.00 [0.315]	N/A	391000902
03	21.46 [0.845]	16.00 [0.630]	8.00 [0.315]	391000903
04	29.46 [1.160]	24.00 [0.945]	16.00 [0.630]	391000904
05	37.47 [1.475]	32.00 [1.260]	24.00 [0.945]	391000905
06	45.47 [1.790]	40.01 [1.575]	32.00 [1.260]	391000906
07	53.47 [2.105]	48.01 [1.890]	40.01 [1.575]	391000907
08	61.47 [2.420]	56.01 [2.205]	48.01 [1.890]	391000908
09	69.47 [2.735]	64.01 [2.520]	56.01 [2.205]	391000909
10	77.47 [3.050]	72.01 [2.835]	64.01 [2.520]	391000910
11	85.47 [3.365]	80.01 [3.150]	72.01 [2.835]	391000911
12	93.47 [3.680]	88.01 [3.465]	80.01 [3.150]	391000912

- NOTES:
1. MATERIAL: SEE TABLE
 2. FINISHES: SEE TABLE
 3. "XX" REFERS TO THE NUMBER OF CIRCUITS
 4. ASSEMBLY IS ROHS COMPLIANT BY EXEMPTION. COMPONENTS MARKED WITH AN ASTERISK (*) ARE ROHS COMPLIANT BY EXEMPTION, ALL OTHERS ARE ROHS COMPLIANT.

ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH
4	XX*2	CLAMPING SCREWS, M2.6 (B)	STEEL	ZINC
3	XX	WIRE PROTECTOR	BRASS	NICKEL
2	XX	TERMINAL (*)	BRASS	NICKEL
1	1	INSULATOR	NYLON 6	CLEAR

REVISED & REDRAWN
 EC NO: WNA2010-0649
 DRAWN: CLYORK 2010/04/26
 CHECKED: DTITUS 2010/04/26
 APPROVED: DTITUS 2010/04/26

QUALITY SYMBOLS
 ▽=0
 ▽=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± .005
2 PLACES	± 0.13	± .010
1 PLACE	± 0.3	± ---
ANGULAR ± 2 °		

DRAFT WHERE APPLICABLE
 MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM/IN
 SCALE: 2:1
 DESIGN UNITS: INCH
 THIRD ANGLE PROJECTION
 DRAWN BY: CLYORK DATE: 2010/04/26
 CHECKED BY: DTITUS DATE: 2010/04/26
 APPROVED BY: DTITUS DATE: 2010/04/26
 MATERIAL NO. SEE CHART

TITLE: 8MM PITCH LOW PROFILE WITH WIRE PROTECTORS
 MOLEX INCORPORATED
 DOCUMENT NO. SD-39100-001
 SHEET NO. 1 OF 1
 THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION