

4

3

2

1







THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

MATERIAL:  
 HOUSING: THERMOPLASTIC, UL94V-0 BLACK.  
 TERMINALS: BRIGHT TIN PLATED, COPPER ALLOY.  
 SCREWS: 6-32, STEEL, ZINC PLATED WITH CLEAR CHROMATE.  
 UNLESS OTHERWISE NOTED.

ELECTRICAL:  
 RATED CURRENT UL/CSA:  
 CLASS C: 25A, 300V.  
 CLASS D: 5A, 600V.  
 WIRE RANGE: 12-22 AWG

MECHANICAL:  
 RECOMMENDED TIGHTENING TORQUE: 7 IN.-LBS.  
 OPERATING TEMP.: 105°C MAX

- △ MARK WITH WHITE PERMANENT INK.
- 2 ALL SCREWS TO BE DRIVEN DOWN TO TERMINAL SURFACE.
- 3 STAINLESS STEEL SCREWS.
- 4 NICKEL PLATED BRASS SCREWS.
- 5 PRELIMINARY PART NUMBER.



LOC		DIBT		REVISIONS			
P	LTR	DESCRIPTION	DATE	BY	APPD		
	C3	REVISED PER ECO-11-004587	11MAR11	RK	HMR		
		11.311	30	6PCV-30-007	8-1546158-7		
		11.311	30	6PCV-30-007	1546814-2		
		10.936	29	6PCV-29-007	1546814-1		
		10.561	28	6PCV-28-007	2-1546686-1		
		10.186	27	6PCV-27-007	2-1546686-0		
		9.811	26	6PCV-26-007	8-1546158-4		
		9.436	25	6PCV-25-007	1-1546686-9		
		9.061	24	6PCV-24-723	3-1437654-8		
		9.061	24	6PCV-24-007	8-1546158-3		
		8.686	23	6PCV-23-007	1-1546686-8		
		8.311	22	6PCV-22-007	1-1546686-7		
		7.936	21	6PCV-21-007	1-1546686-6		
		7.561	20	6PCV-20-720	2-1437654-7		
		7.561	20	6PCV-20-1360	7-1546158-7		
		7.561	20	6PCV-20-1359	7-1546158-6		
		7.186	19	6PCV-19-007	7-1546158-3		
		6.811	18	6PCV-18-1390	1546262-5		
		6.811	18	6PCV-18-007	1437654-8		
		6.436	17	6PCV-17-1206	1437654-1		
		6.436	17	6PCV-17-007	1-1546686-4		
		6.061	16	6PCV-16-719	9-1437653-4		
		6.061	16	6PCV-16-007	8-1437653-1		
		5.686	15	6PCV-15-993	7-1437653-6		
		5.686	15	6PCV-15-007	7-1437653-5		
		5.311	14	6PCV-14-1205	7-1437653-0		
		5.311	14	6PCV-14-007	6-1437653-7		
		4.936	13	6PCV-13-1194	6-1437653-5		
		4.936	13	6PCV-13-007	6-1546158-7		
		4.561	12	6PCV-12-718	5-1437653-8		
		4.561	12	6PCV-12-007	5-1437653-2		
		4.186	11	6PCV-11-007	1-1546686-3		
		3.811	10	6PCV-10-003	6-1546158-1		
		3.811	10	6PCV-10-1193	3-1437653-8		
		3.811	10	6PCV-10-007	3-1437653-6		
		3.436	9	6PCV-09-003	5-1546686-5		
		3.436	9	6PCV-09-1270	2-1437653-8		
		3.436	9	6PCV-09-007	2-1437653-6		
		3.061	8	6PCV-08-1397	5-1546686-4		
		3.061	8	6PCV-08-717	1-1437653-9		
		2.686	7	6PCV-07-007	1437653-4		
		2.311	6	6PCV-06-716	1437653-1		
		2.311	6	6PCV-06-007	9-1437652-6		
		1.936	5	6PCV-05-1396	5-1546686-3		
		1.936	5	6PCV-05-1341	8-1437652-6		
		1.936	5	6PCV-05-007	5-1546158-1		
		1.561	4	6PCV-04-715	7-1437652-5		
		1.561	4	6PCV-04-007	6-1437652-8		
		1.186	3	6PCV-03-1256	4-1546158-7		
		1.186	3	6PCV-03-003	1546119-2		
		1.186	3	6PCV-03-007	5-1437652-5		
		.811	2	6PCV-02-1395	5-1546686-2		
		.811	2	6PCV-02-1339	4-1437652-6		
		.811	2	6PCV-02-007	4-1437652-0		

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES DIMENSIONS: MILLIMETERS FINISH	DIM: S. SCHLEGEL 23MPR03 OK: S. YODER 4/23/04 S. YODER S. YODER 4/23/04 PRODUCT SPEC: APPLICATION SPEC: WEIGHT:	DIM: S. SCHLEGEL 23MPR03 OK: S. YODER 4/23/04 S. YODER S. YODER 4/23/04 PRODUCT SPEC: APPLICATION SPEC: WEIGHT:	NAME: 6PCV-XX-007 ASSEMBLY SIZE: A2 CASE CODE: 00779 DRAWING NO: C-1437652-0 RESTRICTED TO:
---	---	---	--

CUSTOMER DRAWING SCALE: NTS SHEET 1 of 1 REV: C3

4-1437652-0

A

D

C

B

A