

General ordering data

Order No.	1690010000
Part designation	ZDK 2.5/LD RT/1
Version	Special terminal, special connections, 2.5 mm ² , Tension clamp connection, Wemid, dark beige, TS 35
EAN	4008190898274
Qty.	50 pc(s).

Product notes

Note, ordering data	Current of continuous busbar = 10 A
Note, technical data	2.5 mm ² flexible conductors with wire-end ferrules are crimped with the Weidmüller PZ 6/5 crimping tool.
Product description	Z-series standard ranges provide solutions for conductor cross-sections from 0.05 to 35 mm ² .

Additional technical data

Colour of insulating material	dark beige
Connection direction	top
Electronic component	red LED
End plate required	Yes
Explosion-tested version "Ex e"	Yes
Installation advice	TS 35
Insulating material	Wemid
Levels cross-connected internally	No
No. of levels	2
No. of terminal strips per level	2
Open sides	right
Operating temperature range	- 50 °C, + 120 °C
Product family	Z-series
Type of connection	Plugged
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	V-0
Version	Terminal with LED

CSA rating data

Voltage (CSA)	24 V
CSA current	10 A
Min. cross-section (CSA)	AWG 26
Max. cross-section (CSA)	AWG 12

Conductors for clamping (additional connection)

Flexible with ferrule, min. (DIN 46228 pt 1)	0.5 mm ²
Flexible with ferrule, max. (DIN 46228 pt 1)	2.5 mm ²

Conductors for clamping (rated connection)

Clamping range, min.	0.05 mm ²
Clamping range, max.	2.5 mm ²
Type of connection	Tension clamp connection
2nd type of connection	clamped

Conductors for clamping (rated connection)

Connection direction	top
No. of connections	4
Stripping length	10 mm
Blade size	0.6 x 3.5 mm
Gauge to IEC 60947-1	A2
Solid, min.	0.5 mm ²
Solid, max.	2.5 mm ²
Flexible, min.	0.5 mm ²
Flexible, max.	2.5 mm ²
Flexible with ferrule, min. (DIN 46228/1)	0.5 mm ²
Flexible with ferrule, max. (DIN 46228/1)	1.5 mm ²
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	1.5 mm ²
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	1.5 mm ²
AWG conductor size, min.	AWG 26
AWG conductor size, max.	AWG 12
AWG conductor size, min.	0.05 mm ²
AWG conductor size, max.	2.5 mm ²

Dimensions

Width	5.1 mm
Height of lowest version	54 mm
Length	79.1 mm
TS 35 offset	39 mm

Display element

Current	0.05 A
Indicator element	red
Operating voltage for display, max.	24 V
Operating voltage for display, min.	10 V
Type of voltage for indicator	DC

Fuse terminals

Current	0.05 A
Display	LED
Type of voltage for indicator	DC

Rating data

Rated cross-section	2.5 mm ²
Rated voltage	24 V
Rated current	10 A
Standards	IEC 60947-7-1
Pollution severity	3

UL rating data

Voltage (UL)	24 V
Current (UL)	10 A
Min. cross-section (UL)	AWG 30
Max. cross-section (UL)	AWG 12

Approvals

Approvals institutes



Classifications

eClass 4.1	27-14-11-31
eClass 5.0	27-14-11-31
eClass 5.1	27-14-11-31

Similar products

Order No.	Part designation	Version
1693940000	ZDK 2.5/LD RT/2	Special terminal, special connections, 2.5 mm ² , Tension clamp connection, Wemid, dark beige, TS 35