

- High density DIP headers and strips for devices featuring 1,78 lead spacing.
- Series 162 DIP headers use MM #6218 pins. See page 175 for details.
- Series 862 strip headers use MM #6218 pins. See page 175 for details.
- Insulators are high temperature thermoplastic.

Total number of pins				Quantity per tube	Ordering Information	
	A	B	C			

16	14,53	7,62	9,91	35	162-XX-316-00-180000	<p style="font-size: 0.8em; color: green; border: 1px solid green; padding: 2px;">For RoHS compliance select ◇ plating code.</p>
28	25,20	10,16	12,45	20	162-XX-428-00-180000	
30	26,97	10,16	12,45	18	162-XX-430-00-180000	
48	42,98	10,16	12,45	12	162-XX-448-00-180000	
20	18,08	15,24	17,53	28	162-XX-620-00-180000	<div style="border: 1px solid black; border-radius: 50%; padding: 10px; display: inline-block;"> <p style="font-size: 0.8em; color: blue; text-align: center;">For Electrical, Mechanical & Environmental Data, See pg. 4</p> </div> <div style="border: 1px solid black; border-radius: 50%; padding: 10px; display: inline-block; margin-left: 20px;"> <p style="font-size: 0.8em; color: blue; text-align: center;">XX=Plating Code See Below</p> </div>
28	25,20	15,24	17,53	20	162-XX-628-00-180000	
40	35,86	15,24	17,53	14	162-XX-640-00-180000	
42	37,64	15,24	17,53	13	162-XX-642-00-180000	
48	42,98	15,24	17,53	12	162-XX-648-00-180000	
52	46,53	15,24	17,53	11	162-XX-652-00-180000	
56	50,09	15,24	17,53	10	162-XX-656-00-180000	
64	57,20	15,24	17,53	9	162-XX-664-00-180000	
68	60,76	15,24	17,53	8	162-XX-668-00-180000	
64	57,20	19,05	21,34	8	162-XX-764-00-180000	

	<h3>SINGLE ROW STRIP HEADER</h3> <p>If desired, we will supply any length up to 21 pins.</p>
--	--

21	37,64	- - -	2,64	-	862-XX-121-00-180000
----	-------	-------	------	---	----------------------

SPECIFY PLATING CODE XX=	10◇	90	40◇	
Pin Plating	0,25µm Au	5,08µm Sn/Pb	5,08µm Sn	

Downloaded from Elcodis.com electronic components distributor