



JKL LAMP NUMBER	VOLTS RATED	AMPS ±10%	MSCP ±25%	LUMENS ±25%	AVERAGE LIFE HRS.	FILAMENT TYPE
1680	6.0	4.10	32.0	402.2	300	C-6
1295	12.5	3.00	50.0	628.5	300	C-2R
93	12.8	1.04	15.0	188.6	700	C-6
1156	12.8	2.10	32.0	402.2	1,200	C-6
305	28.0	.51	15.0	188.6	300	*C-2V
1691	28.0	.61	15.0	188.6	1,000	2C-2R
2232	28.0	.643	17.0	213.7	2,000	CC-8
307	28.0	.67	21.0	264.0	300	*C-2V
2233	28.0	.77	21.0	264.0	2,000	CC-8
1683	28.0	1.02	32.0	402.2	500	2C-6

\* SUPPORTED

REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE
B	DELETE PART NO'S 1073 & 1665	4/28/04
A	ADD PART NO. 2233	1/27/03
	RELEASED AS CAD	5/4/01

METRIC		DIMENSIONS ARE IN MILLIMETERS	
 THIRD ANGLE PROJECTION		TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0.20 ANGLE +/- 0	
DRAWN BY	APPV'D BY	DATE	
L. WENGSTROM	J.K.	4/28/04	
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			

<b>JKL</b> COMPONENTS CORPORATION			
TITLE S-8 SINGLE CONTACT BAYONET BASE LAMP			
SIZE	FSCM NO.	DRAWING NO.	
<b>A</b>	<b>55335</b>		<b>BAYONET SINGLE CONTACT S-8</b>
SCALE	RELEASED DATE	REVISION DATE	REV. NO.
NONE	5/4/01	4/28/04	<b>B</b>
			SHEET 1 OF 1