


UNCONTROLLED DOCUMENT

| | | |
|---------------|-------------------------------------|---------|
| PART NUMBER | | REV. |
| SSF-LXH250YID | | A |
| REV. | E.C.N. NUMBER AND REVISION COMMENTS | DATE |
| A | E.C.N. #10496. & #10BRDR & REDRAWN. | 4-12-99 |



| ELECTRO-OPTICAL CHARACTERISTICS T _A =25°C I _f =20mA | | | | | |
|---|--------------------------------|--------------|---------|----------------|-----------------------|
| PARAMETER | MIN | TYP | MAX | UNITS | TEST COND |
| PEAK WAVELENGTH | | 585 (YELLOW) | | nm | |
| | | 635 (RED) | | nm | |
| FORWARD VOLTAGE (Y/R) | | 2.1/2.0 | 2.5/2.5 | V _f | |
| REVERSE VOLTAGE | 5.0 | | | V _r | I _r =100μA |
| AXIAL INTENSITY (Y/R) | | 30/40 | | mcd | I _f =20mA |
| VIEWING ANGLE | | 60 | | 2x theta | |
| EMITTED COLOR: | YELLOW/RED | | | | |
| EPOXY LENS FINISH: | DIFFUSED SAME AS EMITTED COLOR | | | | |

| LIMITS OF SAFE OPERATION AT 25°C | | | |
|----------------------------------|--------|------------|------------|
| PARAMETER | COLORS | MAX | UNITS |
| PEAK FORWARD CURRENT* | | 150 | mA |
| STEADY CURRENT | (Y/R) | 30 | mA |
| POWER DISSIPATION | | 105 | mW |
| DERATE FROM 25°C | | -1.2 | mW/°C |
| OPERATING, STORAGE TEMP. | | -40 TO +85 | °C |
| SOLDERING TEMP. | | +260 | °C |
| 2.0mm FROM BODY | | | 3 SEC. MAX |

* t<10μs

NOTES:

1. SSL-LX509FJYD, YELLOW LED.
2. SSL-LX509F3ID, RED LED.
3. SSH-LXH250, BLACK HOLDER.

UNCONTROLLED DOCUMENT

*UNLESS OTHERWISE SPECIFIED TOLERANCE IS ±0.25mm (±0.010")

| | | | |
|--|------------------------------|--|--|
| REV. A | PART NUMBER SSF-LXH250YID | <p>CONFIDENTIAL INFORMATION</p> <p>THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC. THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.</p> <p>RELIABILITY NOTE</p> <p>OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.</p> | <p>LUMEX INCORPORATED</p> <p>290 E. HELLEN ROAD PALATINE, ILLINOIS 60067 PHONE: 1-847-359-2790 WEB: HTTP://WWW.LUMEX.COM</p> |
| T-5mm (T-1 3/4) LED RIGHT ANGLE FAULT INDICATOR, POS.1: 585nm YELLOW LED, YELLOW DIFFUSED LENS, POS.2: 635nm RED LED, RED DIFFUSED LENS. | | DRAWN BY: BC | CHECKED BY: APPROVED BY: DATE: 6-2-95 PAGE: 1 OF 1 SCALE: N/A |