



UNCONTROLLED DOCUMENT

PART NUMBER  
SSL-LX100133SOC



ELECTRO-OPTICAL CHARACTERISTICS  $T_A=25^{\circ}\text{C}$   $I_f=20\text{mA}$

| PARAMETER          | MIN         | TYP  | MAX | UNITS    | TEST COND            |
|--------------------|-------------|------|-----|----------|----------------------|
| PEAK WAVELENGTH    |             | 610  |     | nm       |                      |
| FORWARD VOLTAGE    |             | 2.0  | 2.5 | $V_f$    |                      |
| REVERSE VOLTAGE    | 5.0         |      |     | $V_r$    | $I_f=100\mu\text{A}$ |
| AXIAL INTENSITY    |             | 3200 |     | mcd      | $I_f=20\text{mA}$    |
| VIEWING ANGLE      |             | 30   |     | 2x theta |                      |
| EMITTED COLOR:     | ORANGE      |      |     |          |                      |
| EPOXY LENS FINISH: | WATER CLEAR |      |     |          |                      |

LIMITS OF SAFE OPERATION AT  $25^{\circ}\text{C}$

| PARAMETER                        | MAX        | UNITS                  |
|----------------------------------|------------|------------------------|
| PEAK FORWARD CURRENT*            | 150        | mA                     |
| STEADY CURRENT                   | 30         | mA                     |
| POWER DISSIPATION                | 105        | mW                     |
| DERATE FROM $25^{\circ}\text{C}$ | -1.2       | mW/ $^{\circ}\text{C}$ |
| OPERATING, STORAGE TEMP.         | -40 TO +85 | $^{\circ}\text{C}$     |
| SOLDERING TEMP.                  | +260       | $^{\circ}\text{C}$     |
| 2.0mm FROM BODY                  |            | 3 SEC. MAX             |

\*  $t < 10\mu\text{s}$

UNCONTROLLED DOCUMENT

\*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=#1 ( $\pm 0.039$ ), XX=#0.5 ( $\pm 0.020$ ), XXX=#0.25 ( $\pm 0.010$ ), XXXX=#0.127 ( $\pm 0.005$ ). LEAD SIZE=#0.05 ( $\pm 0.002$ ), LEAD LENGTH=#0.75 ( $\pm 0.030$ ). MIN= +DECIMAL PRECISION MAX.= +0.00 -DECIMAL PRECISION

|      |   |  |                              |   |
|------|---|--|------------------------------|---|
| REV. | PART NUMBER<br>SSL-LX100133SOC                      | CONFIDENTIAL INFORMATION<br>THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES. | <b>LUMEX</b><br>INCORPORATED | 290 E. HELLEN ROAD<br>PALATINE, ILLINOIS 60067<br>PHONE: (847) 359-2790<br>WEB: <a href="http://www.lumex.com">http://www.lumex.com</a> |
|      | T-10mm 610nm SUPER ORANGE LED,<br>WATER CLEAR LENS. | RELIABILITY NOTE<br>OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.   | DRAWN BY: BC                 | CHECKED BY:<br>APPROVED BY:<br>DATE: 9.19.00<br>PAGE: 1 OF 1<br>SCALE: N/A  |