

PRODUCTS

Appliance Parts & Motors
Batteries: OEM / Industrial
Computer Components
Electronic Components
Semiconductors
Telecommunications
Other OEM Components

Check Product Inventory
Find Reps & Distributors
Use Business Link (B2B)
View Pressroom

Industrial Home
Panasonic Factory
Solutions

Global Sites 

OEM Batteries

Products by Chemistry
[Environmental](#)
[Transportation/MSDS](#)
[Catalog Request](#)
[About OEM Batteries](#)
[What's New](#)
[Contact Us](#)
[Distributors/Pack Assy.](#)

[Alkaline](#)
[Carbon Zinc](#)
[Lithium](#)
[Lithium Ion](#)
[Nickel Metal Hydride](#)
[VRLA 6V & 12V](#)
[VRLA Modular](#)
[PC Cards](#)

INDUSTRIAL SOLUTIONS

LITHIUM - Cylindrical Type

Panasonic Cylindrical Lithium Batteries are notable for their high voltage, energy density, durability, and stable operation.



Features:

- High voltage
- High energy density
- Long shelf life
- Stable operation
- High rate discharge
- Strong leakage resistance
- Excellent durability

[View Data Tables](#)

Applications:

- Cameras
- Electrical lock
- Electronic Counter
- Electronic measurement equipment
- Emergency signal light
- Gas safety emergency cutoff system
- Memory back-up
- Utility meters

Downloads:

Please refer to the technical data tables to download individual data sheets by model number.

Note: To view these documents you need the Adobe® Reader® application installed on your system. If you need this application you can download it at www.adobe.com.

- [Available Tab Configurations and Dimensions for Cylindrical Type Cells - 149KB](#) 

Technical Data - Table 1 - Cylindrical Type (BR)

Model Number	Nominal Voltage (V)	*Nominal Capacity (mAh)	Dimensions (mm)		Basic Battery Weight (g)	Continuous Drain (mA)	Operating Temp (°C)	Check our Distributor Inventory
			External Diameter	Height				
BRC	3	5,000	26.0	50.5	42.0	5.0	-40 ~ +85	
BRA	3	1,800	17.0	45.5	18.0	2.5	-40 ~ +85	
BR-1/2AA	3	1,000	14.5	25.5	8.0	2.5	-40 ~ +100	
BR-2/3A	3	1,200	17.0	33.5	13.5	2.5	-40 ~ +85	
*BR-AG	3	2,200	17.0	45.5	18.0	2.5	-40 ~ +85	
*BR-2/3AG	3	1,450	17.0	33.5	13.5	2.5	-40 ~ +85	

*Nominal capacity is based on standard drain and cutoff voltage down to 2.0V at 20°C (68°F)

Technical Data - Table 2 - Tab Configurations and Distributor Inventory

Model No.	Drawing	Check our Distributor Inventory
BR-1/2AAE2P	Tabs for PCB mounting. 2 Pins Positive 1 Pin Negative	
BR-1/2AAE5P	Tabs for PCB mounting. 1 Pin Positive 1 Pin Negative	
BR-2/3AT2SP	12 mm tabs for adding lead wires	
BR-2/3AGT2SP	12 mm tabs for adding lead wires	N/A
BR-2/3AE5SP	Tabs for PCB mounting. 1 Pin Positive 1 Pin Negative	
BR-2/3AGE5SP	Tabs for PCB mounting. 1 Pin Positive 1 Pin Negative	N/A
BR-2/3AE2SP	Tabs for PCB mounting. 2 Pins Positive 1 Pin Negative	
BR-2/3AGE2SP	Tabs for PCB mounting. 2 Pins Positive 1 Pin Negative	N/A
BR-AT2P	12 mm tabs for adding lead wires	
BR-AGT2P	12 mm tabs for adding lead wires	N/A
BR-AE2P	Tabs for PCB mounting. 1 Pin Positive 1 Pin Negative	N/A
BR-AGE2P	Tabs for PCB mounting. 1 Pin Positive 1 Pin Negative	N/A
BR-CT2P	12 mm tabs for adding lead wires	

[← BACK](#)

 [Privacy Statement](#)