


WP 04T

Order No.: 2913632

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2913632>

Web panel with 3.5" graphics-compatible TFT display, 320 x 240 pixels, 1x Ethernet, 2x USB and integrated micro browser

Commercial data

GTIN (EAN)	 4 046356 460422
sales group	K310
Pack	1 pcs.
Customs tariff	85371099
Catalog page information	Page 138 (AX-2009)

Product notes

WEEE/RoHS-compliant since:
10/15/2008



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data**Display data**

Display	8.9 cm/3.5" TFT active
Resolution	320 x 240 Pixel (QVGA)
Brightness	LED
Half-life of background illumination	40000 h
Touch screen	Resistive industrial touch screen

Colors	65,536 colors
--------	---------------

Computer data

Processor	RISC ARM9 CPU; 200 MHz
Main memory	32 MByte SDRAM
Data memory	16 MB Flash
Interfaces	10/100 MBit Ethernet; 2 x USB Host 2.0
Operating systems	Windows CE 6.0

General data

External dimension, width	120 mm
External dimension, height	90 mm
External dimension, depth	5 mm
Note regarding external dimension	Dimensions of the front plate
Installation dimension, width	112 mm
Installation dimension, height	82 mm
Mounting type	Installation in front plate

Ambient Conditions

Degree of protection	IP65 (front), IP20 (back)
Ambient temperature (operation)	0 °C ... 50 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C
Permissible humidity (operation)	20 % ... 85 % (no condensation)
Permissible humidity (storage/transport)	10 % ... 95 % (no condensation)
Vibration (operation)	DIN EN 60068-2-6
Shock	DIN EN 60068-2-27

Certificates / Approvals

Certification

GL

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;