

Aluminum Capacitors + 105 °C, Miniature, Axial Lead, General Purpose



Fig.1 Component outline

FEATURES

- Long life
- High performance
- High CV per case size
- Case sizes to 0.709" [18.0 mm] diameters



| QUICK REFERENCE DATA | |
|---|--|
| DESCRIPTION | VALUE |
| Nominal case size Ø D x L in mm | 0.248" x 0.512" [6.3 x 13.0] to 0.709" x 1.574" [18.0 x 40.0] |
| Operating temperature | - 40 °C to + 105 °C |
| Rated capacitance range, C _R | 1 µF to 4700 µF |
| Tolerance on C _R | ± 20 % |
| Rated voltage range, U _R | 3 WVDC to 250 WVDC |
| Termination | axial leads |
| Life validation test at 105 °C | 2000 hours: Δ CAP ≤ 20 % from initial measurement. Δ ESR ≤ 1.5 x initial specified limit. Δ DCL ≤ initial specified limit. |
| Shelf life at 85 °C | 500 hours: Δ CAP ≤ 20 % from initial measurement. Δ ESR ≤ 1.5 x initial specified limit. Δ DCL ≤ 2.0 x initial specified limit. |
| DC leakage current | 3 WVDC to 16 WVDC: I = 0.1√CV + 2 25 WVDC to 250 WVDC: I = 0.2√CV + 2 I in µA, C in µF, V in Volts |

| RIPPLE CURRENT MULTIPLIERS | | | | |
|----------------------------|---------|-------------|-----------|-----------|
| TEMPERATURE | | | | |
| AMBIENT TEMPERATURE | | MULTIPLIERS | | |
| + 105 °C | | 0.5 | | |
| + 85 °C | | 1.0 | | |
| ≤ 65 °C | | 2.0 | | |
| FREQUENCY (Hz) | | | | |
| WVDC | 50 - 60 | 100 - 120 | 300 - 400 | 1K - 100K |
| 3 - 50 | 0.9 | 1.0 | 1.1 | 1.4 |
| 51 - 250 | 0.8 | 1.0 | 1.3 | 1.6 |

| DIMENSIONS in inches [millimeters] | | | | | | |
|------------------------------------|----------------|----------------|----------------|----------------|-----------------------------------|----------------|
| CASE CODE | NOMINAL | | STYLE 2 | | STYLE 5 RESIN END SEAL APPLIED | |
| | D | L | D (max.) | L (max.) | D (max.) | L (max.) |
| BA | 0.248 [6.300] | 0.512 [13.000] | 0.276 [7.000] | 0.567 [14.400] | 0.276 [7.000] | 0.626 [15.900] |
| BB | 0.248 [6.300] | 0.689 [17.500] | 0.276 [7.000] | 0.756 [19.200] | 0.276 [7.000] | 0.815 [20.700] |
| CB | 0.315 [8.000] | 0.689 [17.500] | 0.339 [8.600] | 0.756 [19.200] | 0.339 [8.600] | 0.815 [20.700] |
| CC | 0.315 [8.000] | 0.807 [20.500] | 0.339 [8.600] | 0.878 [22.300] | 0.339 [8.600] | 0.937 [23.800] |
| DC | 0.374 [9.500] | 0.807 [20.500] | 0.402 [10.200] | 0.878 [22.300] | 0.402 [10.200] | 0.937 [23.800] |
| DD | 0.374 [9.500] | 0.945 [24.000] | 0.402 [10.200] | 1.01 [25.500] | 0.402 [10.200] | 1.063 [27.000] |
| DF | 0.374 [9.500] | 1.260 [32.000] | 0.402 [10.200] | 1.319 [33.500] | 0.402 [10.200] | 1.378 [35.000] |
| DH | 0.374 [9.500] | 1.496 [38.000] | 0.402 [10.200] | 1.567 [39.800] | 0.402 [10.200] | 1.626 [41.300] |
| EF | 0.433 [11.000] | 1.260 [32.000] | 0.465 [11.800] | 1.319 [33.500] | 0.465 [11.800] | 1.378 [35.000] |
| EH | 0.433 [11.000] | 1.496 [38.000] | 0.465 [11.800] | 1.567 [39.800] | 0.465 [11.800] | 1.626 [41.300] |
| FH | 0.492 [12.500] | 1.496 [38.000] | 0.516 [13.100] | 1.567 [39.800] | 0.516 [13.100] | 1.626 [41.300] |
| FK | 0.492 [12.500] | 1.752 [44.500] | 0.516 [13.100] | 1.831 [46.500] | 0.516 [13.100] | 1.890 [48.000] |
| GH | 0.630 [16.000] | 1.496 [38.000] | 0.654 [16.600] | 1.567 [39.800] | 0.654 [16.600] | 1.626 [41.300] |
| GK | 0.630 [16.000] | 1.752 [44.500] | 0.654 [16.600] | 1.831 [46.500] | 0.654 [16.600] | 1.890 [48.000] |
| LS | 0.709 [18.000] | 1.575 [40.000] | 0.736 [18.700] | 1.673 [42.500] | 0.736 [18.700] | 1.693 [43.000] |

ORDERING EXAMPLE

Electrolytic capacitor 30D series: 30D 128 M 025 EH 2 A

| DESCRIPTION | |
|-------------|--|
| CODE | EXPLANATION |
| 30D | product type |
| 128 | capacitance value (1200 µF) |
| M | tolerance (M = ± 20 %) |
| 025 | voltage rating at 105 °C (024 = 25 V) |
| EH | can size (see dimensions table) |
| 2 | sleeve and sealing (2 = P. V. C. sleeve) |
| A | packaging (A = bulk) |

| ELECTRICAL DATA AND ORDERING INFORMATION | | | | |
|--|----------------|------------------------------------|---|--|
| CAPACITANCE (µF) | PART NUMBER | NOMINAL CASE SIZE D x L [mm] | MAX. ESR at + 25 °C 120 Hz (Ω) | MAX. RIPPLE at + 85 °C 120 Hz (A) |
| 6.3 WVDC at + 105 °C, SURGE = 8 V | | | | |
| 150.0 | 30D157M6R3BB2A | 0.248 x 0.689 [6.3 x 17.5] | 2.875 | 0.163 |
| 330.0 | 30D337M6R3CC2A | 0.315 x 0.807 [8.0 x 20.5] | 1.277 | 0.299 |
| 1200.0 | 30D128M6R3DF2A | 0.374 x 1.260 [9.5 x 32.0] | 0.345 | 0.767 |
| 2200.0 | 30D228M6R3EF2A | 0.433 x 1.260 [11.0 x 32.0] | 0.206 | 1.080 |
| 4700.0 | 30D478M6R3GH2A | 0.630 x 1.496 [16.0 x 38.0] | 0.118 | 1.910 |
| 10 WVDC at + 105 °C, SURGE = 12 V | | | | |
| 47.0 | 30D476M010BA2A | 0.248 x 0.512 [6.3 x 13.0] | 7.487 | 0.089 |
| 100.0 | 30D107M010BB2A | 0.248 x 0.689 [6.3 x 17.5] | 3.561 | 0.147 |
| 330.0 | 30D337M010CC2A | 0.315 x 0.807 [8.0 x 20.5] | 1.081 | 0.325 |
| 470.0 | 30D477M010DC2A | 0.374 x 0.807 [9.5 x 20.5] | 0.748 | 0.434 |
| 1000.0 | 30D108M010DF2A | 0.374 x 1.260 [9.5 x 32.0] | 0.356 | 0.755 |
| 2200.0 | 30D228M010EH2A | 0.433 x 1.496 [11.0 x 38.0] | 0.184 | 1.240 |
| 16 WVDC at + 105 °C, SURGE = 20 V | | | | |
| 33.0 | 30D336M016BA2A | 0.248 x 0.512 [6.3 x 13.0] | 9.814 | 0.078 |
| 150.0 | 30D157M016CB2A | 0.315 x 0.689 [8.0 x 17.5] | 2.208 | 0.212 |
| 330.0 | 30D337M016DC2A | 0.374 x 0.807 [9.5 x 20.5] | 1.981 | 0.379 |
| 470.0 | 30D477M016DD2A | 0.374 x 0.945 [9.5 x 24.0] | 0.679 | 0.483 |
| 1200.0 | 30D128M016DH2A | 0.374 x 1.496 [9.5 x 38.0] | 0.265 | 0.947 |
| 4700.0 | 30D478M016GK2A | 0.630 x 1.752 [16.0 x 44.5] | 0.093 | 2.290 |
| 20 WVDC at + 105 °C, SURGE = 25 V | | | | |
| 150.0 | 30D157M020CC2A | 0.315 x 0.807 [8.0 x 20.5] | 2.110 | 0.233 |
| 220.0 | 30D227M020DC2A | 0.374 x 0.807 [9.5 x 20.5] | 1.410 | 0.318 |
| 1000.0 | 30D108M020EF2A | 0.433 x 1.260 [11.0 x 32.0] | 0.323 | 0.863 |
| 1500.0 | 30D158M020EH2A | 0.433 x 1.496 [11.0 x 38.0] | 0.221 | 1.140 |
| 3300.0 | 30D338M020GK2A | 0.630 x 1.752 [16.0 x 44.5] | 0.118 | 2.040 |

Aluminum Capacitors
+ 105 °C, Miniature, Axial Lead, General Purpose

Vishay Sprague

| ELECTRICAL DATA AND ORDERING INFORMATION | | | | |
|---|--------------------|---|---|--|
| CAPACITANCE (μF) | PART NUMBER | NOMINAL CASE SIZE D x L [mm] | MAX. ESR at + 25 °C 120 Hz (Ω) | MAX. RIPPLE at + 85 °C 120 Hz (A) |
| 25 WVDC at + 105 °C, SURGE = 35 V | | | | |
| 22.0 | 30D226M025BA2A | 0.248 x 0.512 [6.3 x 13.0] | 13.270 | 0.067 |
| 47.0 | 30D476M025BB2A | 0.248 x 0.689 [6.3 x 17.5] | 6.128 | 0.112 |
| 100.0 | 30D107M025CC2A | 0.315 x 0.807 [8.0 x 20.5] | 2.914 | 0.197 |
| 220.0 | 30D227M025DC2A | 0.374 x 0.807 [9.5 x 20.5] | 1.327 | 0.326 |
| 330.0 | 30D337M025DD2A | 0.374 x 0.945 [9.5 x 24.0] | 0.885 | 0.423 |
| 470.0 | 30D477M025DF2A | 0.374 x 1.260 [9.5 x 32.0] | 0.612 | 0.575 |
| 1200.0 | 30D128M025EH2A | 0.433 x 1.496 [11.0 x 38.0] | 0.239 | 1.090 |
| 3300.0 | 30D338M025LS2A | 0.709 x 1.575 [18.0 x 40.0] | 0.108 | 2.190 |
| 35 WVDC at + 105 °C, SURGE = 45 V | | | | |
| 33.0 | 30D336M035BB2A | 0.248 x 0.689 [6.3 x 17.5] | 8.330 | 0.096 |
| 100.0 | 30D107M035DC2A | 0.374 x 0.807 [9.5 x 20.5] | 2.740 | 0.212 |
| 220.0 | 30D227M035DD2A | 0.374 x 0.945 [9.5 x 24.0] | 1.250 | 0.356 |
| 330.0 | 30D337M035DF2A | 0.374 x 1.260 [9.5 x 32.0] | 0.830 | 0.495 |
| 1000.0 | 30D108M035EH2A | 0.433 x 1.496 [11.0 x 38.0] | 0.274 | 1.020 |
| 2200.0 | 30D228M035GK2A | 0.630 x 1.752 [16.0 x 44.5] | 0.125 | 1.980 |
| 40 WVDC at + 105 °C, SURGE = 50 V | | | | |
| 15.0 | 30D156M040BA2A | 0.248 x 0.512 [6.3 x 13.0] | 17.600 | 0.058 |
| 22.0 | 30D226M040BB2A | 0.248 x 0.689 [6.3 x 17.5] | 11.700 | 0.081 |
| 47.0 | 30D476M040CB2A | 0.315 x 0.689 [8.0 x 17.5] | 5.435 | 0.134 |
| 100.0 | 30D107M040DC2A | 0.374 x 0.807 [9.5 x 20.5] | 2.585 | 0.234 |
| 470.0 | 30D477M040DH2A | 0.374 x 1.496 [9.5 x 38.0] | 0.543 | 0.663 |
| 1000.0 | 30D108M040FK2A | 0.492 x 1.752 [12.5 x 44.5] | 0.258 | 1.210 |
| 2200.0 | 30D228M040LS2A | 0.709 x 1.575 [18.0 x 40.0] | 0.125 | 2.040 |
| 50 WVDC at + 105 °C, SURGE = 65 V | | | | |
| 10.0 | 30D106M050BA2A | 0.248 x 0.512 [6.3 x 13.0] | 25.85 | 0.048 |
| 22.0 | 30D226M050BB2A | 0.248 x 0.689 [6.3 x 17.5] | 11.700 | 0.081 |
| 33.0 | 30D336M050CB2A | 0.315 x 0.689 [8.0 x 17.5] | 7.850 | 0.112 |
| 100.0 | 30D107M050DC2A | 0.374 x 0.807 [9.5 x 20.5] | 2.585 | 0.233 |
| 220.0 | 30D227M050DF2A | 0.374 x 1.260 [9.5 x 32.0] | 1.177 | 0.417 |
| 330.0 | 30D337M050DH2A | 0.374 x 1.496 [9.5 x 38.0] | 0.785 | 0.551 |
| 1500.0 | 30D158M050GK2A | 0.630 x 1.752 [16.0 x 44.5] | 0.176 | 1.670 |
| 63 WVDC at + 105 °C, SURGE = 75 V | | | | |
| 15.0 | 30D156M063BB2A | 0.248 x 0.689 [6.3 x 17.5] | 16.580 | 0.068 |
| 33.0 | 30D336M063CB2A | 0.315 x 0.689 [8.0 x 17.5] | 7.370 | 0.116 |
| 47.0 | 30D476M063CC2A | 0.315 x 0.807 [8.0 x 20.5] | 5.100 | 0.149 |
| 100.0 | 30D107M063DD2A | 0.374 x 0.945 [9.5 x 24.0] | 2.426 | 0.256 |
| 220.0 | 30D227M063EF2A | 0.433 x 1.260 [11.0 x 32.0] | 1.105 | 0.467 |
| 470.0 | 30D477M063EH2A | 0.433 x 1.496 [11.0 x 38.0] | 0.510 | 0.745 |
| 1000.0 | 30D108M063GK2A | 0.630 x 1.752 [16.0 x 44.5] | 0.242 | 1.420 |

**ELECTRICAL DATA AND ORDERING INFORMATION**

| CAPACITANCE (μ F) | PART NUMBER | NOMINAL CASE SIZE D x L [mm] | MAX. ESR at + 25 °C 120 Hz (Ω) | MAX. RIPPLE at + 85 °C 120 Hz (A) |
|--|----------------|------------------------------------|--|--|
| 75 WVDC at + 105 °C, SURGE = 85 V | | | | |
| 12.0 | 30D126M075BB2A | 0.248 x 0.689 [6.3 x 17.5] | 13.200 | 0.076 |
| 47.0 | 30D476M075DC2A | 0.374 x 0.807 [9.5 x 20.5] | 3.384 | 0.204 |
| 120.0 | 30D127M075DF2A | 0.374 x 1.260 [9.5 x 32.0] | 1.320 | 0.392 |
| 1000.0 | 30D108M075LS2A | 0.709 x 1.575 [18.0 x 40.0] | 0.160 | 1.810 |
| 100 WVDC at + 105 °C, SURGE = 125 V | | | | |
| 4.7 | 30D475M100BB2A | 0.248 x 0.689 [6.3 x 17.5] | 33.840 | 0.048 |
| 10.0 | 30D106M100CB2A | 0.315 x 0.689 [8.0 x 17.5] | 16.097 | 0.079 |
| 100.0 | 30D107M100DH2A | 0.374 x 1.496 [9.5 x 38.0] | 1.609 | 0.386 |
| 220.0 | 30D227M100EK2A | 0.492 x 1.752 [12.5 x 44.5] | 0.733 | 0.717 |
| 470.0 | 30D477M100LS2A | 0.709 x 1.575 [18.0 x 40.0] | 0.338 | 1.240 |
| 160 WVDC at + 105 °C, SURGE = 180 V | | | | |
| 1.5 | 30D155M160BA2A | 0.248 x 0.512 [6.3 x 13.0] | 110.10 | 0.023 |
| 3.3 | 30D335M160CB2A | 0.315 x 0.689 [8.0 x 17.5] | 48.880 | 0.045 |
| 10.0 | 30D106M160DC2A | 0.374 x 0.807 [9.5 x 20.5] | 16.097 | 0.093 |
| 22.0 | 30D226M160DF2A | 0.374 x 1.260 [9.5 x 32.0] | 7.333 | 0.166 |
| 33.0 | 30D336M160EF2A | 0.433 x 1.260 [11.0 x 32.0] | 4.888 | 0.222 |
| 47.0 | 30D476M160EH2A | 0.433 x 1.496 [11.0 x 38.0] | 3.384 | 0.289 |
| 100.0 | 30D107M160GK2A | 0.630 x 1.752 [16.0 x 44.5] | 1.609 | 0.552 |
| 200 WVDC at + 105 °C, SURGE = 250 V | | | | |
| 1.2 | 30D125M200BA2A | 0.248 x 0.512 [6.3 x 13.0] | 132.01 | 0.022 |
| 4.7 | 30D475M200CC2A | 0.315 x 0.807 [8.0 x 20.5] | 33.850 | 0.058 |
| 8.2 | 30D825M200DC2A | 0.374 x 0.807 [9.5 x 20.5] | 19.410 | 0.085 |
| 10.0 | 30D106M200DD2A | 0.374 x 0.945 [9.5 x 24.0] | 16.090 | 0.101 |
| 22.0 | 30D226M200DH2A | 0.374 x 1.496 [9.5 x 38.0] | 7.331 | 0.181 |
| 33.0 | 30D336M200EH2A | 0.433 x 1.496 [11.0 x 38.0] | 4.880 | 0.241 |
| 47.0 | 30D476M200EK2A | 0.492 x 1.752 [12.5 x 44.5] | 3.384 | 0.334 |
| 100.0 | 30D107M200LS2A | 0.709 x 1.575 [18.0 x 40.0] | 1.609 | 0.571 |
| 250 WVDC at + 105 °C, SURGE = 300 V | | | | |
| 1.0 | 30D105M250BA2A | 0.248 x 0.512 [6.3 x 13.0] | 160.97 | 0.021 |
| 3.3 | 30D335M250CC2A | 0.315 x 0.807 [8.0 x 20.5] | 48.010 | 0.049 |
| 12.0 | 30D126M250DF2A | 0.374 x 1.260 [9.5 x 32.0] | 13.210 | 0.124 |
| 47.0 | 30D476M250GH2A | 0.630 x 1.496 [16.0 x 38.0] | 3.384 | 0.355 |



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.