

S-MAX 5012 VLC MWX ETH

This item is no longer available. Should you have any questions, please contact our Sales Team.

Order No.: 2895653




<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2895653>

Powerful combination of PC platform, PLC, Steeplechase VLC and Iconics MachineWorX Runtime, 12.1" display, MODBUS TCP master



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Commercial data

| | |
|--------------------------|---|
| GTIN (EAN) |  |
| Note | Made-to-order |
| sales group | K301 |
| Pack | 1 pcs. |
| Customs tariff | 85371091 |
| Catalog page information | Page 67 (AX-2009) |

Technical data

Module

| | |
|-------------------|---|
| Main memory | 256 MB DDR SODIMM |
| Operating systems | WIN CE.NET |
| Display | 30.7 cm/12.1" TFT active |
| Touch screen | Resistive industrial touch screen |
| Compact flash | 512 MB |
| Power supply unit | 24 V DC |
| Interfaces | COM 1 (RS232), 1xDVI (VGA), 1x PS/2 mouse, 1x PS/2 keyboard, 2x USB |

| | |
|-----------------------|--|
| Network | 3x Ethernet (10/100 Mbps), RJ45, X11: Programming and Maintenance, X10.1 and X10.2: Industrial Ethernet Control |
| Keys | 5 additional keys (software keyboard, change task Alt+Tab, right mouse button, brightness, user-specific function) |
| Graphics card | On-board graphics chip (AGP) |
| Supply voltage | 24 V DC |
| Fieldbus master | MODBUS TCP master |
| Monitor resolution | 800 x 600 |
| Retentive data memory | 128 kByte (NVRAM) |

General data

| | |
|--|---------------------------------|
| Width | 330 mm |
| Height | 268 mm |
| Depth | 75 mm |
| Degree of protection | IP65 (front), IP20 (back) |
| Ambient temperature (operation) | 5 °C ... 40 °C |
| Ambient temperature (storage/transport) | -20 °C ... 60 °C |
| Permissible humidity (operation) | 10 % ... 85 % (no condensation) |
| Permissible humidity (storage/transport) | 10 % ... 85 % (no condensation) |
| Vibration (operation) | DIN EN 60068-2-6 |
| Shock | DIN EN 60068-2-29 |

Certificates / Approvals



Certification

CUL Listed, UL Listed

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;