

## S-MAX 5012 VLC MWX PB

This item is no longer available. Should you have any questions, please contact our Sales Team.


Order No.: 2895679



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2895679>

Powerful combination of PC platform, PLC, Steeplechase VLC and Iconics MachineWorX Runtime, 12.1" display, PROFIBUS field bus master

### Commercial data

GTIN (EAN)	
Note	Made-to-order
sales group	K301
Pack	1 pcs.
Customs tariff	85371091
Catalog page information	Page 67 (AX-2009)

<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Technical data

#### Module

Main memory	256 MB DDR SODIMM
Operating systems	WIN CE.NET
Display	30.7 cm/12.1" TFT active
Touch screen	Resistive industrial touch screen
Compact flash	512 MB
Power supply unit	24 V DC

Interfaces	COM 1 (RS232), 1xDVI (VGA), 1x PS/2 mouse, 1x PS/2 keyboard, 2x USB
Network	3x Ethernet (10/100 Mbps), RJ45, X11: Programming and Maintenance, X10.1 and X10.2: Industrial Ethernet Control
Keys	5 additional keys (software keyboard, change task Alt+Tab, right mouse button, brightness, user-specific function)
Graphics card	On-board graphics chip (AGP)
Supply voltage	24 V DC
Fieldbus master	PROFIBUS master
Monitor resolution	800 x 600
Retentive data memory	128 kByte (NVRAM)

#### General data

Width	330 mm
Height	268 mm
Depth	75 mm
Degree of protection	IP65 (front), IP20 (back)
Ambient temperature (operation)	5 °C ... 40 °C
Ambient temperature (storage/transport)	-20 °C ... 60 °C
Permissible humidity (operation)	10 % ... 85 % (no condensation)
Permissible humidity (storage/transport)	10 % ... 85 % (no condensation)
Vibration (operation)	DIN EN 60068-2-6
Shock	DIN EN 60068-2-29

#### Certificates / Approvals



Certification

CUL Listed, UL Listed

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2011 Phoenix Contact  
Technical modifications reserved;