

VMT 5015 SM

This product has been replaced by a newer version.

Order No.: 2900632



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2900632>

IPC in IP65 with touch screen, 15" display, enclosed housing.

Commercial data

GTIN (EAN)	 4 046356 148221
Note	Made-to-order
sales group	K701
Pack	1 pcs.
Customs tariff	84714100
Catalog page information	Page 153 (AX-2009)

Product notes

WEEE/RoHS-compliant since:
11/04/2010



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Product description

VMT - Mobility made simple!

The VMT 5015 is a high-performance IPC in IP65 with touch screen and optional front USB, mounted in an elegant and rugged aluminum die-cast housing. Waste heat from the processor is dissipated into the surrounding atmosphere via the back panel of the terminal, which is designed as a heatsink. The terminal is supplied with a software keyboard as standard. This software keyboard provides all the alphanumeric keys of a standard keyboard. In addition, you can switch over to a separate block of numeric keys.

The VMT 5015 has a high-resolution 15" color TFT display with a resolution of 1024 x 768 pixels.

The special features of the flat IPC are the high IP65 degree of protection and the easy and direct assembly on the machine. The voltage supply of 10 - 35 V makes the VMT 5015 ideal for mobile applications.

It can be mounted using either a support bracket (left and right), table stand, Vesa standard bracket, or Rittal bracket connection adapter.

Technical data

Display data

Display	38.1 cm/15" TFT active
Resolution	1024 x 768
Half-life of background illumination	> 50000 h
Touch screen	Resistive industrial touch screen
Operating Buttons on the Front	5 additional keys (software keyboard, task change Alt+Tab, right mouse button, brightness, user-specific function)

Computer data

Processor	Celeron M 800 MHz
Main memory	1 GB DDR RAM
Processor fan	Without fan
Data memory	2.5" HDD, min 40 GB , 24x7 Automotive
Graphics card	Intel® 855 GME
Interfaces	COM 1 (RS-232), 1x PS/2 mouse, 1x PS/2 keyboard, 2x USB, line out
Network	1x Ethernet (10/100 Mbps), RJ45
Operating systems	No operating system
Service life of battery	3-5 years (typical)
Power supply unit	24 V DC +/- 20%

General data

External dimension, width	395 mm
External dimension, height	292 mm
External dimension, depth	74 mm
Mounting type	Depending on accessories
Weight	4800 g

Ambient Conditions

Degree of protection	IP65
Ambient temperature (operation)	-20 °C ... 45 °C
Permissible humidity (operation)	10 % ... 85 % (no condensation)

Permissible humidity (storage/transport)	10 % ... 85 % (no condensation)
Vibration (operation)	DIN EN 60068-2-6
Shock	DIN EN 60068-2-27

Accessories

Item	Designation	Description
Assembly		
2913878	VMT CABLE ASSEMBLY KIT	Accessories consisting of: Cable feed-throughs, strain relief clamps, screws, spacer sleeves
2900962	VMT GALGENANSCHLUSSADAPTER	Accessories, bracket connection adapter for a monitor/IPC in the IP65 housing
2900959	VMT HALTERUNG VESA	Accessories, bracket in accordance with VESA standard for a monitor/IPC in the IP65 housing
2900933	VMT HALTEWINKEL LI/RE	Accessories, left/right support bracket for a monitor/IPC in the IP65 housing
2913496	VMT RFID LESER-HALTERUNG	Accessories, RFID reader support bracket for a monitor/IPC in an IP65 housing
2913331	VMT TASTATURABLAG 420MM	Accessories, keyboard storage for an IPC in the IP65 housing
2900946	VMT TISCHFUSS	Accessories, table foot for a monitor/IPC in the IP65 housing
2913399	VMT-GALGENANSCHLUSS STEHEND	Accessories, bracket connection adapter for a monitor/IPC in the IP65 housing
Cable/conductor		
2913946	VMT 50XX COUPLING CABLE SET	Accessories, coupling cable for fast removal for an IPC in the IP65 housing
Plug/Adapter		
1992719	MC 1,5/ 3-STF-3,81-BD NZ 0638	Plug component, Nominal current: 8 A, Number of positions: 3, Pitch: 3.81 mm, Connection method: Screw connection
2900904	VMT EXT PS	Accessories, external power supply unit for an IPC in the IP65 housing

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;