

VMT 5015 PM 1,1 EN


Order No.: 2900629

The illustration can vary depending on the configuration

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2900629>

IPC in IP65 with touch screen, 15" display, enclosed housing.

Commercial data

GTIN (EAN)	 4 046356 148917
Note	Made-to-order
sales group	K701
Pack	1 pcs.
Customs tariff	84714100
Catalog page information	Page 153 (AX-2009)

Product notes

WEEE/RoHS-compliant since:
11/04/2010

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Product description

VMT - Mobility made simple!

The VMT 5015 is a high-performance IPC in IP65 with a touchscreen and optional front USB, mounted in an elegant and solid aluminum die-cast housing. Heat from the processor is dissipated into the surrounding atmosphere via the back panel of the terminal, which is designed as a heatsink. The terminal is supplied with a software keyboard as standard. The software keyboard provides all the alphanumeric keys of a standard keyboard. In addition, it is possible to switch to a separate numeric keypad.

The VMT 5015 has a high-resolution 38.1 cm (15") color TFT display with a resolution of 1024 x 768 pixels.

The flat IPC is characterized in particular by its high IP65 protection class and how simple and easy it is to mount directly onto the machine. With a power supply of 10 - 35 V, the VMT 5015 is ideal for mobile applications.

Options for assembly include the use of a support bracket (left and right), table stand, Vesa standard bracket or Rittal bracket connection adapter.

*** The general user manual is in the download area for article 2887603 VMT 5015***

Technical data

Display data

Display	38.1 cm/15" TFT active
Resolution	1024 x 768 (XGA)
Half-life of background illumination	> 50000 h
Touch screen	Resistive industrial touch screen
Operating Buttons on the Front	5 additional keys (software keyboard, task change Alt+Tab, right mouse button, brightness, user-specific function)

Computer data

Processor	Pentium M 1,1 GHz
Main memory	1 GB DDR RAM
Processor fan	Without fan
Data memory	2.5" HDD, min 40 GB , 24x7 Automotive
Optical drive	No CD-ROM
Graphics card	Intel® 855 GME
Interfaces	COM 1 (RS-232), 1x PS/2 mouse, 1x PS/2 keyboard, 2x USB, line out 1x USB on front
Network	1x Ethernet (10/100 Mbps), RJ45
Operating systems	Windows XP English
Service life of battery	3-5 years (typical)
Power supply unit	24 V DC +/- 20%

General data

External dimension, width	395 mm
External dimension, height	292 mm
External dimension, depth	65 mm
Mounting type	Depending on accessories
Weight	3500 g

Ambient Conditions

Degree of protection	IP65
Power consumption	25 W ((typical))
Ambient temperature (operation)	-20 °C ... 45 °C
Ambient temperature (storage/transport)	-20 °C ... 60 °C
Permissible humidity (operation)	10 % ... 85 % (no condensation)
Permissible humidity (storage/transport)	10 % ... 85 % (no condensation)
Vibration (operation)	DIN EN 60068-2-6
Shock	DIN EN 60068-2-27

Accessories

Item	Designation	Description
------	-------------	-------------

Assembly

2913878	VMT CABLE ASSEMBLY KIT	Accessories consisting of: Cable feed-throughs, strain relief clamps, screws, spacer sleeves
2900962	VMT GALGENANSCHLUSSADAPTER	Accessories, bracket connection adapter for a monitor/IPC in the IP65 housing
2900959	VMT HALTERUNG VESA	Accessories, bracket in accordance with VESA standard for a monitor/IPC in the IP65 housing
2900933	VMT HALTEWINKEL LI/RE	Accessories, left/right support bracket for a monitor/IPC in the IP65 housing
2913496	VMT RFID LESER-HALTERUNG	Accessories, RFID reader support bracket for a monitor/IPC in an IP65 housing
2913331	VMT TASTATURABLAG 420MM	Accessories, keyboard storage for an IPC in the IP65 housing
2900946	VMT TISCHFUSS	Accessories, table foot for a monitor/IPC in the IP65 housing
2913399	VMT-GALGENANSCHLUSS STEHEND	Accessories, bracket connection adapter for a monitor/IPC in the IP65 housing

Cable/conductor

2913946	VMT 50XX COUPLING CABLE SET	Accessories, coupling cable for fast removal for an IPC in the IP65 housing
---------	--------------------------------	---

Plug/Adapter

1992719	MC 1,5/ 3-STF-3,81-BD NZ 0638	Plug component, Nominal current: 8 A, Number of positions: 3, Pitch: 3.81 mm, Connection method: Screw connection
2900904	VMT EXT PS	Accessories, external power supply unit for an IPC in the IP65 housing

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;