

## VS-SCRJ-GOF-BU/BU


Order No.: 1652978



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1652978>

SCRJ socket insert, duplex, for VS-A-F-IP67 panel mounting frame, can be used for glass, multi-mode, HCS and polymer fibers

### Ethernet

Commercial data	
GTIN (EAN)	 4 017918 969943
sales group	D521
Pack	1 pcs.
Customs tariff	85366990
Catalog page information	Page 217 (PC-2009)

### Product notes

WEEE/RoHS-compliant since:  
01/01/2005



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Technical data

#### Mechanical characteristics

Number of positions	2
Number of slots	1
Connection profile	SCRJ according to DIN EN 50377-6-1
Fiber type	GOF, HCS, POF
Ferrule diameter	2.50 mm

Number of fibers	2
Insertion/withdrawal cycles	≥ 500
Connection method	Socket
Ambient temperature (operation)	-25 °C ... 70 °C

**Material data**

Inflammability class acc. to UL 94	V0
Housing material	PBT
Ferrule material	Zirconia ceramics
Ferrule holder color	White
Degree of protection	IP20

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2011 Phoenix Contact  
Technical modifications reserved;