


PSM-SET-FSMA/4-KT

Order No.: 2799720

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2799720>

F-SMA plug set for polymer fiber, for self assembly consisting of 4 quick mounting connectors with bend protection sleeve

Commercial data	
GTIN (EAN)	 4 017918 156053
sales group	H628
Pack	1 pcs.
Customs tariff	85366990
Catalog page information	Page 522 (IF-2009)

Product notes

WEEE/RoHS-compliant since:
08/01/2005



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
General data	
Type of plug	F-SMA/Type 905, IEC 874-2
FO fiber	Polymer fiber
Attenuation	< 1.5 dB

Accessories

Item	Designation	Description
Cable/conductor		
2313397	FL FOC PN-B-980/1000	PROFINET polymer fiber cable, duplex, 980/1000 µm, heavy-weight design, for permanent indoor installation, by the meter, without connector
2313407	FL FOC PN-C-FLEX-980/1000	PROFINET polymer fiber cable, duplex, 980/1000 µm, heavy-weight highly flexible design, for flexible cable conduit applications, by the meter, without connector
2901553	FOC-KDHEAVY-1011/IP20/...	POF installation cable (IP20 heads only) for fixed installation in the inner area with individual elements made of highly durable polyamide (PE). The cable is halogen-free, ozone and UV resistant and has a rugged polyurethane (PUR) outer sheath.
2901551	FOC-PN-B-1000/IP20/...	POF PROFINET installation cable (IP20 heads only) for fixed installation in the inner area with individual elements of highly durable polyamide (PE). Individual elements made of extremely wear-resistant polyamide (PE). The cable is halogen-free, ozone and UV resistant and has a rugged polyurethane (PUR) outer sheath.
2901552	FOC-PN-C-1003/IP20/□	Highly flexible POF PROFINET cable (IP20 heads only) for use in drag chains for an alternating bending frequency of up to 5 million cycles. Individual elements made of extremely wear-resistant polyamide (PE). The cable is halogen-free, ozone and UV resistant and has a rugged polyurethane (PUR) outer sheath.
2901548	FOC-RUGGED-1012/IP20/...	rugged POF installation cable (IP20 heads only) for fixed installation in the inner area with individual elements made of highly durable polyamide (PE). Dimensioned for higher requirements in respect of tensile load and lateral pressure, with individual elements made of highly wear-resistant polyamide (PE). The cable is halogen-free, ozone and UV resistant and has a reinforced (PUR) outer sheath.
2901549	FOC-RUGGED-FLEX-1013/IP20/...	Highly flexible POF round cable (IP20 heads only) for use in drag chains for an alternating bending frequency of up to 5 million cycles with individual elements made of highly wear-resistant polyamide (PE). The cable is halogen-free, ozone and UV resistant and has a rugged polyurethane (PUR) outer sheath.
2744319	PSM-LWL-KDHEAVY-980/1000	Polymer fiber cable, duplex 980/1000 µm, medium-weight version for permanent indoor installation, by the meter, without connector
2744322	PSM-LWL-RUGGED-980/1000	Polymer fiber cable, duplex, 980 µm/1000 µm, heavy version for permanent indoor installation, sold by the meter without connectors
2744335	PSM-LWL-RUGGED-FLEX-980/1000	Polymer fiber cable, duplex 980/1000 µm, heavy-weight, highly flexible version for flexible conduit applications, by the meter, without connector

Tools

2744131	PSM-POF-KONFTOOL	Polymer fiber DIY case, consisting of: Stripping knife, stripping pliers, polishing wheels for F-SMA and SCRJ quick mounting connectors, polishing pad and emery paper
---------	------------------	--

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;