
Data Sheet

Chip Monolithic Ceramic Capacitors Safety Standard Certified Type GC (UL, IEC60384-14 Class X1/Y2) GA355DR7GC472KY02L (2220, X7R, 4700pF, AC250V(r.m.s.))

• For your new designs, alternative parts should be used. These parts should be used only for existing design. Please consult with us for details.

RoHS regulation conformity parts



(in mm)

Dimensions

Length L	5.7mm±0.4mm	
Width W	5.0mm±0.4mm	
Thickness T	2.0mm±0.3mm	
Electrode e	0.3mm min.	
Electrode g (min.)	4.0mm	

Rated Value

	Murata PN Code	Spec	
Temperature Char.	R7	X7R (EIA), ±15%	
Capacitance	472	4700pF	
Capacitance Tol.	Tol. K ±10%		
Rated Voltage	GC	AC250V(r.m.s.)	

Packaging

Code	Packaging	Minimum Quantity
L	180mm Embossed Tape	1000

Specifications

Please refer to 'Safety Standard Certified Type GC/GD/GF/GB Specifications and Test Methods' PDF file.

Standard Certification

\geq	Standard No.	Class	Rated Voltage
UL	UL1414	Line By-pass	
VDE	IEC 60384-14 EN 60384-14		
BSI	EN 60065 (14.2) IEC 60384-14 EN 60384-14	X1, Y2	AC250V (r.m.s.)
SEMKO	IEC 60384-14 EN 60384-14		
ESTI	EN 60065 IEC 60384-14		

This data sheet is applied to SAFETY STANDARD CERTIFIED CHIP MONOLITHIC CERAMIC CAPACITOR Type GC for your design.

<Notice>

Solderability of Tin plating termination chip might be deteriorated when low temperature soldering profile where peak solder temperature is below the Tin
melting point is used. Please confirm the solderability of Tin plating termination chip before use.

Plese refer to 'Caution' and 'Notice' for the other details.

The RoHS compliance means that we judge from EU Directive 2002/95/EC the products do not contain lead, cadmium, mercury, hexavalent chromium, PBB and PBDE, except exemptions stated in EU Directive 2002/95/EC annex and impurities existing in natural world.
This statement does not insure the compliance of any of the listed parts with any laws or legal imperatives developed by any EU members

individually with regards to the RoHS Directive.

A Note:

1. This datasheet is downloaded from the website of Murata Manufacturing co., ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please approve our product specifications or transact the approval sheet for product specifications before ordering.

