

Ceramic High Voltage Disc Capacitors, Class 2



Dimensions in mm

| | COATING EXTENSION e | BULK STANDARD LEAD LENGTH L |
|---------------------------------|------------------------|--------------------------------|
| HA., HB., HC., HD., HE., HF. | 3 max. | 30.0 + 0 - 3 or |
| HGZ | 5 max. | 10.0 ± 1 |

COATING:

Epoxy dipped, insulating,
Flame retarding acc. to UL 94V-0

TEMPERATURE CHARACTERISTIC OF CAPACITANCE:

See General Information

TAPING AND SPECIAL LEAD CONFIGURATIONS:

See General Information

MARKING:

| | |
|-----------------------|--------------------------------------|
| Capacitance value | Clear text |
| Capacitance tolerance | with letter code |
| Rated voltage | Clear text |
| Ceramic dielectric | with letter code |
| | HAZ, HBZ, HCZ, HFZ, HGZ series: 'D' |
| | HAE, HCE, HDE, HEE, HFE series: 'E' |
| | HAX, HBX, HCX series: no Letter code |
| Manufacturers logo | Where D ≥ 13 mm only |

DESIGN:

Disc capacitors with epoxy coating

RATED VOLTAGE U_R :

| | |
|---------------|--------------------|
| HAZ, HAE, HAX | 1 kV _{DC} |
| HBZ, HBE, HBX | 2 kV _{DC} |
| HCZ, HCE, HCX | 3 kV _{DC} |
| HDE | 4 kV _{DC} |
| HEE | 5 kV _{DC} |
| HFZ, HFE | 6 kV _{DC} |
| HGZ | 8 kV _{DC} |

DIELECTRIC STRENGTH BETWEEN LEADS:

| | |
|----------------|------------------------------|
| Component test | |
| HAZ, HAE, HAX | 1750 kV _{DC} , 2 s |
| HBZ, HBE, HBX | 3000 kV _{DC} , 2 s |
| HCZ, HCE, HCX | 5000 kV _{DC} , 2 s |
| HDE | 6000 kV _{DC} , 2 s |
| HEE | 7500 kV _{DC} , 2 s |
| HFZ, HFE | 9000 kV _{DC} , 2 s |
| HGZ | 12000 kV _{DC} , 2 s |

DISSIPATION FACTOR $\tan \delta$:

| | |
|-------------------------|-------------------------|
| HA., HB., HC., HD., HE. | ≤ 25 • 10 ⁻³ |
| HF., HG. | ≤ 20 • 10 ⁻³ |

INSULATION RESISTANCE R_{IS} :

$$\geq 1 \cdot 10^{10} \Omega$$

CATEGORY TEMPERATURE RANGE ϑ_A :

(- 40 to + 85) °C

CLIMATIC CATEGORY ACC. TO EN 60068-1:

40 / 085 / 21



RoHS
COMPLIANT

ORDERING INFORMATION

| HAZ | 101 | M | BA | BJ0 | K | R |
|-------|----------------------|-----------|------------------|-----------------------|------------------|-------------------|
| MODEL | CAPACITANCE VALUE | TOLERANCE | RATED VOLTAGE | LEAD CONFIGURATION | INTERNAL CODE | RoHS COMPLIANT |



| ORDERING INFORMATION, CERAMIC HIGH VOLTAGE DISC CAPACITORS, 1 KV (DC) | | | | | | | | | |
|---|-------------|-------------|----------------|----------------|---------------|--------------|----------------|----------------|----------------|
| C (pF) | TOL. (%) | D x s (mm) | F ± 1* (mm) | d ± 0.05* (mm) | V ± 0.5* (mm) | CERAMIC CODE | ORDERING CODE | | |
| CLASS 2 K 2000 | | | | | | | | | |
| 47 | ± 10 % | 7.0 x 3.0 | 5 | 0.6 | 1.2 | Z | HAZ470□BA□□□KR | | |
| 56 | | 7.0 x 3.0 | | | | | HAZ560□BA□□□KR | | |
| 68 | | 7.0 x 3.0 | | | | | HAZ680□BA□□□KR | | |
| 82 | | 7.0 x 3.0 | | | | | HAZ820□BA□□□KR | | |
| 100 | | 7.0 x 3.0 | | | | | HAZ101□BA□□□KR | | |
| 150 | | 7.0 x 3.0 | | | | | HAZ151□BA□□□KR | | |
| 220 | | 7.0 x 3.0 | | | | | HAZ221□BA□□□KR | | |
| 330 | | 7.0 x 3.0 | | | | | HAZ331□BA□□□KR | | |
| 470 | | ± 20 % | | | | | 7.0 x 3.0 | HAZ471□BA□□□KR | |
| 680 | | 7.0 x 3.0 | | | | | HAZ681□BA□□□KR | | |
| 1000 | | 9.0 x 3.0 | | | | | HAZ102□BA□□□KR | | |
| 1500 | | 9.0 x 3.0 | | | | | HAZ152□BA□□□KR | | |
| 2200 | | 11.0 x 3.0 | | | | | HAZ222□BA□□□KR | | |
| 3300 | | 13.0 x 3.0 | | | | | HAZ332□BA□□□KR | | |
| 4700 | 15.0 x 3.0 | 7.5 | HAZ472□BA□□□KR | | | | | | |
| CLASS 2 K 6000 | | | | | | | | | |
| 1000 | ± 20 % | 7.0 x 3.0 | 5 | 0.6 | 1.2 | E | HAE102□BA□□□KR | | |
| 1500 | | 9.0 x 3.0 | | | | | HAE152□BA□□□KR | | |
| 2200 | | 9.0 x 3.0 | | | | | HAE222□BA□□□KR | | |
| 3300 | | 11.0 x 3.0 | | | | | HAE332□BA□□□KR | | |
| 4700 | | 11.0 x 3.0 | | | | | HAE472□BA□□□KR | | |
| 6800 | | 13.0 x 3.0 | | | | | HAE682□BA□□□KR | | |
| 0.010 μF | | 15.0 x 3.0 | | | | | 7.5 | HAE103□BA□□□KR | |
| CLASS 2 K 10000 | | | | | | | | | |
| 2200 | - 20 + 50 % | 7.0 x 3.0 | 5 | 0.6 | 1.2 | X | HAX222□BA□□□KR | | |
| 3300 | | 9.0 x 3.0 | | | | | HAX332□BA□□□KR | | |
| 4700 | | 9.0 x 3.0 | | | | | HAX472□BA□□□KR | | |
| 6800 | | 13.0 x 3.0 | | | | | HAX682□BA□□□KR | | |
| 0.010 μF | | (± 20 %) ** | | | | | 13.0 x 3.0 | 7.5 | HAX103□BA□□□KR |
| 0.015 μF | | | | | | | 17.0 x 3.0 | | HAX153□BA□□□KR |
| 0.022 μF | 18.0 x 3.0 | | HAX223□BA□□□KR | | | | | | |

* Standard lead configuration, other lead spacing and diameter available on request.

** ± 20 % available on request.

| ORDERING CODE | | | |
|---------------|--------------------|--|---|
| □ | 7th digit | Capacitance tolerance | ± 10 % = K ± 20 % = M + 50 - 20 % = S |
| □□□ | 10th to 12th digit | Lead configuration (See General Information) | |
| R | 14th digit | RoHS Compliant Component | |

| ORDERING INFORMATION, CERAMIC HIGH VOLTAGE DISC CAPACITORS, 2 KV (DC) | | | | | | | |
|---|--------------------------------|------------|--------------|-----------------|----------------|--------------|----------------|
| C (pF) | TOL. (%) | D x s (mm) | F ± 1 * (mm) | d ± 0.05 * (mm) | V ± 0.5 * (mm) | CERAMIC CODE | ORDERING CODE |
| CLASS 2 K 2000 | | | | | | | |
| 56 | ± 10 % ± 20 % | 7.0 x 3.0 | 7.5 | 0.6 | 1.4 | Z | HBZ560□BA□□□KR |
| 68 | | 7.0 x 3.0 | | | | | HBZ680□BB□□□KR |
| 82 | | 7.0 x 3.0 | | | | | HBZ820□BB□□□KR |
| 100 | | 7.0 x 3.0 | | | | | HBZ101□BB□□□KR |
| 150 | | 7.0 x 3.0 | | | | | HBZ151□BB□□□KR |
| 220 | | 7.0 x 3.0 | | | | | HBZ221□BB□□□KR |
| 330 | | 7.0 x 3.0 | | | | | HBZ331□BB□□□KR |
| 470 | | 7.0 x 3.0 | | | | | HBZ471□BB□□□KR |
| 680 | | 7.0 x 3.0 | | | | | HBZ681□BB□□□KR |
| 1000 | | 9.0 x 3.0 | | | | | HBZ102□BB□□□KR |
| 1500 | | 9.0 x 3.0 | | | | | HBZ152□BB□□□KR |
| 2200 | | 11.0 x 3.0 | | | | | HBZ222□BB□□□KR |
| 3300 | | 13.0 x 3.0 | | | | | HBZ332□BB□□□KR |
| 4700 | | 15.0 x 3.0 | | | | | HBZ472□BB□□□KR |
| CLASS 2 K 6000 | | | | | | | |
| 680 | ± 20 % | 7.0 x 3.0 | 7.5 | 0.6 | 1.4 | E | HBE681□BB□□□KR |
| 1000 | | 7.0 x 3.0 | | | | | HBE102□BB□□□KR |
| 1500 | | 9.0 x 3.0 | | | | | HBE152□BB□□□KR |
| 2200 | | 9.0 x 3.0 | | | | | HBE222□BB□□□KR |
| 3300 | | 11.0 x 3.0 | | | | | HBE332□BB□□□KR |
| 4700 | | 11.0 x 3.0 | | | | | HBE472□BB□□□KR |
| 6800 | | 13.0 x 3.0 | | | | | HBE682□BB□□□KR |
| 0.010 μF | | 15.0 x 3.0 | | | | | HBE103□BB□□□KR |
| CLASS 2 K 10000 | | | | | | | |
| 1500 | - 20 + 50 % (± 20 %) ** | 6.0 x 3.0 | 7.5 | 0.6 | 1.2 | X | HBX152□BB□□□KR |
| 2200 | | 7.0 x 3.0 | | | | | HBX222□BB□□□KR |
| 3300 | | 9.0 x 3.0 | | | | | HBX332□BB□□□KR |
| 4700 | | 9.0 x 3.0 | | | | | HBX472□BB□□□KR |
| 6800 | | 13.0 x 3.0 | | | | | HBX682□BB□□□KR |
| 0.010 μF | | 13.0 x 3.0 | | | | | HBX103□BB□□□KR |
| 0.015 μF | | 17.0 x 3.0 | | | | | HBX153□BB□□□KR |
| 0.022 μF | | 18.0 x 3.0 | | | | | HBX223□BB□□□KR |

* Standard lead configuration, other lead spacing and diameter available on request.

** ± 20 % available on request.

| ORDERING CODE | | | |
|---------------|--------------------|--|---|
| □ | 7th digit | Capacitance tolerance | ± 10 % = K ± 20 % = M + 50 - 20 % = S |
| □□□ | 10th to 12th digit | Lead configuration (See General Information) | |
| R | 14th digit | RoHS Compliant Component | |



| ORDERING INFORMATION, CERAMIC HIGH VOLTAGE DISC CAPACITORS, 3 KV (DC) | | | | | | | | | | | |
|---|------------|----------------|----------------|----------------|---------------|--------------|----------------|----------------|-----|---|----------------|
| C (pF) | TOL. (%) | D x s (mm) | F ± 1* (mm) | d ± 0.05* (mm) | V ± 0.5* (mm) | CERAMIC CODE | ORDERING CODE | | | | |
| CLASS 2 K 2000 | | | | | | | | | | | |
| 68 | ± 10 % | 7.0 x 4.0 | 10 | 0.6 | 1.8 | Z | HCZ680□BC□□□KR | | | | |
| 82 | | 7.0 x 4.0 | | | | | HCZ820□BC□□□KR | | | | |
| 100 | | 7.0 x 4.0 | | | | | HCZ101□BC□□□KR | | | | |
| 120 | | 7.0 x 4.0 | | | | | HCZ121□BC□□□KR | | | | |
| 150 | | 7.0 x 4.0 | | | | | HCZ151□BC□□□KR | | | | |
| 180 | | 8.0 x 4.0 | | | | | HCZ181□BC□□□KR | | | | |
| 220 | | 8.0 x 4.0 | | | | | HCZ221□BC□□□KR | | | | |
| 330 | | 8.0 x 4.0 | | | | | HCZ331□BC□□□KR | | | | |
| 470 | | ± 20 % | | | | | 10.0 x 4.0 | 0.8 | 2.0 | E | HCZ471□BC□□□KR |
| 680 | | | | | | | 10.0 x 4.0 | | | | HCZ681□BC□□□KR |
| 1000 | 11.0 x 4.0 | | HCZ102□BC□□□KR | | | | | | | | |
| 1200 | 15.0 x 4.0 | | HCZ122□BC□□□KR | | | | | | | | |
| 1500 | 15.0 x 4.0 | | HCZ152□BC□□□KR | | | | | | | | |
| 2200 | 17.0 x 4.0 | | HCZ222□BC□□□KR | | | | | | | | |
| 3300 | 21.0 x 4.0 | | HCZ332□BC□□□KR | | | | | | | | |
| 4700 | 21.0 x 4.0 | | HCZ472□BC□□□KR | | | | | | | | |
| 6800 | 25.0 x 4.0 | HCZ682□BC□□□KR | | | | | | | | | |
| CLASS 2 K 6000 | | | | | | | | | | | |
| 470 | ± 20 % | 7.0 x 4.0 | 10 | 0.6 | 2.0 | E | HCE471□BC□□□KR | | | | |
| 680 | | 8.0 x 4.0 | | | | | HCE681□BC□□□KR | | | | |
| 1000 | | 9.0 x 4.0 | | | | | HCE102□BC□□□KR | | | | |
| 1500 | | 11.0 x 4.0 | | | | | HCE152□BC□□□KR | | | | |
| 2200 | | 11.0 x 4.0 | | | | | HCE222□BC□□□KR | | | | |
| 3300 | | 15.0 x 4.0 | | 0.8 | 2.2 | | HCE332□BC□□□KR | | | | |
| 4700 | | 17.0 x 4.0 | | | | | HCE472□BC□□□KR | | | | |
| 6800 | | 21.0 x 4.0 | | | | | HCE682□BC□□□KR | | | | |
| 0.010 μF | | 25.0 x 4.0 | | | | | 2.5 | HCE103□BC□□□KR | | | |

* Standard lead configuration, other lead spacing and diameter available on request.

| ORDERING CODE | | | |
|---------------|--------------------|--|---|
| □ | 7th digit | Capacitance tolerance | ± 10 % = K ± 20 % = M + 50 - 20 % = S |
| □□□ | 10th to 12th digit | Lead configuration (See General Information) | |
| R | 14th digit | RoHS Compliant Component | |

| ORDERING INFORMATION, CERAMIC HIGH VOLTAGE DISC CAPACITORS, 4 KV (DC) | | | | | | | |
|---|----------------------|------------|--------------|-----------------|----------------|--------------|----------------|
| C (pF) | TOL. (%) | D x s (mm) | F ± 1 * (mm) | d ± 0.05 * (mm) | V ± 0.5 * (mm) | CERAMIC CODE | ORDERING CODE |
| CLASS 2 K 6000 | | | | | | | |
| 33 | ± 20 % (± 10 %)** | 8.0 x 4.5 | 12.5 | 0.6 | 1.9 | E | HDE330□BD□□□KR |
| 47 | | 8.0 x 5.0 | | | HDE470□BD□□□KR | | |
| 68 | | 8.0 x 5.0 | | | HDE680□BD□□□KR | | |
| 100 | | 8.0 x 5.0 | | | HDE101□BD□□□KR | | |
| 150 | | 8.0 x 5.0 | | | HDE151□BD□□□KR | | |
| 220 | | 8.0 x 5.0 | | | HDE221□BD□□□KR | | |
| 330 | | 8.0 x 5.0 | | | HDE331□BD□□□KR | | |
| 470 | | 8.0 x 5.0 | | | HDE471□BD□□□KR | | |
| 680 | | 9.0 x 5.0 | | | HDE681□BD□□□KR | | |
| 1000 | | 10.0 x 5.0 | | | HDE102□BD□□□KR | | |
| 1500 | | 12.0 x 5.0 | | | HDE152□BD□□□KR | | |
| 2200 | | 13.0 x 5.0 | | | HDE222□BD□□□KR | | |
| 3300 | | 15.0 x 5.0 | | | HDE332□BD□□□KR | | |
| 4700 | | 18.0 x 5.0 | | | HDE472□BD□□□KR | | |

* Standard lead configuration, other lead spacing and diameter available on request.

** ± 10 % available on request.

| ORDERING INFORMATION, CERAMIC HIGH VOLTAGE DISC CAPACITORS, 5 KV (DC) | | | | | | | |
|---|----------|------------|--------------|-----------------|----------------|--------------|----------------|
| C (pF) | TOL. (%) | D x s (mm) | F ± 1 * (mm) | d ± 0.05 * (mm) | V ± 0.5 * (mm) | CERAMIC CODE | ORDERING CODE |
| CLASS 2 K 6000 | | | | | | | |
| 220 | ± 20 % | 7.0 x 5.0 | 12.5 | 0.6 | 3.8 | E | HEE221□BE□□□KR |
| 330 | | 9.0 x 5.0 | | HEE331□BE□□□KR | | | |
| 680 | | 9.0 x 5.0 | | HEE681□BE□□□KR | | | |
| 1000 | | 11.0 x 5.0 | | HEE102□BE□□□KR | | | |
| 1500 | | 13.0 x 5.0 | | HEE152□BE□□□KR | | | |
| 2200 | | 15.0 x 5.0 | | HEE222□BE□□□KR | | | |

* Standard lead configuration, other lead spacing and diameter available on request.

| ORDERING CODE | | | |
|---------------|--------------------|--|--------------------------|
| □ | 7th digit | Capacitance tolerance | ± 10 % = K ± 20 % = M |
| □□□ | 10th to 12th digit | Lead configuration (See General Information) | |
| R | 14th digit | RoHS Compliant Component | |



| ORDERING INFORMATION, CERAMIC HIGH VOLTAGE DISC CAPACITORS, 6 KV (DC) | | | | | | | |
|---|-----------------------|----------------|-------------|----------------|---------------|--------------|----------------|
| C (pF) | TOL. (%) | D x s (mm) | F ± 1* (mm) | d ± 0.05* (mm) | V ± 0.5* (mm) | CERAMIC CODE | ORDERING CODE |
| CLASS 2 K 2000 | | | | | | | |
| 56 | ± 20 % (± 10 %) ** | 7.0 x 5.0 | 12.5 | 0.6 | 3.5 | Z | HFZ560□BF□□□KR |
| 68 | | 7.0 x 5.0 | | | | | HFZ680□BF□□□KR |
| 82 | | 7.0 x 5.0 | | | | | HFZ820□BF□□□KR |
| 100 | | 8.0 x 5.0 | | | | | HFZ101□BF□□□KR |
| 120 | | 8.0 x 5.0 | | | | | HFZ121□BF□□□KR |
| 150 | | 8.0 x 5.0 | | | | | HFZ151□BF□□□KR |
| 180 | | 10.0 x 5.0 | | | | | HFZ181□BF□□□KR |
| 220 | | 10.0 x 5.0 | | | | | HFZ221□BF□□□KR |
| 270 | | 10.0 x 5.0 | | | | | HFZ271□BF□□□KR |
| 330 | | 10.0 x 5.0 | | | | | HFZ331□BF□□□KR |
| 390 | | 12.0 x 5.0 | | HFZ391□BF□□□KR | | | |
| 470 | | 12.0 x 5.0 | | HFZ471□BF□□□KR | | | |
| 560 | | 13.0 x 5.0 | | HFZ561□BF□□□KR | | | |
| 680 | | 15.0 x 5.0 | | HFZ681□BF□□□KR | | | |
| 820 | | 15.0 x 5.0 | | HFZ821□BF□□□KR | | | |
| 1000 | | 17.0 x 5.0 | | HFZ102□BF□□□KR | | | |
| 1200 | | 19.0 x 5.0 | | HFZ122□BF□□□KR | | | |
| 1500 | | 21.0 x 5.0 | | HFZ152□BF□□□KR | | | |
| 1800 | | 21.0 x 5.0 | | HFZ182□BF□□□KR | | | |
| 2200 | | 25.0 x 5.0 | | HFZ222□BF□□□KR | | | |
| 2700 | 25.0 x 5.0 | HFZ272□BF□□□KR | | | | | |
| CLASS 2 K 6000 | | | | | | | |
| 150 | ± 20 % | 7.0 x 5.0 | 12.5 | 0.6 | 3.5 | E | HFE151□BF□□□KR |
| 220 | | 7.0 x 5.0 | | | | | HFE221□BF□□□KR |
| 330 | | 9.0 x 5.0 | | | | | HFE331□BF□□□KR |
| 470 | | 9.0 x 5.0 | | | | | HFE471□BF□□□KR |
| 680 | | 9.0 x 5.0 | | | | | HFE681□BF□□□KR |
| 1000 | | 11.0 x 5.5 | | | | | HFE102□BF□□□KR |
| 1500 | | 13.0 x 5.5 | | HFE152□BF□□□KR | | | |
| 2200 | | 15.0 x 5.5 | | HFE222□BF□□□KR | | | |
| 3300 | | 21.0 x 5.5 | | HFE332□BF□□□KR | | | |
| 4700 | | 21.0 x 5.5 | | HFE472□BF□□□KR | | | |
| 6800 | | 23.0 x 5.5 | | HFE682□BF□□□KR | | | |
| | | | | | | | |

* Standard lead configuration, other lead spacing and diameter available on request.

** ± 10 % available on request.

| ORDERING CODE | | | |
|---------------|--------------------|--|--------------------------|
| □ | 7th digit | Capacitance tolerance | ± 10 % = K ± 20 % = M |
| □□□ | 10th to 12th digit | Lead configuration (See General Information) | |
| R | 14th digit | RoHS Compliant Component | |

| ORDERING INFORMATION, CERAMIC HIGH VOLTAGE DISC CAPACITORS, 8 KV (DC) | | | | | | | |
|---|--------------------------|----------------|-----------------|--------------------|-------------------|-----------------|----------------|
| C (pF) | TOL. (%) | D x s (mm) | F ± 1 * (mm) | d ± 0.05 * (mm) | V ± 0.5 * (mm) | CERAMIC CODE | ORDERING CODE |
| CLASS 2 K 2000 | | | | | | | |
| 100 | ± 20 % (± 10 %)** | 9.0 x 8.3 | 12.5 | 0.8 | 4.0 | Z | HGZ101□BP□□□KR |
| 120 | | 9.0 x 8.3 | | | | | HGZ121□BP□□□KR |
| 150 | | 9.0 x 8.3 | | | | | HGZ151□BP□□□KR |
| 180 | | 11.0 x 8.3 | | | | | HGZ181□BP□□□KR |
| 220 | | 11.0 x 8.3 | | | | | HGZ221□BP□□□KR |
| 270 | | 11.0 x 8.3 | | | | | HGZ271□BP□□□KR |
| 330 | | 13.0 x 8.3 | | | | | HGZ331□BP□□□KR |
| 390 | | 13.0 x 8.3 | | | | | HGZ391□BP□□□KR |
| 470 | | 14.0 x 8.3 | | | | | HGZ471□BP□□□KR |
| 560 | | 16.0 x 8.3 | | | | | HGZ561□BP□□□KR |
| 680 | | 16.0 x 8.3 | | | | | HGZ681□BP□□□KR |
| 820 | | 18.0 x 8.3 | | | | | HGZ821□BP□□□KR |
| 1000 | | 18.0 x 8.3 | | | | | HGZ102□BP□□□KR |
| 1200 | | 21.0 x 8.3 | | | | | HGZ122□BP□□□KR |
| 1500 | | 21.0 x 8.3 | | | | | HGZ152□BP□□□KR |
| 1800 | | 24.0 x 8.3 | | | | | HGZ182□BP□□□KR |
| 2200 | 24.0 x 8.3 | HGZ222□BP□□□KR | | | | | |

* Standard lead configuration, other lead spacing and diameter available on request.

** ± 10 % available on request.

| ORDERING CODE | | | |
|---------------|--------------------|--|--------------------------|
| □ | 7th digit | Capacitance tolerance | ± 10 % = K ± 20 % = M |
| □□□ | 10th to 12th digit | Lead configuration (See General Information) | |
| R | 14th digit | RoHS Compliant Component | |



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.