

- Metallized polycarbonate
- CECC approval, detail specification 30501-020
- According to CECC 30500, IEC 60384-6




TYPICAL APPLICATIONS

Automotive and other applications in high ambient temperatures. Stable filters, oscillators and timing circuits.

CONSTRUCTION

Polycarbonate film capacitor with vacuum-evaporated aluminum electrodes. Radial leads of tinned wire are electrically welded to the contact metal layer on the ends of the capacitor winding. Encapsulation in self-extinguishing material meeting the requirements of UL 94V-0.



TECHNICAL DATA

	63	100	250	400
Rated voltage U_R , VDC	63	100	250	400
Rated voltage U_R , VAC	40	63	160	200
Capacitance, μF	0.001 -15	0.001 -6.8	0.001 -3.3	0.001 -1.0
Capacitance tolerance	$\pm 20\%$, $\pm 10\%$, $\pm 5\%$, $\pm 2.5\%$.			
Temperature range	-55 ... +125°C Above +85°C DC and AC voltage derating is 1.25%/°C.			
Climatic category	IEC 60068-1, 55/125/56 DIN 40040, FKD -55 ... +125°C Average relative humidity $\leq 80\%$ RH = 100% for 30 days per year. RH = 90% for further days limited by average value per year.			
Test voltage	1.6 x U_R VDC for 2 s			
Capacitance drift	Max. 2% after a 2 year storage period at a temperature of +10 ... +40°C and a relative humidity of 40...60%.			
Reliability	Operational life > 200 000 h. Failure rate < 6 FIT, T = +40°C, U = 0.5 x U_R . Failure criteria according to DIN 44122.			
Maximum pulse steepness:	dU/dt according to article table. For peak to peak voltages lower than rated voltage ($U_{pp} < U_R$), the specified dU/dt can be multiplied by the factor U_R/U_{pp} .			
Temperature coefficient	0 (± 100) ppm/°C (at 1 kHz)			
Self-inductance	Approximately 6 nH/cm for the total length of capacitor winding and the leads.			

p	d	std l	max l	b
5.0 \pm 0.4	0.5	4 ⁺¹	30	\pm 0.4
7.5 \pm 0.4	0.6	4 ⁺¹	30	\pm 0.4
10.0 \pm 0.4	0.6	4 ⁺¹	30	\pm 0.4
15.0 \pm 0.4	0.8	4 ⁺¹	30	\pm 0.4
22.5 \pm 0.4	0.8	4 ⁺¹	30	\pm 0.4
27.5 \pm 0.4	0.8	4 ⁺¹	30	\pm 0.4
37.5 \pm 0.5	1.0	4 ⁺¹	30	\pm 0.7

TECHNICAL DATA

Dissipation factor $\tan\delta$

Maximum values at +23°C
 $C \leq 0.1 \mu\text{F}$ $0.1 \mu\text{F} < C \leq 1.0 \mu\text{F}$ $C > 1.0 \mu\text{F}$


CMK5	1 kHz	0.3%	0.3%	
	10 kHz	0.5%	0.5%	
	100 kHz	0.8%	1.0%	
CMK7.5 ... 27.5	1 kHz	0.3%	0.3%	0.3%
	10 kHz	0.5%	0.5%	
	100 kHz	1.0%		

Insulation resistance


Minimum value between terminals
 Measured at +20°C, according to IEC 60384-6.
 $C \leq 0.33 \mu\text{F}$ $C > 0.33 \mu\text{F}$

$U_R \leq 100\text{V}$	15000 MΩ	5000 s
$U_R > 100\text{V}$	30000 MΩ	10000 s


TYPICAL DATA




Capacitance vs. temperature (at 1 kHz)




Capacitance vs. frequency (at +23°C)




Insulation resistance vs. temperature



Dissipation factor vs. temperature









Dissipation factor vs. frequency (at +23°C)



Resonance frequencies CMK 5

RATED AC VOLTAGE VS. FREQUENCY



ENVIRONMENTAL TEST DATA

Damp heat test Test conditions: $T = +40^{\circ}\text{C}$, $\text{RH} = 93\%$, $t = 56$ days.
 Test criteria: $\Delta C/C \leq \pm 3\%$,
 $\Delta \tan\delta \leq 0.003$ (1kHz),
 $\Delta \tan\delta \leq 0.005$ (10kHz),
 IR after test $0.5 \times \text{IR min.}$

Endurance test Test conditions: $T = +125^{\circ}\text{C}$, $U = 1.25 \times (0.5 \times U_R)$,
 $t = 2000$ h.
 Test criteria: $\Delta C/C \leq \pm 3\%$,
 $\Delta \tan\delta \leq 0.002$ (1kHz)
 $\Delta \tan\delta \leq 0.003$ (10kHz)
 IR after test $0.5 \times \text{IR min.}$

MARKING

- Capacitance
- Tolerance code
- Rated voltage
- Capacitor family code CMK
- Manufacturing date code

ORDERING INFORMATION

See article table and pages 18 to 23 for options and article code construction. The standard quantity/reel is for 360 mm reel. If 500 mm reel is required, it must be specified when ordering and the quantity is 2 x the given quantity.

ARTICLE TABLE

Capacitance μF	Max dimensions in mm				Quantity per package				Max dU/dt $\text{V}/\mu\text{s}$	Article code
	B	H	L	p	Bulk	Tray	Reel	Ammo		
63 VDC/40 VAC										
LEAD SPACING 5 MM										
0.0010	25	65	72	5.0	2000		2500	3000	10	CMK5 102K63L4 BULK
0.0012	25	65	72	5.0	2000		2500	3000	10	CMK5 122K63L4 BULK
0.0015	25	65	72	5.0	2000		2500	3000	10	CMK5 152K63L4 BULK
0.0018	25	65	72	5.0	2000		2500	3000	10	CMK5 182K63L4 BULK
0.0022	25	65	72	5.0	2000		2500	3000	10	CMK5 222K63L4 BULK
0.0027	25	65	72	5.0	2000		2500	3000	10	CMK5 272K63L4 BULK
0.0033	25	65	72	5.0	2000		2500	3000	10	CMK5 332K63L4 BULK
0.0039	25	65	72	5.0	2000		2500	3000	10	CMK5 392K63L4 BULK
0.0047	25	65	72	5.0	2000		2500	3000	10	CMK5 472K63L4 BULK
0.0056	25	65	72	5.0	2000		2500	3000	10	CMK5 562K63L4 BULK
0.0068	25	65	72	5.0	2000		2500	3000	10	CMK5 682K63L4 BULK
0.0082	25	65	72	5.0	2000		2500	3000	10	CMK5 822K63L4 BULK
0.010	25	65	72	5.0	2000		2500	3000	10	CMK5 103K63L4 BULK
0.012	25	65	72	5.0	2000		2500	3000	10	CMK5 123K63L4 BULK
0.015	25	65	72	5.0	2000		2500	3000	10	CMK5 153K63L4 BULK
0.018	25	65	72	5.0	2000		2500	3000	10	CMK5 183K63L4 BULK
0.022	25	65	72	5.0	2000		2500	3000	10	CMK5 223K63L4 BULK
0.027	25	65	72	5.0	2000		2500	3000	10	CMK5 273K63L4 BULK
0.033	25	65	72	5.0	2000		2500	3000	10	CMK5 333K63L4 BULK
0.039	25	65	72	5.0	2000		2500	3000	10	CMK5 393K63L4 BULK
0.047	25	65	72	5.0	2000		2500	3000	10	CMK5 473K63L4 BULK
0.056	25	65	72	5.0	2000		2500	3000	10	CMK5 563K63L4 BULK
0.068	25	65	72	5.0	2000		2500	3000	10	CMK5 683K63L4 BULK
0.082	25	65	72	5.0	2000		2500	3000	10	CMK5 823K63L4 BULK
0.10	35	80	72	5.0	2000		2000	2000	10	CMK5 104K63L4 BULK
0.12	35	80	72	5.0	2000		2000	2000	10	CMK5 124K63L4 BULK
0.15	35	80	72	5.0	2000		2000	2000	10	CMK5 154K63L4 BULK
0.18	35	80	72	5.0	2000		2000	2000	10	CMK5 184K63L4 BULK
0.22	35	80	72	5.0	2000		2000	2000	10	CMK5 224K63L4 BULK
0.27	45	90	72	5.0	1000		1500	1700	10	CMK5 274K63L4 BULK
0.33	45	90	72	5.0	1000		1500	1700	10	CMK5 334K63L4 BULK
0.39	50	100	72	5.0	1000		1300	1500	10	CMK5 394K63L4 BULK
0.47	60	110	72	5.0	1000		1000	1200	10	CMK5 474K63L4 BULK
0.56	60	110	72	5.0	1000		1000	1200	10	CMK5 564K63L4 BULK
0.68	72	130	72	5.0	1000		800		10	CMK5 684K63L4 BULK
LEAD SPACING 7.5 MM										
0.0010	40	80	105	7.5	1000		1700	1900	10	CMK7,5 102K63L4 BULK
0.0012	40	80	105	7.5	1000		1700	1900	10	CMK7,5 122K63L4 BULK
0.0015	40	80	105	7.5	1000		1700	1900	10	CMK7,5 152K63L4 BULK
0.0018	40	80	105	7.5	1000		1700	1900	10	CMK7,5 182K63L4 BULK
0.0022	40	80	105	7.5	1000		1700	1900	10	CMK7,5 222K63L4 BULK
0.0027	40	80	105	7.5	1000		1700	1900	10	CMK7,5 272K63L4 BULK
0.0033	40	80	105	7.5	1000		1700	1900	10	CMK7,5 332K63L4 BULK
0.0039	40	80	105	7.5	1000		1700	1900	10	CMK7,5 392K63L4 BULK
0.0047	40	80	105	7.5	1000		1700	1900	10	CMK7,5 472K63L4 BULK
0.0056	40	80	105	7.5	1000		1700	1900	10	CMK7,5 562K63L4 BULK
0.0068	40	80	105	7.5	1000		1700	1900	10	CMK7,5 682K63L4 BULK
0.0082	40	80	105	7.5	1000		1700	1900	10	CMK7,5 822K63L4 BULK
0.010	40	80	105	7.5	1000		1700	1900	10	CMK7,5 103K63L4 BULK
0.012	40	80	105	7.5	1000		1700	1900	10	CMK7,5 123K63L4 BULK
0.015	40	80	105	7.5	1000		1700	1900	10	CMK7,5 153K63L4 BULK
0.018	40	80	105	7.5	1000		1700	1900	10	CMK7,5 183K63L4 BULK
0.022	40	80	105	7.5	1000		1700	1900	10	CMK7,5 223K63L4 BULK
0.027	40	80	105	7.5	1000		1700	1900	10	CMK7,5 273K63L4 BULK
0.033	40	80	105	7.5	1000		1700	1900	10	CMK7,5 333K63L4 BULK
0.039	40	80	105	7.5	1000		1700	1900	10	CMK7,5 393K63L4 BULK
0.056	40	80	105	7.5	1000		1700	1900	10	CMK7,5 563K63L4 BULK
0.068	40	80	105	7.5	1000		1700	1900	10	CMK7,5 683K63L4 BULK
0.082	40	80	105	7.5	1000		1700	1900	10	CMK7,5 823K63L4 BULK

ARTICLE TABLE

Capacitance µF	Max dimensions in mm				Quantity per package				Max dU/dt V/µs	Article code
	B	H	L	p	Bulk	Tray	Reel	Ammo		

63 VDC/40 VAC

LEAD SPACING 7.5 MM

0.10	4.0	8.0	10.5	7.5	1000		1700	1900	10	CMK7,5 104K63L4 BULK
0.12	4.0	8.0	10.5	7.5	1000		1700	1900	10	CMK7,5 124K63L4 BULK
0.15	4.0	8.0	10.5	7.5	1000		1700	1900	10	CMK7,5 154K63L4 BULK
0.18	4.0	8.0	10.5	7.5	1000		1700	1900	10	CMK7,5 184K63L4 BULK
0.22	4.0	8.0	10.5	7.5	1000		1700	1900	10	CMK7,5 224K63L4 BULK
0.27	4.0	8.0	10.5	7.5	1000		1700	1900	10	CMK7,5 274K63L4 BULK
0.33	5.0	11.0	10.5	7.5	1000		1300	1500	10	CMK7,5 334K63L4 BULK
0.39	5.0	11.0	10.5	7.5	1000		1300	1500	10	CMK7,5 394K63L4 BULK
0.47	5.0	11.0	10.5	7.5	1000		1300	1500	10	CMK7,5 474K63L4 BULK
0.56	5.0	11.0	10.5	7.5	1000		1300	1500	10	CMK7,5 564K63L4 BULK
0.68	6.0	12.0	10.5	7.5	1000		1000	1200	10	CMK7,5 684K63L4 BULK

LEAD SPACING 10 MM

0.0027	4.0	9.0	13.0	10.0	1000		900		8	CMK10 272K63L4 BULK
0.0033	4.0	9.0	13.0	10.0	1000		900		8	CMK10 332K63L4 BULK
0.0039	4.0	9.0	13.0	10.0	1000		900		8	CMK10 392K63L4 BULK
0.0047	4.0	9.0	13.0	10.0	1000		900		8	CMK10 472K63L4 BULK
0.0056	4.0	9.0	13.0	10.0	1000		900		8	CMK10 562K63L4 BULK
0.0068	4.0	9.0	13.0	10.0	1000		900		8	CMK10 682K63L4 BULK
0.0082	4.0	9.0	13.0	10.0	1000		900		8	CMK10 822K63L4 BULK
0.010	4.0	9.0	13.0	10.0	1000		900		8	CMK10 103K63L4 BULK
0.012	4.0	9.0	13.0	10.0	1000		900		8	CMK10 123K63L4 BULK
0.015	4.0	9.0	13.0	10.0	1000		900		8	CMK10 153K63L4 BULK
0.018	4.0	9.0	13.0	10.0	1000		900		8	CMK10 183K63L4 BULK
0.022	4.0	9.0	13.0	10.0	1000		900		8	CMK10 223K63L4 BULK
0.027	4.0	9.0	13.0	10.0	1000		900		8	CMK10 273K63L4 BULK
0.033	4.0	9.0	13.0	10.0	1000		900		8	CMK10 333K63L4 BULK
0.039	4.0	9.0	13.0	10.0	1000		900		8	CMK10 393K63L4 BULK
0.047	4.0	9.0	13.0	10.0	1000		900		8	CMK10 473K63L4 BULK
0.056	4.0	9.0	13.0	10.0	1000		900		8	CMK10 563K63L4 BULK
0.068	4.0	9.0	13.0	10.0	1000		900		8	CMK10 683K63L4 BULK
0.082	4.0	9.0	13.0	10.0	1000		900		8	CMK10 823K63L4 BULK
0.10	4.0	9.0	13.0	10.0	1000		900		8	CMK10 104K63L4 BULK
0.12	4.0	9.0	13.0	10.0	1000		900		8	CMK10 124K63L4 BULK
0.15	4.0	9.0	13.0	10.0	1000		900		8	CMK10 154K63L4 BULK
0.18	4.0	9.0	13.0	10.0	1000		900		8	CMK10 184K63L4 BULK
0.22	4.0	9.0	13.0	10.0	1000		900		8	CMK10 224K63L4 BULK
0.27	4.0	9.0	13.0	10.0	1000		900		8	CMK10 274K63L4 BULK
0.33	4.0	9.0	13.0	10.0	1000		900		8	CMK10 334K63L4 BULK
0.39	4.0	9.0	13.0	10.0	1000		900		8	CMK10 394K63L4 BULK
0.47	4.5	10.5	13.0	10.0	1000		800		8	CMK10 474K63L4 BULK
0.56	5.0	11.0	13.0	10.0	800		700		8	CMK10 564K63L4 BULK
0.68	5.0	11.0	13.0	10.0	800		700		8	CMK10 684K63L4 BULK
0.82	6.0	12.0	13.0	10.0	600		500		8	CMK10 824K63L4 BULK
1.0	6.0	12.0	13.0	10.0	600		500		8	CMK10 105K63L4 BULK
1.2	6.0	12.0	13.0	10.0	600		500		8	CMK10 125K63L4 BULK

LEAD SPACING 15 MM

0.68	5.5	10.5	18.0	15.0	1000		600		6	CMK15 684K63L4 BULK
0.82	5.5	10.5	18.0	15.0	1000		600		6	CMK15 824K63L4 BULK
1.0	5.5	10.5	18.0	15.0	1000		600		6	CMK15 105K63L4 BULK
1.2	5.5	12.5	18.0	15.0	1000		600		6	CMK15 125K63L4 BULK
1.5	6.5	12.5	18.0	15.0	1000		500		6	CMK15 155K63L4 BULK
1.8	6.5	12.5	18.0	15.0	1000		500		6	CMK15 185K63L4 BULK
2.2	7.5	14.5	18.0	15.0	800		400		6	CMK15 225K63L4 BULK
2.7	8.0	15.0	18.0	15.0	600		400		6	CMK15 275K63L4 BULK
3.3	8.5	16.0	18.0	15.0	600		400		6	CMK15 335K63L4 BULK

ARTICLE TABLE

Capacitance µF	Max dimensions in mm				Quantity per package				Max dU/dt V/µs	Article code
	B	H	L	p	Bulk	Tray	Reel	Ammo		
63 VDC/40 VAC										
LEAD SPACING 22.5 MM										
2.7	6.5	14.5	26.0	22.5		234			3	CMK22,5 275K63L4 TRAY
3.3	6.5	14.5	26.0	22.5		234			3	CMK22,5 335K63L4 TRAY
3.9	7.0	16.5	26.0	22.5		216			3	CMK22,5 395K63L4 TRAY
4.7	7.0	16.5	26.0	22.5		216			3	CMK22,5 475K63L4 TRAY
5.6	9.0	18.5	26.0	22.5		168			3	CMK22,5 565K63L4 TRAY
6.8	9.0	18.5	26.0	22.5		168			3	CMK22,5 685K63L4 TRAY
8.2	10.5	19.0	26.0	22.5		264			3	CMK22,5 825K63L4 TRAY
10	11.0	21.5	26.0	22.5		253			3	CMK22,5 106K63L4 TRAY
LEAD SPACING 27.5 MM										
10	11.5	22.5	31.5	27.5		198			2	CMK27,5 106K63L4 TRAY
12	11.5	22.5	31.5	27.5		198			2	CMK27,5 126K63L4 TRAY
15	11.5	22.5	31.5	27.5		198			2	CMK27,5 156K63L4 TRAY
100 VDC/63 VAC										
LEAD SPACING 5 MM										
0.0010	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 102K100L4 BULK
0.0012	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 122K100L4 BULK
0.0015	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 152K100L4 BULK
0.0018	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 182K100L4 BULK
0.0022	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 222K100L4 BULK
0.0027	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 272K100L4 BULK
0.0033	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 332K100L4 BULK
0.0039	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 392K100L4 BULK
0.0047	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 472K100L4 BULK
0.0056	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 562K100L4 BULK
0.0068	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 682K100L4 BULK
0.0082	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 822K100L4 BULK
0.010	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 103K100L4 BULK
0.012	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 123K100L4 BULK
0.015	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 153K100L4 BULK
0.018	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 183K100L4 BULK
0.022	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 223K100L4 BULK
0.027	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 273K100L4 BULK
0.033	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 333K100L4 BULK
0.039	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 393K100L4 BULK
0.047	3.5	8.0	7.2	5.0	2000		2000	2000	15	CMK5 473K100L4 BULK
0.056	3.5	8.0	7.2	5.0	2000		2000	2000	15	CMK5 563K100L4 BULK
0.068	3.5	8.0	7.2	5.0	2000		2000	2000	15	CMK5 683K100L4 BULK
0.082	3.5	8.0	7.2	5.0	2000		2000	2000	15	CMK5 823K100L4 BULK
0.10	3.5	8.0	7.2	5.0	2000		2000	2000	15	CMK5 104K100L4 BULK
0.12	4.5	9.0	7.2	5.0	1000		1500	1700	15	CMK5 124K100L4 BULK
0.15	5.0	10.0	7.2	5.0	1000		1300	1500	15	CMK5 154K100L4 BULK
0.18	5.0	10.0	7.2	5.0	1000		1300	1500	15	CMK5 184K100L4 BULK
0.22	6.0	11.0	7.2	5.0	1000		1000	1200	15	CMK5 224K100L4 BULK
0.27	6.0	11.0	7.2	5.0	1000		1000	1200	15	CMK5 274K100L4 BULK
0.33	7.2	13.0	7.2	5.0	1000		800		15	CMK5 334K100L4 BULK
LEAD SPACING 7.5 MM										
0.0010	4.0	8.0	10.5	7.5	1000		1700	1900	15	CMK7,5 102K100L4 BULK
0.0012	4.0	8.0	10.5	7.5	1000		1700	1900	15	CMK7,5 122K100L4 BULK
0.0015	4.0	8.0	10.5	7.5	1000		1700	1900	15	CMK7,5 152K100L4 BULK
0.0018	4.0	8.0	10.5	7.5	1000		1700	1900	15	CMK7,5 182K100L4 BULK
0.0022	4.0	8.0	10.5	7.5	1000		1700	1900	15	CMK7,5 222K100L4 BULK
0.0027	4.0	8.0	10.5	7.5	1000		1700	1900	15	CMK7,5 272K100L4 BULK

ARTICLE TABLE

Capacitance µF	Max dimensions in mm				Quantity per package				Max dU/dt V/µs	Article code
	B	H	L	p	Bulk	Tray	Reel	Ammo		
100 VDC/63 VAC										
LEAD SPACING 7.5 MM										
0.0033	4.0	8.0	10.5	7.5	1000		1700	1900	15	CMK7,5 332K100L4 BULK
0.0039	4.0	8.0	10.5	7.5	1000		1700	1900	15	CMK7,5 392K100L4 BULK
0.0047	4.0	8.0	10.5	7.5	1000		1700	1900	15	CMK7,5 472K100L4 BULK
0.0056	4.0	8.0	10.5	7.5	1000		1700	1900	15	CMK7,5 562K100L4 BULK
0.0068	4.0	8.0	10.5	7.5	1000		1700	1900	15	CMK7,5 682K100L4 BULK
0.0082	4.0	8.0	10.5	7.5	1000		1700	1900	15	CMK7,5 822K100L4 BULK
0.010	4.0	8.0	10.5	7.5	1000		1700	1900	15	CMK7,5 103K100L4 BULK
0.012	4.0	8.0	10.5	7.5	1000		1700	1900	15	CMK7,5 123K100L4 BULK
0.015	4.0	8.0	10.5	7.5	1000		1700	1900	15	CMK7,5 153K100L4 BULK
0.018	4.0	8.0	10.5	7.5	1000		1700	1900	15	CMK7,5 183K100L4 BULK
0.022	4.0	8.0	10.5	7.5	1000		1700	1900	15	CMK7,5 223K100L4 BULK
0.027	4.0	8.0	10.5	7.5	1000		1700	1900	15	CMK7,5 273K100L4 BULK
0.033	4.0	8.0	10.5	7.5	1000		1700	1900	15	CMK7,5 333K100L4 BULK
0.039	4.0	8.0	10.5	7.5	1000		1700	1900	15	CMK7,5 393K100L4 BULK
0.047	4.0	8.0	10.5	7.5	1000		1700	1900	15	CMK7,5 473K100L4 BULK
0.056	4.0	8.0	10.5	7.5	1000		1700	1900	15	CMK7,5 563K100L4 BULK
0.068	4.0	8.0	10.5	7.5	1000		1700	1900	15	CMK7,5 683K100L4 BULK
0.082	4.0	8.0	10.5	7.5	1000		1700	1900	15	CMK7,5 823K100L4 BULK
0.10	4.0	8.0	10.5	7.5	1000		1700	1900	15	CMK7,5 104K100L4 BULK
0.12	4.0	8.0	10.5	7.5	1000		1700	1900	15	CMK7,5 124K100L4 BULK
0.15	5.0	11.0	10.5	7.5	1000		1300	1500	15	CMK7,5 154K100L4 BULK
0.18	5.0	11.0	10.5	7.5	1000		1300	1500	15	CMK7,5 184K100L4 BULK
0.22	5.0	11.0	10.5	7.5	1000		1300	1500	15	CMK7,5 224K100L4 BULK
0.27	6.0	12.0	10.5	7.5	1000		1000	1200	15	CMK7,5 274K100L4 BULK
0.33	6.0	12.0	10.5	7.5	1000		1000	1200	15	CMK7,5 334K100L4 BULK
LEAD SPACING 10 MM										
0.0027	4.0	9.0	13.0	10.0	1000		900		10	CMK10 272K100L4 BULK
0.0033	4.0	9.0	13.0	10.0	1000		900		10	CMK10 332K100L4 BULK
0.0039	4.0	9.0	13.0	10.0	1000		900		10	CMK10 392K100L4 BULK
0.0047	4.0	9.0	13.0	10.0	1000		900		10	CMK10 472K100L4 BULK
0.0056	4.0	9.0	13.0	10.0	1000		900		10	CMK10 562K100L4 BULK
0.0068	4.0	9.0	13.0	10.0	1000		900		10	CMK10 682K100L4 BULK
0.0082	4.0	9.0	13.0	10.0	1000		900		10	CMK10 822K100L4 BULK
0.010	4.0	9.0	13.0	10.0	1000		900		10	CMK10 103K100L4 BULK
0.012	4.0	9.0	13.0	10.0	1000		900		10	CMK10 123K100L4 BULK
0.015	4.0	9.0	13.0	10.0	1000		900		10	CMK10 153K100L4 BULK
0.018	4.0	9.0	13.0	10.0	1000		900		10	CMK10 183K100L4 BULK
0.022	4.0	9.0	13.0	10.0	1000		900		10	CMK10 223K100L4 BULK
0.027	4.0	9.0	13.0	10.0	1000		900		10	CMK10 273K100L4 BULK
0.033	4.0	9.0	13.0	10.0	1000		900		10	CMK10 333K100L4 BULK
0.039	4.0	9.0	13.0	10.0	1000		900		10	CMK10 393K100L4 BULK
0.047	4.0	9.0	13.0	10.0	1000		900		10	CMK10 473K100L4 BULK
0.056	4.0	9.0	13.0	10.0	1000		900		10	CMK10 563K100L4 BULK
0.068	4.0	9.0	13.0	10.0	1000		900		10	CMK10 683K100L4 BULK
0.082	4.0	9.0	13.0	10.0	1000		900		10	CMK10 823K100L4 BULK
0.10	4.0	9.0	13.0	10.0	1000		900		10	CMK10 104K100L4 BULK
0.12	4.0	9.0	13.0	10.0	1000		900		10	CMK10 124K100L4 BULK
0.15	4.0	9.0	13.0	10.0	1000		900		10	CMK10 154K100L4 BULK
0.18	4.0	9.0	13.0	10.0	1000		900		10	CMK10 184K100L4 BULK
0.22	4.5	10.5	13.0	10.0	1000		800		10	CMK10 224K100L4 BULK
0.27	5.0	11.0	13.0	10.0	800		700		10	CMK10 274K100L4 BULK
0.33	5.0	11.0	13.0	10.0	800		700		10	CMK10 334K100L4 BULK
0.39	6.0	12.0	13.0	10.0	600		500		10	CMK10 394K100L4 BULK
0.47	6.0	12.0	13.0	10.0	600		500		10	CMK10 474K100L4 BULK
0.56	6.0	12.0	13.0	10.0	600		500		10	CMK10 564K100L4 BULK

ARTICLE TABLE

Capacitance μF	Max dimensions in mm				Quantity per package				Max dU/dt V/ μs	Article code
	B	H	L	p	Bulk	Tray	Reel	Ammo		
100 VDC/63 VAC										
LEAD SPACING 15 MM										
0.27	5.5	10.5	18.0	15.0	1000		600		8	CMK15 274K100L4 BULK
0.33	5.5	10.5	18.0	15.0	1000		600		8	CMK15 334K100L4 BULK
0.39	5.5	10.5	18.0	15.0	1000		600		8	CMK15 394K100L4 BULK
0.47	5.5	10.5	18.0	15.0	1000		600		8	CMK15 474K100L4 BULK
0.56	5.5	12.5	18.0	15.0	1000		600		8	CMK15 564K100L4 BULK
0.68	6.5	12.5	18.0	15.0	1000		500		8	CMK15 684K100L4 BULK
0.82	6.5	12.5	18.0	15.0	1000		500		8	CMK15 824K100L4 BULK
1.0	7.5	14.5	18.0	15.0	800		400		8	CMK15 105K100L4 BULK
1.2	7.5	14.5	18.0	15.0	800		400		8	CMK15 125K100L4 BULK
1.5	8.5	16.0	18.0	15.0	600		400		8	CMK15 155K100L4 BULK
LEAD SPACING 22.5 MM										
1.5	6.5	14.5	26.0	22.5		234			4	CMK22,5 155K100L4 TRAY
1.8	7.0	16.5	26.0	22.5		216			4	CMK22,5 185K100L4 TRAY
2.2	7.0	16.5	26.0	22.5		216			4	CMK22,5 225K100L4 TRAY
2.7	9.0	18.5	26.0	22.5		168			4	CMK22,5 275K100L4 TRAY
3.3	9.0	18.5	26.0	22.5		168			4	CMK22,5 335K100L4 TRAY
3.9	10.5	19.0	26.0	22.5		264			4	CMK22,5 395K100L4 TRAY
LEAD SPACING 27.5 MM										
4.7	10.5	20.5	31.5	27.5		216			3	CMK27,5 475K100L4 TRAY
5.6	10.5	20.5	31.5	27.5		216			3	CMK27,5 565K100L4 TRAY
6.8	11.5	22.5	31.5	27.5		198			3	CMK27,5 685K100L4 TRAY
250 VDC/160 VAC										
LEAD SPACING 5 MM										
0.0010	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 102K250L4 BULK
0.0012	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 122K250L4 BULK
0.0015	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 152K250L4 BULK
0.0018	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 182K250L4 BULK
0.0022	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 222K250L4 BULK
0.0027	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 272K250L4 BULK
0.0033	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 332K250L4 BULK
0.0039	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 392K250L4 BULK
0.0047	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 472K250L4 BULK
0.0056	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 562K250L4 BULK
0.0068	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 682K250L4 BULK
0.0082	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 822K250L4 BULK
0.010	2.5	6.5	7.2	5.0	2000		2500	3000	15	CMK5 103K250L4 BULK
0.012	3.5	8.0	7.2	5.0	2000		2000	2000	15	CMK5 123K250L4 BULK
0.015	3.5	8.0	7.2	5.0	2000		2000	2000	15	CMK5 153K250L4 BULK
0.018	3.5	8.0	7.2	5.0	2000		2000	2000	15	CMK5 183K250L4 BULK
0.022	3.5	8.0	7.2	5.0	2000		2000	2000	15	CMK5 223K250L4 BULK
0.027	3.5	8.0	7.2	5.0	2000		2000	2000	15	CMK5 273K250L4 BULK
0.033	4.5	9.0	7.2	5.0	1000		1500	1700	15	CMK5 333K250L4 BULK
0.039	4.5	9.0	7.2	5.0	1000		1500	1700	15	CMK5 393K250L4 BULK
0.047	4.5	9.0	7.2	5.0	1000		1500	1700	15	CMK5 473K250L4 BULK
0.056	5.0	10.0	7.2	5.0	1000		1300	1500	15	CMK5 563K250L4 BULK
0.068	5.0	10.0	7.2	5.0	1000		1300	1500	15	CMK5 683K250L4 BULK
0.082	6.0	11.0	7.2	5.0	1000		1000	1200	15	CMK5 823K250L4 BULK
0.10	6.0	11.0	7.2	5.0	1000		1000	1200	15	CMK5 104K250L4 BULK

ARTICLE TABLE

Capacitance µF	Max dimensions in mm				Quantity per package				Max dU/dt V/µs	Article code
	B	H	L	p	Bulk	Tray	Reel	Ammo		

250 VDC/160 VAC

LEAD SPACING 7.5 MM

0.0010	4.0	8.0	10.5	7.5	1000		1700	1900	20	CMK7,5 102K250L4 BULK
0.0012	4.0	8.0	10.5	7.5	1000		1700	1900	20	CMK7,5 122K250L4 BULK
0.0015	4.0	8.0	10.5	7.5	1000		1700	1900	20	CMK7,5 152K250L4 BULK
0.0018	4.0	8.0	10.5	7.5	1000		1700	1900	20	CMK7,5 182K250L4 BULK
0.0022	4.0	8.0	10.5	7.5	1000		1700	1900	20	CMK7,5 222K250L4 BULK
0.0027	4.0	8.0	10.5	7.5	1000		1700	1900	20	CMK7,5 272K250L4 BULK
0.0033	4.0	8.0	10.5	7.5	1000		1700	1900	20	CMK7,5 332K250L4 BULK
0.0039	4.0	8.0	10.5	7.5	1000		1700	1900	20	CMK7,5 392K250L4 BULK
0.0047	4.0	8.0	10.5	7.5	1000		1700	1900	20	CMK7,5 472K250L4 BULK
0.0056	4.0	8.0	10.5	7.5	1000		1700	1900	20	CMK7,5 562K250L4 BULK
0.0068	4.0	8.0	10.5	7.5	1000		1700	1900	20	CMK7,5 682K250L4 BULK
0.0082	4.0	8.0	10.5	7.5	1000		1700	1900	20	CMK7,5 822K250L4 BULK
0.010	4.0	8.0	10.5	7.5	1000		1700	1900	20	CMK7,5 103K250L4 BULK
0.012	4.0	8.0	10.5	7.5	1000		1700	1900	20	CMK7,5 123K250L4 BULK
0.015	4.0	8.0	10.5	7.5	1000		1700	1900	20	CMK7,5 153K250L4 BULK
0.018	4.0	8.0	10.5	7.5	1000		1700	1900	20	CMK7,5 183K250L4 BULK
0.022	4.0	8.0	10.5	7.5	1000		1700	1900	20	CMK7,5 223K250L4 BULK
0.027	4.0	8.0	10.5	7.5	1000		1700	1900	20	CMK7,5 273K250L4 BULK
0.033	4.0	8.0	10.5	7.5	1000		1700	1900	20	CMK7,5 333K250L4 BULK
0.039	4.0	8.0	10.5	7.5	1000		1700	1900	20	CMK7,5 393K250L4 BULK
0.047	4.0	8.0	10.5	7.5	1000		1700	1900	20	CMK7,5 473K250L4 BULK
0.056	5.0	11.0	10.5	7.5	1000		1300	1500	20	CMK7,5 563K250L4 BULK
0.068	5.0	11.0	10.5	7.5	1000		1300	1500	20	CMK7,5 683K250L4 BULK
0.082	5.0	11.0	10.5	7.5	1000		1300	1500	20	CMK7,5 823K250L4 BULK
0.10	6.0	12.0	10.5	7.5	1000		1000	1200	20	CMK7,5 104K250L4 BULK

LEAD SPACING 10 MM

0.0022	4.0	9.0	13.0	10.0	1000		900		15	CMK10 222K250L4 BULK
0.0027	4.0	9.0	13.0	10.0	1000		900		15	CMK10 272K250L4 BULK
0.0033	4.0	9.0	13.0	10.0	1000		900		15	CMK10 332K250L4 BULK
0.0039	4.0	9.0	13.0	10.0	1000		900		15	CMK10 392K250L4 BULK
0.0047	4.0	9.0	13.0	10.0	1000		900		15	CMK10 472K250L4 BULK
0.0056	4.0	9.0	13.0	10.0	1000		900		15	CMK10 562K250L4 BULK
0.0068	4.0	9.0	13.0	10.0	1000		900		15	CMK10 682K250L4 BULK
0.0082	4.0	9.0	13.0	10.0	1000		900		15	CMK10 822K250L4 BULK
0.010	4.0	9.0	13.0	10.0	1000		900		15	CMK10 103K250L4 BULK
0.012	4.0	9.0	13.0	10.0	1000		900		15	CMK10 123K250L4 BULK
0.015	4.0	9.0	13.0	10.0	1000		900		15	CMK10 153K250L4 BULK
0.018	4.0	9.0	13.0	10.0	1000		900		15	CMK10 183K250L4 BULK
0.022	4.0	9.0	13.0	10.0	1000		900		15	CMK10 223K250L4 BULK
0.027	4.0	9.0	13.0	10.0	1000		900		15	CMK10 273K250L4 BULK
0.033	4.0	9.0	13.0	10.0	1000		900		15	CMK10 333K250L4 BULK
0.039	4.0	9.0	13.0	10.0	1000		900		15	CMK10 393K250L4 BULK
0.047	4.0	9.0	13.0	10.0	1000		900		15	CMK10 473K250L4 BULK
0.056	4.0	9.0	13.0	10.0	1000		900		15	CMK10 563K250L4 BULK
0.068	4.5	10.5	13.0	10.0	1000		800		15	CMK10 683K250L4 BULK
0.082	4.5	10.5	13.0	10.0	1000		800		15	CMK10 823K250L4 BULK
0.10	5.0	11.0	13.0	10.0	800		700		15	CMK10 104K250L4 BULK
0.12	6.0	12.0	13.0	10.0	600		500		15	CMK10 124K250L4 BULK
0.15	6.0	12.0	13.0	10.0	600		500		15	CMK10 154K250L4 BULK
0.18	6.0	12.0	13.0	10.0	600		500		15	CMK10 184K250L4 BULK

LEAD SPACING 15 MM

0.10	5.5	10.5	18.0	15.0	1000		600		10	CMK15 104K250L4 BULK
0.12	5.5	10.5	18.0	15.0	1000		600		10	CMK15 124K250L4 BULK
0.15	5.5	10.5	18.0	15.0	1000		600		10	CMK15 154K250L4 BULK
0.18	5.5	10.5	18.0	15.0	1000		600		10	CMK15 184K250L4 BULK
0.22	5.5	12.5	18.0	15.0	1000		600		10	CMK15 224K250L4 BULK
0.27	6.5	12.5	18.0	15.0	1000		500		10	CMK15 274K250L4 BULK
0.33	7.5	14.5	18.0	15.0	800		400		10	CMK15 334K250L4 BULK
0.39	7.5	14.5	18.0	15.0	800		400		10	CMK15 394K250L4 BULK

ARTICLE TABLE

Capacitance µF	Max dimensions in mm				Quantity per package				Max dU/dt V/µs	Article code	
	B	H	L	p	Bulk	Tray	Reel	Ammo			
250 VDC/160 VAC											
LEAD SPACING 22.5 MM											
0.47	6.5	14.5	26.0	22.5		234				8	CMK22,5 474K250L4 TRAY
0.56	6.5	14.5	26.0	22.5		234				8	CMK22,5 564K250L4 TRAY
0.68	7.0	16.5	26.0	22.5		216				8	CMK22,5 684K250L4 TRAY
0.82	7.0	16.5	26.0	22.5		216				8	CMK22,5 824K250L4 TRAY
1.0	9.0	18.5	26.0	22.5		168				8	CMK22,5 105K250L4 TRAY
1.2	9.0	18.5	26.0	22.5		168				8	CMK22,5 125K250L4 TRAY
1.5	9.0	18.5	26.0	22.5		168				8	CMK22,5 155K250L4 TRAY
1.8	11.0	21.5	26.0	22.5		253				8	CMK22,5 185K250L4 TRAY
2.2	11.0	21.5	26.0	22.5		253				8	CMK22,5 225K250L4 TRAY
LEAD SPACING 27.5 MM											
1.5	10.5	20.5	31.5	27.5		216				6	CMK27,5 155K250L4 TRAY
1.8	10.5	20.5	31.5	27.5		216				6	CMK27,5 185K250L4 TRAY
2.2	11.5	22.5	31.5	27.5		198				6	CMK27,5 225K250L4 TRAY
2.7	14.5	24.5	31.5	27.5		153				6	CMK27,5 275K250L4 TRAY
3.3	14.5	24.5	31.5	27.5		153				6	CMK27,5 335K250L4 TRAY
400 VDC/200 VAC											
LEAD SPACING 7.5 MM											
0.0010	4.0	8.0	10.5	7.5	1000		1700	1900		30	CMK7,5 102K400L4 BULK
0.0012	4.0	8.0	10.5	7.5	1000		1700	1900		30	CMK7,5 122K400L4 BULK
0.0015	4.0	8.0	10.5	7.5	1000		1700	1900		30	CMK7,5 152K400L4 BULK
0.0018	4.0	8.0	10.5	7.5	1000		1700	1900		30	CMK7,5 182K400L4 BULK
0.0022	4.0	8.0	10.5	7.5	1000		1700	1900		30	CMK7,5 222K400L4 BULK
0.0027	4.0	8.0	10.5	7.5	1000		1700	1900		30	CMK7,5 272K400L4 BULK
0.0033	4.0	8.0	10.5	7.5	1000		1700	1900		30	CMK7,5 332K400L4 BULK
0.0039	4.0	8.0	10.5	7.5	1000		1700	1900		30	CMK7,5 392K400L4 BULK
0.0047	4.0	8.0	10.5	7.5	1000		1700	1900		30	CMK7,5 472K400L4 BULK
0.0056	4.0	8.0	10.5	7.5	1000		1700	1900		30	CMK7,5 562K400L4 BULK
0.0068	4.0	8.0	10.5	7.5	1000		1700	1900		30	CMK7,5 682K400L4 BULK
0.0082	4.0	8.0	10.5	7.5	1000		1700	1900		30	CMK7,5 822K400L4 BULK
0.010	4.0	8.0	10.5	7.5	1000		1700	1900		30	CMK7,5 103K400L4 BULK
0.012	4.0	8.0	10.5	7.5	1000		1700	1900		30	CMK7,5 123K400L4 BULK
0.015	4.0	8.0	10.5	7.5	1000		1700	1900		30	CMK7,5 153K400L4 BULK
0.018	4.0	8.0	10.5	7.5	1000		1700	1900		30	CMK7,5 183K400L4 BULK
0.022	5.0	11.0	10.5	7.5	1000		1300	1500		30	CMK7,5 223K400L4 BULK
0.027	5.0	11.0	10.5	7.5	1000		1300	1500		30	CMK7,5 273K400L4 BULK
0.033	5.0	11.0	10.5	7.5	1000		1300	1500		30	CMK7,5 333K400L4 BULK
0.039	6.0	12.0	10.5	7.5	1000		1000	1200		30	CMK7,5 393K400L4 BULK
0.047	6.0	12.0	10.5	7.5	1000		1000	1200		30	CMK7,5 473K400L4 BULK
0.056	6.0	12.0	10.5	7.5	1000		1000	1200		30	CMK7,5 563K400L4 BULK
LEAD SPACING 10 MM											
0.0022	4.0	9.0	13.0	10.0	1000		900			25	CMK10 222K400L4 BULK
0.0027	4.0	9.0	13.0	10.0	1000		900			25	CMK10 272K400L4 BULK
0.0033	4.0	9.0	13.0	10.0	1000		900			25	CMK10 332K400L4 BULK
0.0039	4.0	9.0	13.0	10.0	1000		900			25	CMK10 392K400L4 BULK
0.0047	4.0	9.0	13.0	10.0	1000		900			25	CMK10 472K400L4 BULK
0.0056	4.0	9.0	13.0	10.0	1000		900			25	CMK10 562K400L4 BULK
0.0068	4.0	9.0	13.0	10.0	1000		900			25	CMK10 682K400L4 BULK
0.0082	4.0	9.0	13.0	10.0	1000		900			25	CMK10 822K400L4 BULK
0.010	4.0	9.0	13.0	10.0	1000		900			25	CMK10 103K400L4 BULK
0.012	4.0	9.0	13.0	10.0	1000		900			25	CMK10 123K400L4 BULK
0.015	4.0	9.0	13.0	10.0	1000		900			25	CMK10 153K400L4 BULK
0.018	4.0	9.0	13.0	10.0	1000		900			25	CMK10 183K400L4 BULK
0.022	4.0	9.0	13.0	10.0	1000		900			25	CMK10 223K400L4 BULK

ARTICLE TABLE

Capacitance μF	Max dimensions in mm				Quantity per package				Max dU/dt $\text{V}/\mu\text{s}$	Article code
	B	H	L	p	Bulk	Tray	Reel	Ammo		
400 VDC/200 VAC										
LEAD SPACING 10 MM										
0.027	4.5	10.5	13.0	10.0	1000		800		25	CMK10 273K400L4 BULK
0.033	5.0	11.0	13.0	10.0	800		700		25	CMK10 333K400L4 BULK
0.039	5.0	11.0	13.0	10.0	800		700		25	CMK10 393K400L4 BULK
0.047	6.0	12.0	13.0	10.0	600		500		25	CMK10 473K400L4 BULK
0.056	6.0	12.0	13.0	10.0	600		500		25	CMK10 563K400L4 BULK
0.068	6.0	12.0	13.0	10.0	600		500		25	CMK10 683K400L4 BULK
LEAD SPACING 15 MM										
0.047	5.5	10.5	18.0	15.0	1000		600		15	CMK15 473K400L4 BULK
0.056	5.5	10.5	18.0	15.0	1000		600		15	CMK15 563K400L4 BULK
0.068	5.5	10.5	18.0	15.0	1000		600		15	CMK15 683K400L4 BULK
0.082	5.5	12.5	18.0	15.0	1000		600		15	CMK15 823K400L4 BULK
0.10	6.5	12.5	18.0	15.0	1000		500		15	CMK15 104K400L4 BULK
0.12	7.5	14.5	18.0	15.0	800		400		15	CMK15 124K400L4 BULK
0.15	7.5	14.5	18.0	15.0	800		400		15	CMK15 154K400L4 BULK
0.18	8.0	15.0	18.0	15.0	600		400		15	CMK15 184K400L4 BULK
LEAD SPACING 22.5 MM										
0.15	6.5	14.5	26.0	22.5			234		10	CMK22,5 154K400L4 TRAY
0.18	6.5	14.5	26.0	22.5			234		10	CMK22,5 184K400L4 TRAY
0.22	6.5	14.5	26.0	22.5			234		10	CMK22,5 224K400L4 TRAY
0.27	7.0	16.5	26.0	22.5			216		10	CMK22,5 274K400L4 TRAY
0.33	8.0	16.0	26.0	22.5			186		10	CMK22,5 334K400L4 TRAY
0.39	9.0	18.5	26.0	22.5			168		10	CMK22,5 394K400L4 TRAY
0.47	9.0	18.5	26.0	22.5			168		10	CMK22,5 474K400L4 TRAY
0.56	10.5	19.0	26.0	22.5			264		10	CMK22,5 564K400L4 TRAY
LEAD SPACING 27.5 MM										
0.47	10.5	20.5	31.5	27.5			216		8	CMK27,5 474K400L4 TRAY
0.56	10.5	20.5	31.5	27.5			216		8	CMK27,5 564K400L4 TRAY
0.68	10.5	20.5	31.5	27.5			216		8	CMK27,5 684K400L4 TRAY
0.82	10.5	20.5	31.5	27.5			216		8	CMK27,5 824K400L4 TRAY
1.0	11.5	22.5	31.5	27.5			198		8	CMK27,5 105K400L4 TRAY