

PHE844RD6150MR06L2

aka F844DM154M440C PHE844RD6150MD15R06L2

Capacitor, film, 0.15 μ F, +/-20% Tol, -40/+105C, Safety: X1, 440VAC,
Lead Spacing=22.5 mm



Dimensions (mm)

| ID | Dimension | Tolerance |
|----|-----------|-----------|
| L | 26 | max |
| H | 18.5 | max |
| T | 9 | max |
| S | 22.5 | +/-0.4 |
| LL | 6 | nom |
| F | 0.8 | nom |

Specifications

| | |
|------------------------------|--------------------------|
| Manufacturer: | KEMET |
| Brand: | Rifa |
| Capacitance: | 0.15 μ F |
| Temperature Range: | -40/+105C |
| Rated Temperature: | 105C |
| Voltage @ rated temp: | 1000V |
| Voltage AC: | 440VAC |
| Tolerance: | +/-20% |
| Body Type: | Radial Box |
| Construction: | Non-inductive |
| Application: | Safety: X1 |
| Dielectric: | Metallized Polypropylene |
| Dissipation Factor @ 1 kHz: | 0.1% |
| Dissipation Factor @ 10 kHz: | 0.4% |
| Insulation Resistance: | 30 GOhm |
| Maximum dVdT: | 100v/us |
| UL_1414: | 250V |
| UL_1283: | 480V |
| IEC_60384-14: | 440V |
| EN_132400: | 440V |
| C_22.2_NO.1: | 250V |
| C_22.2_NO.8: | 480V |
| Miscellaneous Electrical: | PHE844 |
| Package Kind: | Bulk |
| Package Type: | Tray |
| Package Quantity: | 308 |