


Solid Tantalum Chip Capacitors, MIDGET[®], Conformal Coated



FEATURES

- 8 mm, 12 mm, 16 mm tape and reel packaging available per EIA-481-1 and reeling per IEC 286-3, 7" [178 mm] standard
- Compliant to RoHS Directive 2002/95/EC



RoHS*
COMPLIANT

PERFORMANCE CHARACTERISTICS

Operating Temperature: - 55 °C to + 85 °C
(To + 125 °C with voltage derating)

Note: Refer to Doc. 40088

Capacitance Range: 0.10 μF to 330 μF

Capacitance Tolerance: ± 10 %, ± 20 % standard


Voltage Rating: 4 WV_{DC} to 50 WV_{DC}

ORDERING INFORMATION						
194D	225	X0	004	A	2	T
TYPE	CAPACITANCE	CAPACITANCE TOLERANCE	DC VOLTAGE RATING AT + 85 °C	CASE CODE	TERMINATION	PACKAGING
This is expressed in picofarads. The first two digits are the significant figures. The third is the number of zeros to follow	X0 = ± 20 % X9 = ± 10 % X5 = ± 5 % Special Order		This is expressed in volts. To complete the three-digit block, zeros precede the voltage rating	See Ratings and Case Codes Table	2 = Gold plated Standard (RoHS compliant) (50 μ" minimum) 8 = 60/40 solder plated 7 = Hot solder dipped	T = T/R (full reel) 7" [178 mm] reel standard H = T/R (half reel) 7" [178 mm] B = Bulk See Tape and Reel Specifications

Note

- Preferred tolerance and reel sizes are in bold.
- We reserve the right to supply higher voltage ratings and tighter capacitance tolerance capacitors in the same case size. Voltage substitutions will be marked with the higher voltage rating.

DIMENSIONS in inches [millimeters]



CASE CODE	W	L	H	P	T ₁	T ₂ (MAX.)
A	0.050 ± 0.015 [1.27 ± 0.38]	0.100 ± 0.015 [2.54 ± 0.38]	0.050 ± 0.015 [1.27 ± 0.38]	0.030 ± 0.005 [0.76 ± 0.13]	0.005 [0.13]	0.015 [0.38]
B	0.050 ± 0.015 [1.27 ± 0.38]	0.150 ± 0.015 [3.81 ± 0.38]	0.050 ± 0.015 [1.27 ± 0.38]	0.030 ± 0.005 [0.76 ± 0.13]	0.005 [0.13]	0.015 [0.38]
C	0.050 ± 0.015 [1.27 ± 0.38]	0.200 ± 0.015 [5.08 ± 0.38]	0.050 ± 0.015 [1.27 ± 0.38]	0.030 ± 0.005 [0.76 ± 0.13]	0.005 [0.13]	0.015 [0.38]
D	0.100 ± 0.015 [2.54 ± 0.38]	0.150 ± 0.015 [3.81 ± 0.38]	0.050 ± 0.015 [1.27 ± 0.38]	0.030 ± 0.005 [0.76 ± 0.13]	0.005 [0.13]	0.015 [0.38]
E	0.100 ± 0.015 [2.54 ± 0.38]	0.200 ± 0.015 [5.08 ± 0.38]	0.050 ± 0.015 [1.27 ± 0.38]	0.030 ± 0.005 [0.76 ± 0.13]	0.005 [0.13]	0.015 [0.38]
F	0.135 ± 0.015 [3.43 ± 0.38]	0.220 ± 0.015 [5.59 ± 0.38]	0.070 ± 0.015 [1.78 ± 0.38]	0.030 ± 0.005 [0.76 ± 0.13]	0.005 [0.13]	0.015 [0.38]
G	0.110 ± 0.015 [2.79 ± 0.38]	0.265 ± 0.015 [6.73 ± 0.38]	0.110 ± 0.015 [2.79 ± 0.38]	0.050 ± 0.005 [1.27 ± 0.13]	0.005 [0.13]	0.015 [0.38]
H	0.150 ± 0.015 [3.81 ± 0.38]	0.285 ± 0.015 [7.24 ± 0.38]	0.110 ± 0.015 [2.79 ± 0.38]	0.050 ± 0.005 [1.27 ± 0.13]	0.005 [0.13]	0.015 [0.38]

Note

- When solder coated terminations are required, add 0.015" [0.381 mm] to termination dimension tolerances
- * Pb containing terminations that are not RoHS compliant, exemptions may apply.



194D RATINGS AND CASE CODES								
μF	4 V	6 V	10 V	15 V	20 V	25 V	35 V	50 V
0.10							A	A
0.15							A	A
0.22							A	B
0.33						A	B	B
0.47					A	A/B	B	C
0.68				A	A/B	B	C	D
1.0			A	A/B	A/B	C	D	E
1.5		A	A/B	A/B	B/C	D	E	F
2.2	A	A/B	A/B	A/B/C	C/D	E	F	F
3.3	A/B	A/B	A/B/C	C/D	D/E	F	F	G
4.7	B	A/B/C	B/C/D	D/E	E/F	F	F/G	H
6.8	B/C	C/D	D/E	E/F	F	F/G	G/H	H
10	C/D	D/E	E/F	E/F	E/F/G	F/G	G/H	
15	D/E	E/F	E/F	F/G	F/G	H	H	
22	E/F	F	F/G	F/G	G/H	H		
33	F	F/G	F/G	G/H	H	H		
47	F/G	F/G	G/H	G/H				
68	F/G	G/H	H	H				
100	H	H	H					
120	H	H	H					
150	H	H						
330	H	H						

STANDARD/EXTENDED RATINGS				
CAPACITANCE (μF)	CASE CODE	PART NUMBER (1)	MAX. DCL AT + 25 °C (μA)	MAX. DF AT + 25 °C 120 Hz (%)
4 WV _{DC} AT + 85 °C, SURGE = 5 V . . . 2.7 WV _{DC} AT + 125 °C, SURGE = 3.4 V				
2.2	A	194D225X_004A2	0.5	6
3.3	A	194D335X_004A2	0.5	6
3.3	B	194D335X_004B2	0.5	6
4.7	B	194D475X_004B2	0.5	6
6.8	B	194D685X_004B2	0.5	6
6.8	C	194D685X_004C2	0.5	6
10	C	194D106X_004C2	0.5	6
10	D	194D106X_004D2	0.5	6
15	D	194D156X_004D2	0.6	6
15	E	194D156X_004E2	0.6	6
22	E	194D226X_004E2	0.9	6
22	F	194D226X_004F2	0.9	6
33	F	194D336X_004F2	1.3	6
47	F	194D476X_004F2	1.9	6
47	G	194D476X_004G2	1.9	6
68	F	194D686X_004F2	2.7	6
68	G	194D686X_004G2	2.7	6
100	H	194D107X_004H2	4.0	8
120	H	194D127X_004H2	4.8	8
150	H	194D157X_004H2	6.0	8
330	H	194D337X_004H2	13.2	10

Note

(1) For 10 % tolerance, specify "9"; for 20 % tolerance, change to "0".

STANDARD/EXTENDED RATINGS

CAPACITANCE (μ F)	CASE CODE	PART NUMBER (1)	MAX. DCL AT + 25 °C (μ A)	MAX. DF AT + 25 °C 120 Hz (%)
6 WV_{DC} AT + 85 °C, SURGE = 8 V . . . 4 WV_{DC} AT + 125 °C, SURGE = 5 V				
1.5	A	194D155X_006A2	0.5	6
2.2	A	194D225X_006A2	0.5	6
2.2	B	194D225X_006B2	0.5	6
3.3	A	194D335X_006A2	0.5	6
3.3	B	194D335X_006B2	0.5	6
4.7	A	194D475X_006A2	0.5	6
4.7	B	194D475X_006B2	0.5	6
4.7	C	194D475X_006C2	0.5	6
6.8	C	194D685X_006C2	0.5	6
6.8	D	194D685X_006D2	0.5	6
10	D	194D106X_006D2	0.6	6
10	E	194D106X_006E2	0.6	6
15	E	194D156X_006E2	1.0	6
15	F	194D156X_006F2	1.0	6
22	F	194D226X_006F2	1.4	6
33	F	194D336X_006F2	2.1	6
33	G	194D336X_006G2	2.1	6
47	F	194D476X_006F2	3.0	6
47	G	194D476X_006G2	3.0	6
68	G	194D686X_006G2	4.3	6
68	H	194D686X_006H2	4.3	6
100	H	194D107X_006H2	6.0	8
120	H	194D127X_006H2	7.2	8
150	H	194D157X_006H2	9.0	8
330	H	194D337X_006H2	20	10
10 WV_{DC} AT + 85 °C, SURGE = 13 V . . . 7 WV_{DC} AT + 125 °C, SURGE = 9 V				
1.0	A	194D105X_010A2	0.5	4
1.5	A	194D155X_010A2	0.5	6
1.5	B	194D155X_010B2	0.5	6
2.2	A	194D225X_010A2	0.5	6
2.2	B	194D225X_010B2	0.5	6
3.3	A	194D335X_010A2	0.5	6
3.3	B	194D335X_010B2	0.5	6
3.3	C	194D335X_010C2	0.5	6
4.7	B	194D475X_010B2	0.5	6
4.7	C	194D475X_010C2	0.5	6
4.7	D	194D475X_010D2	0.5	6
6.8	D	194D685X_010D2	0.7	6
6.8	E	194D685X_010E2	0.7	6
10	C	194D106X_010C2	1.0	6
10	E	194D106X_010E2	1.0	6
10	F	194D106X_010F2	1.0	6
15	E	194D156X_010E2	1.5	6
15	F	194D156X_010F2	1.5	6
22	F	194D226X_010F2	2.2	6
22	G	194D226X_010G2	2.2	6
33	F	194D336X_010F2	3.3	6
33	G	194D336X_010G2	3.3	6
47	G	194D476X_010G2	4.7	6
47	H	194D476X_010H2	4.7	6
68	H	194D686X_010H2	6.8	6
100	H	194D107X_010H2	10	8
120	H	194D127X_010H2	12	8

Note

(1) For 10 % tolerance, specify "9"; for 20 % tolerance, change to "0".



Solid Tantalum Chip Capacitors,
MIDGET[®], Conformal Coated

Vishay Sprague

STANDARD/EXTENDED RATINGS				
CAPACITANCE (μ F)	CASE CODE	PART NUMBER (1)	MAX. DCL AT + 25 °C (μ A)	MAX. DF AT + 25 °C 120 Hz (%)
15 WV_{DC} AT + 85 °C, SURGE = 20 V . . . 10 WV_{DC} AT + 125 °C, SURGE = 12 V				
0.68	A	194D684X_015A2	0.5	4
1.0	A	194D105X_015A2	0.5	4
1.0	B	194D105X_015B2	0.5	4
1.5	A	194D155X_015A2	0.5	6
1.5	B	194D155X_015B2	0.5	6
2.2	A	194D225X_015A2	0.5	6
2.2	B	194D225X_015B2	0.5	6
2.2	C	194D225X_015C2	0.5	6
3.3	C	194D335X_015C2	0.5	6
3.3	D	194D335X_015D2	0.5	6
4.7	D	194D475X_015D2	0.7	6
4.7	E	194D475X_015E2	0.7	6
6.8	E	194D685X_015E2	1.1	6
6.8	F	194D685X_015F2	1.1	6
10	E	194D106X_015E2	1.6	6
10	F	194D106X_015F2	1.6	6
15	F	194D156X_015F2	2.4	6
15	G	194D156X_015G2	2.4	6
22	F	194D226X_015F2	3.5	6
22	G	194D226X_015G2	3.5	6
33	G	194D336X_015G2	5.3	6
33	H	194D336X_015H2	5.3	6
47	G	194D476X_015G2	10	8
47	H	194D476X_015H2	7.0	6
68	H	194D686X_015H2	10	6
20 WV_{DC} AT + 85 °C, SURGE = 26 V . . . 13 WV_{DC} AT + 125 °C, SURGE = 16 V				
0.47	A	194D474X_020A2	0.5	4
0.68	A	194D684X_020A2	0.5	4
0.68	B	194D684X_020B2	0.5	4
1.0	A	194D105X_020A2	0.5	4
1.0	B	194D105X_020B2	0.5	4
1.5	B	194D155X_020B2	0.5	6
1.5	C	194D155X_020C2	0.5	6
2.2	C	194D225X_020C2	0.5	6
2.2	D	194D225X_020D2	0.5	6
3.3	D	194D335X_020D2	0.7	6
3.3	E	194D335X_020E2	0.7	6
4.7	E	194D475X_020E2	0.9	6
4.7	F	194D475X_020F2	0.9	6
6.8	F	194D685X_020F2	1.4	6
10	E	194D106X_020E2	2.0	6
10	F	194D106X_020F2	2.0	6
10	G	194D106X_020G2	2.0	6
15	F	194D156X_020F2	3.0	6
15	G	194D156X_020G2	3.0	6
22	G	194D226X_020G2	4.0	8
22	H	194D226X_020H2	4.4	6
33	H	194D336X_020H2	6.6	6

Note

(1) For 10 % tolerance, specify "9"; for 20 % tolerance, change to "0".

STANDARD/EXTENDED RATINGS				
CAPACITANCE (μ F)	CASE CODE	PART NUMBER (1)	MAX. DCL AT + 25 °C (μ A)	MAX. DF AT + 25 °C 120 Hz (%)
25 WV_{DC} AT + 85 °C, SURGE = 32 V . . . 17 WV_{DC} AT + 125 °C, SURGE = 20 V				
0.33	A	194D334X_025A2	0.5	4
0.47	A	194D474X_025A2	0.5	4
0.47	B	194D474X_025B2	0.5	4
0.68	B	194D684X_025B2	0.5	4
1.0	C	194D105X_025C2	0.5	4
1.5	D	194D155X_025D2	0.5	6
2.2	E	194D225X_025E2	0.6	6
3.3	F	194D335X_025F2	0.8	6
4.7	F	194D475X_025F2	1.2	6
6.8	F	194D685X_025F2	1.7	6
6.8	G	194D685X_025G2	1.7	6
10	F	194D106X_025F2	2.5	6
10	G	194D106X_025G2	2.5	6
15	H	194D156X_025H2	3.8	6
22	H	194D226X_025H2	5.5	6
33	H	194D336X_025H2	10	8
35 WV_{DC} AT + 85 °C, SURGE = 46 V . . . 23 WV_{DC} AT + 125 °C, SURGE = 28 V				
0.10	A	194D104X_035A2	0.5	4
0.15	A	194D154X_035A2	0.5	4
0.22	A	194D224X_035A2	0.5	4
0.33	B	194D334X_035B2	0.5	4
0.47	B	194D474X_035B2	0.5	4
0.68	C	194D684X_035C2	0.5	4
1.0	D	194D105X_035D2	0.5	4
1.5	E	194D155X_035E2	0.5	6
2.2	F	194D225X_035F2	0.8	6
3.3	F	194D335X_035F2	1.2	6
4.7	F	194D475X_035F2	1.6	6
4.7	G	194D475X_035G2	1.6	6
6.8	G	194D685X_035G2	2.4	6
6.8	H	194D685X_035H2	2.4	6
10	G	194D106X_035G2	3.5	6
10	H	194D106X_035H2	3.5	6
15	H	194D156X_035H2	5.3	6
50 WV_{DC} AT + 85 °C, SURGE = 65 V . . . 33 WV_{DC} AT + 125 °C, SURGE = 38 V				
0.10	A	194D104X_050A2	0.5	4
0.15	A	194D154X_050A2	0.5	4
0.22	B	194D224X_050B2	0.5	4
0.33 (2)	B	194D334X_050B2	0.5	4
0.47	C	194D474X_050C2	0.5	4
0.68	D	194D684X_050D2	0.5	4
1.0	E	194D105X_050E2	0.5	4
1.5	F	194D155X_050F2	0.8	6
2.2	F	194D225X_050F2	1.1	6
3.3	G	194D335X_050G2	1.7	6
4.7	H	194D475X_050H2	2.4	6
6.8	H	194D685X_050H2	3.4	6

Notes

(1) For 10 % tolerance, specify "9"; for 20 % tolerance, change to "0".

(2) 5 % tolerance is not available for the 0.33 μ F/50 V design



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.