


Class H(K), J and R Fuseblocks



Porcelain Type Fuseblocks


Class H(K) and R Dimensions

Agency Approvals: UL Listed

Class H and K Dimension Fuseblocks - Porcelain Type

Volts	Amps	Poles	Fuseblocks		
			Terminal Type		
			Pressure	Screw	Box Lug
250	1/10	1	—	2601	—
	to	2	—	2604	—
	30	3	—	2607	—
	31	1	—	—	2602
	to	2	—	—	2605
	60	3	—	—	2608
600	1/10	1	—	2610	—
	30	1	—	—	2611
	31	1	—	—	2611
	to	1	—	—	2611
	60	1	—	—	2611
	60	1	—	—	2611

CE CE logo denotes compliance with European Union Low Voltage Directive (50-1000V AC, 75-1500V DC). Refer to BIF document #8002 or contact Bussmann Application Engineering at 636-527-1270 for more information.



Modular Type Fuseblocks

Class H & J Fuses

Reinforced retaining clips standard

Available in 30A and 60A, 3-pole models only.

Agency Approvals: UL Recognized, Guide IZLT2, File E14853

CSA Certified, Class 6225-01, File 47235

Modular Type For Class H & J Fuses

Fuse Type	Volts	Amps	Catalog Number	
			Screw	Pressure
H	250	60	11241-3SR	11241-3PR
			11242-3SR	11242-3PR
		600	30	11241-3SR
	11242-3SR			11242-3PR
	600		60	11239-3SR
		11240-3SR		11240-3PR
J		600	30	11241-3SR
	60		11239-3SR	11239-3PR

Note: Order two blocks per fuse (matched or mixed.)

CE CE logo denotes compliance with European Union Low Voltage Directive (50-1000V AC, 75-1500V DC). Refer to BIF document #8002 or contact Bussmann Application Engineering at 636-527-1270 for more information.

