

In-Line Fuseholders




HR and HM Series In-Line Fuseholders for SFE and 1/4" x Various Length Fuses

Voltage Ratings: 32V, 20A
No agency listings.

Electrical Ratings		Wire
Catalog Symbol	Includes Fuse	
HRJ*	SFE-20	
HRJ	SFE-14	
HRH	SFE-9	19" of #14
HRF	SFE-7 1/2	
HRG	SFE-6	
HRF	SFE-4	
HMJ**	SFE-20	
HMH	SFE-14	
HMH	SFE-9	8" of #14
HME	SFE-7 1/2	
HMG	SFE-6	
HMF	SFE-4	

*Also available as in-line fuseholder only with lead wire contacts.
HRJ LEST-Fuse.
**Also available as in-line fuseholder only with lead wire contacts.
HMJ LEST-Fuse.

HHJ-A For 1/2" x 1 1/2" fuse, no wire or fuse included, accepts #18 - #22 wire.
HHJ-B For 1/2" x 1 1/2" fuse, no wire or fuse included, accepts #12 - #16 wire.
HHJ-B For 1/2" x 1 1/2" fuse, no wire or fuse included, accepts #12 - #10 wire.



Dimensional Data




HFA Series In-Line Waterproof Fuseholders for 1/2" x 1 1/2" Fuses

Construction:
Body - Phenolic;
Contacts - Copper crimp leads
Voltage Rating: 250V, 20A
Agency Information:
UL Recognized, (Guide IZLT2,
File E14853)
UL Flammability Rating: 94V0

Electrical Ratings		Terminals
Catalog Symbol	Amps	Volts
HFA	20	250
HFA-HH*	20	250
		1/2" O.C.

*No UL Recognition.

Dimensional Data



CE logo denotes compliance with European Union Low Voltage Directive (50-1000V ac, 75-1500V dc). Refer to Data Sheet: 8002 or contact Bussmann Application Engineering at 636-527-1270 for more information.



HHT Series In-Line Fuseholders for 5 x 15mm or 5 x 20mm Fuses

Construction:
Body - Black Thermoplastic
Contacts - Brass
Wire - 16 awg, red

Electrical Ratings	
Amps	Volts
5 x 15mm	5
5 x 20mm	10
	32

Dimensional Data

