




Semiconductor Fuse

20-100A, 700 Volts

Bussmann

BIF Document
35785291
Size 22x58



Pre-Arcing

Time-Current Characteristic Curves

FWP 20A22F-100A22F

Approved: **NN**

Page **1 of 2**

Rev. Date: **SEPT-97**

Pub. Date: **JAN-98**

COOPER Bussmann
1-17-01 SB00233

BUSSMANN
P.O. Box 14460
St. Louis, MO 63178-4460
U.S.A.
Phone: 636-394-2877
Fax: 800-544-2570
Int'l Fax: 636-527-1413

BUSSMANN U.K.
Burton-on-the-Wolds
Leicestershire LE12 5TH
England
Phone: 44-1509-882737
Fax: 44-1509-882786

BUSSMANN DENMARK
5 Litterbuen
DK-2740 Skovlunde
Copenhagen, Denmark
Phone: 45-4485-0900
Fax: 45-4485-0901

Bussmann reserves the right without notice to change design and/or discontinue distribution of this product.




Semiconductor Fuse

20-100A, 700 Volts

BIF Document
35785291
 Size **22x58**



Bussmann



Peak Let-Through Cut-Off Current Characteristic Curves
FWP 20A22F-100A22F

Approved: **NN**
 Rev. Date: **SEPT-97**

Page **2 of 2**
 Pub. Date: **JAN-98**