

## E-Rated Fuses for Trans. &amp; Feeder Protection

## Specifications

Buss Catalog No.	Amperage	Maximum Design Voltage	Construction	Maximum Interrupting Capacity		Dimensions	
				Amps. (Asym.)	Amps. (Sym.)	Length	Diameter
<b>5500V, E-Rated; Indoor/Enclosure</b>							
JCU-10E	10E	5500V	Single	80,000	50,000	17.81" (452.4mm)	3" (76.2mm)
JCU-15E	15E	5500V	Single	80,000	50,000	12.88" (327.0mm)	2.1" (53.34mm)
JCU-20E	20E	5500V	Single	80,000	50,000		
JCU-25E	25E	5500V	Single	80,000	50,000	15.88" (403.2mm)	3" (76.2mm)
JCU-30E	30E	5500V	Single	100,000	63,000		
JCU-40E	40E	5500V	Single	100,000	63,000		
JCU-50E	50E	5500V	Single	100,000	63,000	17.88" (454.15mm)	3" (76.20mm)
JCU-65E	60E	5500V	Single	100,000	63,000		
JCU-80E	80E	5500V	Single	100,000	63,000	28.81" (731.77mm)	4" (101.60mm)
JCU-100E	100E	5500V	Single	100,000	63,000		
JCU-125E	125E	5500V	Single	100,000	63,000		
JCU-150E	150E	5500V	Single	100,000	63,000	17.88" (454.15mm)	3" (76.20mm)
JCU-175E	175E	5500V	Single	100,000	63,000		
JCU-200E	200E	5500V	Single	100,000	63,000	15.88" (398.95mm)	2.1" (53.34mm)
JCU-250E	250E	5500V	Single	100,000	63,000		
JCU-300E	300E	5500V	Double	100,000	63,000	17.88" (454.15mm)	3" (76.2mm)
JCU-350E	350E	5500V	Double	100,000	63,000		
JCU-400E	400E	5500V	Double	100,000	63,000	28.81" (731.77mm)	4" (101.60mm)
JCU-450E	450E	5500V	Double	100,000	63,000		
JCU-600E	600E	5500V	Double*	80,000	50,000	15.88" (398.95mm)	2.1" (53.34mm)
JCU-750E	750E	5500V	Double*	80,000	50,000		
<b>8300V, E-Rated; Indoor/Enclosure</b>							
JCZ-15E	15E	8300V	Single	80,000	50,000	15.88" (398.95mm)	2.1" (53.34mm)
JCZ-20E	20E	8300V	Single	80,000	50,000		
JCZ-25E	25E	8300V	Single	80,000	50,000	17.88" (454.15mm)	3" (76.2mm)
JCZ-30E	30E	8300V	Single	80,000	50,000		
JCZ-40E	40E	8300V	Single	80,000	50,000		
JCZ-50E	50E	8300V	Single	80,000	50,000	17.88" (454.15mm)	3" (76.2mm)
JCZ-65E	65E	8300V	Single	80,000	50,000		
JCZ-80E	80E	8300V	Single	80,000	50,000	15.88" (398.95mm)	2.1" (53.34mm)
JCZ-100E	100E	8300V	Single	80,000	50,000		
JCZ-125E	125E	8300V	Single	80,000	50,000	15.88" (398.95mm)	2.1" (53.34mm)
JCZ-150E	150E	8300V	Single	80,000	50,000		
JCZ-200E	200E	8300V	Double	80,000	50,000	15.88" (398.95mm)	2.1" (53.34mm)
JCZ-25E	25E	8300V	Single	80,000	50,000		
JCZ-30E	30E	8300V	Single	80,000	50,000	15.88" (398.95mm)	2.1" (53.34mm)
JCZ-40E	40E	8300V	Single	80,000	50,000		
JCZ-50E	50E	8300V	Single	80,000	50,000		
JCZ-65E	65E	8300V	Single	80,000	50,000	15.88" (398.95mm)	2.1" (53.34mm)
JCZ-80E	80E	8300V	Single	80,000	50,000		
JCZ-100E	100E	8300V	Double	80,000	50,000	15.88" (398.95mm)	2.1" (53.34mm)
JCZ-125E	125E	8300V	Double	80,000	50,000		

Recommended Fuse Clips: 3" - 1A0065; 90789A67304, A9354730

**General Notes:**

- All fuses are fitted with a striker pin which can be used for indication or tripping purposes.
  - The fuses are suitable for use either indoors or outdoors.
  - These fuses are interchangeable with corresponding fuses produced by most other leading North American manufacturers.
- Contact Bussmann for the latest product information on E-Rated Fuses for Transformer and feeder protection.

\* Bolt on mounting

