

One-Time General Purpose Fuses

250 and 600 Volts, 1/8 to 600 Amps

NON and NOS



Catalog Symbol: NON (250V); NOS (600V)
 For general purpose application
 Ampere Rating: 1/8 to 600A
 Voltage Rating: NON: 250Vac, 125Vdc (0-100A);
 NOS: 600Vac
 Non-Current-Limiting
 Interrupting Rating: 50,000A RMS Sym. (0-60A),
 10,000A RMS Sym. (65-600A), 50,000A @ 125Vdc (NON 0-60),
 10,000A @ 125Vdc (NON 65-100A)
Agency Information:
 UL Listed - 250V: Class K5 (0-60A), Std. 248-9
 Class H (65-600A), Std. 248-6
 (125Vdc: NON 0-100)
 600V: Class K5 (0-60A), Std. 248-9
 Class H (70-600A), Std. 248-6
 UL Guide JDDZ, File E4274
 CSA Certified, Class 1421-01, File 53787 (0-12 & 65-600A)† 250V
 (0-600A) 600V

Catalog Numbers—NON ONE-TIME (250Vac)

| | | | |
|------------|-----------|---------|---------|
| NON-1/8 | NON-5 | NON-40 | NON-175 |
| NON-1/2 | NON-6 | NON-45 | NON-200 |
| NON-3/4 | NON-6 1/4 | NON-50 | NON-225 |
| NON-9/10 | NON-7 | NON-60 | NON-250 |
| NON-1 | NON-8 | NON-65 | NON-300 |
| NON-1 1/4 | NON-9 | NON-70 | NON-350 |
| NON-1 1/2 | NON-10 | NON-75 | NON-400 |
| NON-1 9/10 | NON-12 | NON-80 | NON-450 |
| NON-2 | NON-15 | NON-90 | NON-500 |
| NON-2 1/2 | NON-20 | NON-100 | NON-600 |
| NON-3 | NON-25 | NON-110 | — |
| NON-3 3/10 | NON-30 | NON-125 | — |
| NON-4 | NON-35 | NON-150 | — |


Carton Quantity and Weight—NON ONE-TIME (250Vac)

| Catalog Number | Carton Qty. | Weight** | |
|----------------|-------------|----------|-------|
| | | Lbs. | Kg. |
| NON 1/8-30 | 10 | 0.38 | 0.172 |
| NON 35-60 | 10 | 1.00 | 0.453 |
| NON 65-100 | 5 | 0.79 | 0.358 |
| NON 110-200 | 1 | 0.79 | 0.358 |
| NON 225-400 | 1 | 1.65 | 0.748 |
| NON 450-600 | 1 | 2.76 | 1.251 |

NON -(1/8-60) is rated at 125Vdc with 50,000 AIC Rating.
 NON -(65-100) is rated at 125Vdc with 10,000 AIC Rating.

**Weight per carton.


† For CSA Certified 15-60A Ratings, see PON Data Sheet: 4126



Recommended fuseblocks for
 Class H & K5, 250V & 600V fuses
 See Data Sheets: 1112 (250V) and
 1113 (600V)

Dimensions

All diameters (± 0.008)



General Information:

- Protect lighting, heating and other circuits not subject to temporary surges and where available short-circuit currents are relatively low.
- ONE-TIME fuses do not have any appreciable degree of time-delay and thus should not be specified in circuits where large transients or motor overloads occur. Use Buss FUSETRON® or LOW-PEAK® dual-element, time-delay fuses.
- For general purpose circuits, size at ampere rating of circuit.
- For motor circuits, size at 300% to 400%.

Catalog Numbers—NOS ONE-TIME (600Vac)

| | | | |
|--------|--------|---------|---------|
| NOS-1 | NOS-12 | NOS-70 | NOS-225 |
| NOS-2 | NOS-15 | NOS-75 | NOS-250 |
| NOS-3 | NOS-20 | NOS-80 | NOS-300 |
| NOS-4 | NOS-25 | NOS-90 | NOS-350 |
| NOS-5 | NOS-30 | NOS-100 | NOS-400 |
| NOS-6 | NOS-35 | NOS-110 | NOS-450 |
| NOS-7 | NOS-40 | NOS-125 | NOS-500 |
| NOS-8 | NOS-45 | NOS-150 | NOS-600 |
| NOS-9 | NOS-50 | NOS-175 | — |
| NOS-10 | NOS-60 | — | — |

Carton Quantity and Weight—NOS ONE-TIME (600Vac)

| Catalog Number | Carton Qty. | Weight** | |
|----------------|-------------|----------|-------|
| | | Lbs. | Kg. |
| NOS 1-30 | 10 | 1.45 | 0.657 |
| NOS 35-60 | 10 | 2.6 | 1.179 |
| NOS 70-100 | 5 | 2.80 | 1.270 |
| NOS 110-200 | 1 | 1.24 | 0.562 |
| NOS 225-400 | 1 | 3.03 | 1.374 |
| NOS 450-600 | 1 | 4.63 | 2.100 |


**Weight per carton.

CE logo denotes compliance with European Union Low Voltage Directive (50-1000Vac, 75-1500Vdc). Refer to Data Sheet: 8002 or contact Bussmann Application Engineering at 636-527-1270 for more information. Applies to OPM-1038 and OPM-1038R.

One-Time General Purpose Fuses

250 and 600 Volts, $\frac{1}{8}$ to 600 Amps

NON and NOS



The only controlled copy of this Data Sheet is the electronic read-only version located on the Bussmann Network Drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.