

Common Mode Filters(SMD) For Power Line

Conformity to RoHS Directive

ACM Series ACM4520 Type

FEATURES

- Several large current products are prepared to correspond to the various applications.
- Low profile and compact shape, it is suited for surface mounting.
- It shows high common-mode impedance despite of its compact shape.

APPLICATIONS

Radiation noise suppression for power line (DVC, DVD cam, DSC, etc.)


TEMPERATURE RANGE

Operating	-40 to +85°C
-----------	--------------

PACKAGING STYLE AND QUANTITIES

Packaging style	Reel	Quantity
Reel	ø180mm	800 pieces/reel
Taping	ø330mm	2500 pieces/reel

SHAPES AND DIMENSIONS




PRODUCT IDENTIFICATION

ACM	4520	-	901	-	2P	-	T	-	□□□
(1)	(2)	(3)	(4)	(5)	(6)				


- (1) Series name
- (2) Dimensions W×T
4520: 4.5×2.0mm
- (3) Impedance [at 100MHz]
901: 900Ω
142: 1400Ω
- (4) Numbers of lines
2P: 2-line
- (5) Packaging style
T: ø180mm reel taping
TL: ø330mm reel taping
B: Bulk
- (6) TDK internal code

CIRCUIT DIAGRAM



• No polarity

RECOMMENDED PC BOARD PATTERN



- Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

- All specifications are subject to change without notice.


ELECTRICAL CHARACTERISTICS

Part No.	Common mode impedance (Ω)[at 100MHz]		DC resistance (Ω)max. [1 line]	Rated current I_{dc} (A)max.	Rated voltage E_{dc} (V)max.	Insulation resistance ($M\Omega$)min.
	min.	typ.				
ACM4520-901-2P	650	900	0.06	2.0	50	10
ACM4520-142-2P	1000	1400	0.08	1.5	50	10

TYPICAL ELECTRICAL CHARACTERISTICS

IMPEDANCE vs. FREQUENCY CHARACTERISTICS

ACM4520-901-2P



ACM4520-142-2P

